

## Compact cylinders ADN/AEN, to ISO 21287

**FESTO**



Festo Core Range  
Solves the majority of your automation tasks

Worldwide:  
Simply good:  
Fast:

Quickest delivery – wherever, whenever  
Expected high Festo quality  
Easy and fast to select

With the Festo Core Range, we have selected the most important products and functions from our broad product catalogue, and added the quickest delivery.

The Core Range offers you the best value for your automation tasks.

Just look  
for the  
star!


## Key features

### At a glance

Sensor slots on three sides for flush mounting of proximity switches

Piston rod with choice of male or female thread

Mounting option:  
Female thread and through-hole



Centring hole in the end cap suitable for centring pins ZBS

Magnet for contactless position sensing

Integrated cushioning for absorbing residual energy

### More than the standard

- The compact cylinders comply with or are based on the ISO 21287 standard, depending on the piston diameter
- The ADN/AEN is characterised by its compact design and wide range of application thanks to the large number of variants
- The variants can be configured using a modular product system

### Powerful

- Integrated cushioning for absorbing residual energy
- Long service life thanks to exceptional cushioning characteristics and low friction values

### Convenient

- Easy to mount with a comprehensive range of mounting accessories for just about every type of installation
- Highly flexible thanks to the wide range of variants
- Contactless position sensing using proximity switches

### Reliable

- Optimised manufacturing methods, patented technology and more than 40 years of experience in the field of cylinders make Festo and ADN/AEN a great partner

### Cushioning types

#### Cushioning P

#### Operating mode

- The drive is fitted with polymer elastic end-position cushioning

#### Application

- Small loads
- Low speeds
- Small cushioning capacity

#### Advantages

- No adjustment required
- Saves time

#### Cushioning PPS

#### Operating mode

- The drive has self-adjusting, pneumatic end-position cushioning

#### Application


- Larger loads
- Higher speeds
- Larger cushioning capacity

#### Advantages

- No adjustment required
- Cushioning capacity is four times bigger than ADN-...-P
- Saves time
- Reduces noise

### Cushioning capacity of ISO 21287 and ISO 15552

The cushioning capacity of the compact cylinder ADN-...-PPS fills the gap between ADN-...-P and standards-based cylinders to ISO 15552.



### For manufacturing lithium-ion batteries

















#### ADN-...-F1A

Recommended for production systems for manufacturing lithium-ion batteries. Metals with copper, zinc or nickel as the main constituent are excluded from use. Exceptions are nickel in steels, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.










#### Accessories

Please contact your Festo representative for information on which accessories are suitable for manufacturing lithium-ion batteries

## Key features

| Variants from the modular product system                                            |                                                                               |                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symbol                                                                              | Key features                                                                  | Description                                                                                                                                                                                                                                                                    |
|    | S1 Reinforced piston rod                                                      | Increased lateral loads. Absorbs many times more lateral load than a basic cylinder                                                                                                                                                                                            |
|    | S2 Through piston rod                                                         | The piston rod can be used for attachment at both ends of the cylinder                                                                                                                                                                                                         |
|    | S6 Heat-resistant seals                                                       | Temperature resistance up to max. 120°C                                                                                                                                                                                                                                        |
|    | S10 Constant motion (slow speed) at low piston speeds                         | <ul style="list-style-type: none"> <li>• Break-away pressure: very low</li> <li>• Dynamic response: suitable for very slow, constant and stick-slip-free movements</li> </ul> Application example: slow, constant feed motion                                                  |
|    | S11 Low friction                                                              | <ul style="list-style-type: none"> <li>• Break-away pressure: very low</li> <li>• Dynamic response: especially suitable for slow movements with considerably reduced system friction</li> <li>• Application example: slow applications where standstill is critical</li> </ul> |
|    | S20 Through, hollow piston rod                                                | The piston rod can be used for attachment at both ends of the cylinder. The piston rod is hollow inside. This means it can be used to carry vacuum or compressed air                                                                                                           |
|    | K2 Extended male piston rod thread                                            | –                                                                                                                                                                                                                                                                              |
|   | K5 Custom piston rod thread                                                   | Metric standard thread to ISO                                                                                                                                                                                                                                                  |
|  | K8 Extended piston rod                                                        | –                                                                                                                                                                                                                                                                              |
|  | K10 Smooth anodised aluminium piston rod                                      | Ideal for use in welding environments: <ul style="list-style-type: none"> <li>• Protection against welding spatter</li> <li>• Small moving masses</li> <li>• Harder surface compared to steel</li> <li>• Long service life</li> </ul>                                          |
|  | KP With clamping unit                                                         | Integrated clamping unit on the piston rod                                                                                                                                                                                                                                     |
|  | EL With end-position locking                                                  | Positive locking in the end position as a drop guard. If there is a drop in pressure, the cylinder is secured in its end position to prevent it from dropping                                                                                                                  |
|  | Q Square piston rod                                                           | Protection against rotation. For position-oriented feeding                                                                                                                                                                                                                     |
|  | R3 High corrosion protection                                                  | All external cylinder surfaces comply with corrosion resistance class 3 to Festo standard 940 070. The piston rod is made from corrosion- and acid-resistant steel                                                                                                             |
|  | R8 Dust protection with wiper seal                                            | The cylinder has a hard-chrome-plated piston rod and a hard wiper seal, which protects against dry, dusty media                                                                                                                                                                |
|  | TL Captive rating plate                                                       | Laser-etched rating plate. Easy to identify spare parts, even after years in a harsh environment                                                                                                                                                                               |
|  | TT Low temperature                                                            | Temperature resistance down to max. -40°C                                                                                                                                                                                                                                      |
|  | F1A Recommended for production plants for manufacturing lithium-ion batteries | Cylinders free of copper, zinc and nickel ( $\leq 1\%$ )                                                                                                                                                                                                                       |





Product range overview

| Function                                                                            | Version                                                                             | Type                                     | Piston $\varnothing$ | Stroke                                        | Position sensing | Recommended for production systems for manufacturing lithium-ion batteries | Cushioning |     |                      |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|----------------------|-----------------------------------------------|------------------|----------------------------------------------------------------------------|------------|-----|----------------------|
|                                                                                     |                                                                                     |                                          | [mm]                 | [mm]                                          |                  |                                                                            | A          | F1A | P                    |
| Double-acting                                                                       | <b>Basic version</b>                                                                |                                          |                      |                                               |                  |                                                                            |            |     |                      |
|                                                                                     |    | ADN                                      | 12                   | 5, 10, 15, 20, 25, 30, 35, 40, 50, 60         | 1 ... 300        | ■                                                                          | ■          | ■   | ■<br>∅ 20<br>... 100 |
|                                                                                     |                                                                                     |                                          | 16                   | 5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70     | 1 ... 300        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 20                   | 5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70     | 1 ... 300        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 25                   | 5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80 | 1 ... 300        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 32, 40, 50           | 5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80 | 1 ... 400        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 63                   | 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80    | 1 ... 400        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 80, 100              | 10, 15, 20, 25, 30, 40, 50, 60, 80            | 1 ... 500        |                                                                            |            |     |                      |
|                                                                                     | 125                                                                                 | –                                        | 1 ... 500            |                                               |                  |                                                                            |            |     |                      |
|                                                                                     |  | ADN...-S2<br>Through piston rod          | 12, 16, 20, 25       | –                                             | 1 ... 300        | ■                                                                          | ■          | ■   | ■<br>∅ 20<br>... 100 |
|                                                                                     |                                                                                     |                                          | 32, 40, 50, 63       | –                                             | 1 ... 400        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 80, 100, 125         | –                                             | 1 ... 500        |                                                                            |            |     |                      |
|                                                                                     |  | ADN...-S20<br>Through, hollow piston rod | 16, 20, 25           | –                                             | 1 ... 300        | ■                                                                          | –          | ■   | ■<br>∅ 20<br>... 100 |
|                                                                                     |                                                                                     |                                          | 32, 40, 50, 63       | –                                             | 1 ... 400        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 80, 100, 125         | –                                             | 1 ... 500        |                                                                            |            |     |                      |
|                                                                                     | <b>Reinforced piston rod</b>                                                        |                                          |                      |                                               |                  |                                                                            |            |     |                      |
|                                                                                     |  | ADN...-S1                                | 25                   | –                                             | 5 ... 300        | ■                                                                          | –          | ■   | –                    |
|                                                                                     |                                                                                     |                                          | 40, 63               | –                                             | 10 ... 400       |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 100                  | –                                             | 10 ... 500       |                                                                            |            |     |                      |
|                                                                                     | <b>Protected against rotation with square piston rod</b>                            |                                          |                      |                                               |                  |                                                                            |            |     |                      |
|                                                                                     |  | ADN...-Q                                 | 12, 16, 20, 25       | –                                             | 1 ... 300        | ■                                                                          | –          | ■   | –                    |
|                                                                                     |                                                                                     |                                          | 32, 40, 50, 63       | –                                             | 1 ... 400        |                                                                            |            |     |                      |
|                                                                                     |                                                                                     |                                          | 80, 100, 125         | –                                             | 1 ... 500        |                                                                            |            |     |                      |
|  | ADN...-Q-S2<br>Through piston rod                                                   | 12, 16, 20, 25                           | –                    | 1 ... 300                                     | ■                | –                                                                          | ■          | –   |                      |
|                                                                                     |                                                                                     | 32, 40, 50, 63                           | –                    | 1 ... 400                                     |                  |                                                                            |            |     |                      |
|                                                                                     |                                                                                     | 80, 100, 125                             | –                    | 1 ... 500                                     |                  |                                                                            |            |     |                      |
|  | ADN...-Q-S20<br>Through, hollow piston rod                                          | 16, 20, 25                               | –                    | 1 ... 200                                     | ■                | –                                                                          | ■          | –   |                      |
|                                                                                     |                                                                                     | 32, 40, 50, 63                           | –                    | 1 ... 300                                     |                  |                                                                            |            |     |                      |
|                                                                                     |                                                                                     | 80, 100, 125                             | –                    | 1 ... 400                                     |                  |                                                                            |            |     |                      |
| <b>Standard hole pattern, with clamping unit</b>                                    |                                                                                     |                                          |                      |                                               |                  |                                                                            |            |     |                      |
|  | ADN...-KP                                                                           | 20, 25                                   | –                    | 10 ... 300                                    | ■                | –                                                                          | ■          | –   |                      |
|                                                                                     |                                                                                     | 32, 40, 50, 63                           | –                    | 10 ... 400                                    |                  |                                                                            |            |     |                      |
|                                                                                     |                                                                                     | 80, 100                                  | –                    | 10 ... 500                                    |                  |                                                                            |            |     |                      |
| <b>Standard hole pattern, with end-position locking</b>                             |                                                                                     |                                          |                      |                                               |                  |                                                                            |            |     |                      |
|  | ADN...-EL                                                                           | 20, 25                                   | –                    | 10 ... 300                                    | ■                | –                                                                          | ■          | –   |                      |
|                                                                                     |                                                                                     | 32, 40, 50, 63                           | –                    | 10 ... 400                                    |                  |                                                                            |            |     |                      |
|                                                                                     |                                                                                     | 80, 100                                  | –                    | 10 ... 500                                    |                  |                                                                            |            |     |                      |

## Product range overview

| Type                                                     | Male piston rod thread | Female piston rod thread | Extended male piston rod thread | Custom piston rod thread | Extended piston rod | Smooth anodised piston rod | Heat-resistant seals max. 120°C | Slow speed (constant motion) | Low friction | High corrosion protection | Dust protection | Low temperature      | → Page/Internet |
|----------------------------------------------------------|------------------------|--------------------------|---------------------------------|--------------------------|---------------------|----------------------------|---------------------------------|------------------------------|--------------|---------------------------|-----------------|----------------------|-----------------|
|                                                          | A                      | I                        | K2                              | K5                       | K8                  | K10                        | S6                              | S10                          | S11          | R3                        | R8              | TT                   |                 |
| <b>Basic version</b>                                     |                        |                          |                                 |                          |                     |                            |                                 |                              |              |                           |                 |                      |                 |
| <b>ADN</b>                                               | ■                      | ■                        | ■                               | ■                        | ■                   | ■<br>from Ø 20             | ■                               | ■                            | ■            | ■                         | ■<br>from Ø 20  | ■<br>Ø 20<br>... 100 | 13              |
| <b>ADN-...-S2</b><br>Through piston rod                  | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | -                         | -               | ■<br>Ø 20<br>... 100 | 13              |
| <b>ADN-...-S20</b><br>Through, hollow piston rod         | ■                      | -                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | -                         | -               | -                    | 13              |
| <b>Reinforced piston rod</b>                             |                        |                          |                                 |                          |                     |                            |                                 |                              |              |                           |                 |                      |                 |
| <b>ADN-...-S1</b>                                        | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | ■                         | -               | -                    | 13              |
| <b>Protected against rotation with square piston rod</b> |                        |                          |                                 |                          |                     |                            |                                 |                              |              |                           |                 |                      |                 |
| <b>ADN-...-Q</b>                                         | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | -                         | -               | -                    | 13              |
| <b>ADN-...-Q-S2</b><br>Through piston rod                | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | -                         | -               | -                    | 13              |
| <b>ADN-...-Q-S20</b><br>Through, hollow piston rod       | ■                      | -                        | ■                               | ■                        | ■                   | -                          | ■                               | -                            | -            | -                         | -               | -                    | 13              |
| <b>Standard hole pattern, with clamping unit</b>         |                        |                          |                                 |                          |                     |                            |                                 |                              |              |                           |                 |                      |                 |
| <b>ADN-...-KP</b>                                        | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | -                               | -                            | -            | -                         | -               | -                    | 42              |
| <b>Standard hole pattern, with end-position locking</b>  |                        |                          |                                 |                          |                     |                            |                                 |                              |              |                           |                 |                      |                 |
| <b>ADN-...-EL</b>                                        | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | -                               | -                            | -            | -                         | -               | -                    | 51              |




Product range overview

| Function                                                                            | Version                                                                           | Type                               | Piston $\varnothing$    | Stroke                                | Position sensing | Cushioning |       |                      |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------|-------------------------|---------------------------------------|------------------|------------|-------|----------------------|
|                                                                                     |                                                                                   |                                    | [mm]                    |                                       |                  | [mm]       | Fixed | Self-adjusting       |
|                                                                                     |                                                                                   |                                    |                         |                                       | A                | P          | PPS   |                      |
| Double-acting                                                                       | <b>Standard hole pattern, non-rotating with yoke</b>                              |                                    |                         |                                       |                  |            |       |                      |
|                                                                                     |  | ADNGF                              | 12                      | 5, 10, 15, 20, 25, 30, 40             | 1 ... 200        | ■          | ■     | ■<br>∅ 20<br>... 100 |
|                                                                                     |                                                                                   |                                    | 16                      | 5, 10, 15, 20, 25, 30, 40, 50         | 1 ... 200        |            |       |                      |
|                                                                                     |                                                                                   |                                    | 20, 25                  | 5, 10, 15, 20, 25, 30, 40, 50, 60     | 3 ... 200        |            |       |                      |
|                                                                                     |                                                                                   |                                    | 32, 40, 50              | 5, 10, 15, 20, 25, 30, 40, 50, 60, 80 | 5 ... 300        |            |       |                      |
|                                                                                     |                                                                                   |                                    | 63, 80                  | 10, 15, 20, 25, 30, 40, 50, 60, 80    | 5 ... 300        |            |       |                      |
|                                                                                     |                                                                                   |                                    | 100                     | 10, 15, 20, 25, 30, 40, 50, 60, 80    | 5 ... 400        |            |       |                      |
|                                                                                     |  | ADNGF-...-S2<br>Through piston rod | 12, 16                  | -                                     | 1 ... 200        | ■          | ■     | ■<br>∅ 20<br>... 100 |
|                                                                                     |                                                                                   |                                    | 20, 25                  |                                       | 3 ... 200        |            |       |                      |
|                                                                                     |                                                                                   |                                    | 32, 40, 50, 63, 80, 100 |                                       | 5 ... 250        |            |       |                      |
|                                                                                     |                                                                                   |                                    |                         |                                       |                  |            |       |                      |
|                                                                                     | <b>Standard hole pattern, high-force cylinder</b>                                 |                                    |                         |                                       |                  |            |       |                      |
|                                                                                     |  | ADNH                               | 25                      | -                                     | 1 ... 150        | ■          | ■     | -                    |
|                                                                                     |                                                                                   |                                    | 40                      |                                       |                  |            |       |                      |
|                                                                                     |                                                                                   |                                    | 63                      |                                       |                  |            |       |                      |
| 100                                                                                 |                                                                                   |                                    |                         |                                       |                  |            |       |                      |
| <b>Standard hole pattern, multi-position cylinder</b>                               |                                                                                   |                                    |                         |                                       |                  |            |       |                      |
|  | ADNM                                                                              | 25                                 | -                       | 1 ... 2 000                           | ■                | ■          | -     |                      |
|                                                                                     |                                                                                   | 40                                 |                         |                                       |                  |            |       |                      |
|                                                                                     |                                                                                   | 63                                 |                         |                                       |                  |            |       |                      |
|                                                                                     |                                                                                   | 100                                |                         |                                       |                  |            |       |                      |

## Product range overview

| Type                                                  | Male piston rod thread | Female piston rod thread | Extended male piston rod thread | Custom piston rod thread | Extended piston rod | Heat-resistant seals max. 120°C | → Page/Internet |
|-------------------------------------------------------|------------------------|--------------------------|---------------------------------|--------------------------|---------------------|---------------------------------|-----------------|
|                                                       | A                      | I                        | K2                              | K5                       | K8                  | S6                              |                 |
| <b>Standard hole pattern, non-rotating with yoke</b>  |                        |                          |                                 |                          |                     |                                 |                 |
| <b>ADNGF</b>                                          | -                      | -                        | -                               | -                        | -                   | ■                               | adngf           |
| <b>ADNGF-...-S2</b><br>Through piston rod             | -                      | -                        | -                               | -                        | -                   | ■                               | adngf           |
| <b>Standard hole pattern, high-force cylinder</b>     |                        |                          |                                 |                          |                     |                                 |                 |
| <b>ADNH</b>                                           | ■                      | ■                        | ■                               | ■                        | ■                   | ■                               | adnh            |
| <b>Standard hole pattern, multi-position cylinder</b> |                        |                          |                                 |                          |                     |                                 |                 |
| <b>ADNM</b>                                           | ■                      | ■                        | ■                               | ■                        | ■                   | ■                               | adnh            |

Product range overview


| Function                                                                          | Version                                                                           | Type                            | Piston $\varnothing$                | Stroke   | Position sensing | Cushioning |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------|-------------------------------------|----------|------------------|------------|
|                                                                                   |                                                                                   |                                 | [mm]                                | [mm]     | A                | P          |
| Single-acting                                                                     | <b>Basic version</b>                                                              |                                 |                                     |          |                  |            |
|                                                                                   |  | AEN                             | 12                                  | 1 ... 10 | ■                | ■          |
|                                                                                   |                                                                                   |                                 | 16, 20, 25, 32, 40, 50, 63, 80, 100 | 1 ... 25 |                  |            |
|                                                                                   |  | AEN...-Z<br>Pulling             | 12                                  | 1 ... 10 | ■                | ■          |
|                                                                                   |                                                                                   |                                 | 16, 20, 25, 32, 40, 50, 63, 80, 100 | 1 ... 25 |                  |            |
|                                                                                   | <b>Protected against rotation with square piston rod</b>                          |                                 |                                     |          |                  |            |
|  | AEN...-Q                                                                          | 16                              | 1 ... 25                            | ■        | ■                |            |
|                                                                                   |                                                                                   | 20, 25, 32, 40, 50, 63, 80, 100 | 1 ... 25                            |          |                  |            |



## Product range overview

| Type                                                     | Male piston rod thread | Female piston rod thread | Extended male piston rod thread | Custom piston rod thread | Extended piston rod | Smooth anodised piston rod | Heat-resistant seals max. 120°C | → Page/Internet |
|----------------------------------------------------------|------------------------|--------------------------|---------------------------------|--------------------------|---------------------|----------------------------|---------------------------------|-----------------|
|                                                          | A                      | I                        | K2                              | K5                       | K8                  | K10                        | S6                              |                 |
| <b>Basic version</b>                                     |                        |                          |                                 |                          |                     |                            |                                 |                 |
| AEN                                                      | ■                      | ■                        | ■                               | ■                        | ■                   | ■<br>from Ø 20             | ■                               | 61              |
| AEN-...-Z<br>Pulling                                     | ■                      | ■                        | ■                               | ■                        | ■                   | ■<br>from Ø 20             | ■                               | 61              |
| <b>Protected against rotation with square piston rod</b> |                        |                          |                                 |                          |                     |                            |                                 |                 |
| AEN-...-Q                                                | ■                      | ■                        | ■                               | ■                        | ■                   | -                          | ■                               | 61              |

### Peripherals overview



## Peripherals overview

| Mounting attachments and accessories |                                           | Description                                                                                  | → Page/Internet |
|--------------------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------|-----------------|
| [1]                                  | Compact cylinder<br>ADN                   | Double-acting cylinder                                                                       | 13              |
|                                      | Compact cylinder<br>AEN                   | Single acting cylinder                                                                       | 61              |
| [2]                                  | One-way flow control valve<br>GRLA/GRLZ   | For regulating speed                                                                         | 85              |
| [3]                                  | Push-in fitting<br>QS                     | For connecting tubing with standard O.D.                                                     | qs              |
| [4]                                  | Foot mounting<br>HNA                      | For bearing or end caps                                                                      | 74              |
| [5]                                  | Flange mounting<br>FNC                    | For bearing or end caps                                                                      | 75              |
| [6]                                  | Trunnion flange<br>ZNCF/CRZNG             | For bearing caps                                                                             | 82              |
| [7]                                  | Trunnion support<br>LNZG                  | For trunnion flange ZNCF/CRZNG                                                               | 83              |
| [8]                                  | Swivel flange<br>SNCL/SNCL-...-R3         | For end caps                                                                                 | 76              |
| [9]                                  | Multi-position kit<br>DPNA                | For connecting two cylinders with the same piston diameter to form a multi-position cylinder | 79              |
| [10]                                 | Swivel flange<br>SNCS/CRSNCS/SNCS-...-R3  | For end caps                                                                                 | 77              |
| [11]                                 | Swivel flange<br>SNCB/SNCB-...-R3         | For swivel flange SNCL                                                                       | 81              |
| [12]                                 | Clevis foot<br>LBN/CRLBN                  | For swivel flange SNCL                                                                       | 80              |
| [13]                                 | Clevis foot<br>LBG/LBG-...-R3             | For swivel flange SNCS                                                                       | 78              |
| [14]                                 | Proximity switch<br>SME-8                 | Can be integrated in the cylinder profile barrel                                             | 87              |
| [15]                                 | Proximity switch<br>SME/SMT-8M            | Can be integrated in the cylinder profile barrel                                             | 87              |
| [16]                                 | Proximity switch<br>SMT-8G                | Inserted into the slot lengthwise                                                            | 87              |
| [17]                                 | Slot cover<br>ABP-5-S                     | For protecting the sensor cables and the sensor slots from contamination                     | 87              |
| [18]                                 | Proximity switch<br>SMPO-8E               | Pneumatic output signal                                                                      | 87              |
| [19]                                 | Mounting kit<br>SMB-8E                    | For proximity switch SMPO-8E                                                                 | 87              |
| [20]                                 | Self-aligning rod coupler<br>FK/CRFK/DARP | To compensate for radial and angular deviations                                              | 84              |
| [21]                                 | Rod clevis<br>SG/CRSG                     | Permits a swivelling movement of the cylinder in one plane                                   | 84              |
| [22]                                 | Adapters<br>AD                            | For mounting a suction cup on a hollow piston rod                                            | 84              |
| [23]                                 | Coupling piece<br>KSG/KSZ                 | To compensate for radial deviations                                                          | 84              |
| [24]                                 | Rod eye<br>SGS/CRSGS                      | With spherical bearing                                                                       | 84              |
| [25]                                 | Right-angle clevis foot<br>LQG            | For rod eye SGS                                                                              | 85              |
| [26]                                 | Rod clevis<br>SGA                         | With male thread                                                                             | 84              |

## Type codes

|     |                                                     |  |
|-----|-----------------------------------------------------|--|
| 001 | Series                                              |  |
| ADN | Compact cylinder, double-acting, based on ISO 21287 |  |

|     |                      |  |
|-----|----------------------|--|
| 002 | Piston diameter [mm] |  |
| 12  | 12                   |  |
| 16  | 16                   |  |
| 20  | 20                   |  |
| 25  | 25                   |  |
| 32  | 32                   |  |
| 40  | 40                   |  |
| 50  | 50                   |  |
| 63  | 63                   |  |
| 80  | 80                   |  |
| 100 | 100                  |  |
| 125 | 125                  |  |

|     |                   |  |
|-----|-------------------|--|
| 003 | Stroke range [mm] |  |
| ... | 1 ... 500         |  |

|     |                        |  |
|-----|------------------------|--|
| 004 | Piston rod thread type |  |
| A   | Male thread            |  |
| I   | Female thread          |  |

|     |                                                   |  |
|-----|---------------------------------------------------|--|
| 005 | Cushioning                                        |  |
| P   | Elastic cushioning rings/plates on both sides     |  |
| PPS | Pneumatic cushioning, self-adjusting at both ends |  |

|     |                      |  |
|-----|----------------------|--|
| 006 | Position sensing     |  |
| A   | For proximity sensor |  |

|     |                                                                                    |  |
|-----|------------------------------------------------------------------------------------|--|
| 007 | Special material properties                                                        |  |
|     | None                                                                               |  |
| F1A | Recommended for production facilities for the manufacture of lithium-ion batteries |  |

|     |                             |  |
|-----|-----------------------------|--|
| 008 | Protection against rotation |  |
|     | None                        |  |
| Q   | Square piston rod           |  |

|     |                            |  |
|-----|----------------------------|--|
| 009 | Piston rod type            |  |
|     | At one end                 |  |
| S2  | Through piston rod         |  |
| S20 | Through, hollow piston rod |  |

|              |               |  |
|--------------|---------------|--|
| 010          | Custom thread |  |
| "M5"K5       | M5            |  |
| "M6"K5       | M6            |  |
| "M8"K5       | M8            |  |
| "M10"K5      | M10           |  |
| "M10x1,25"K5 | M10x1.25      |  |
| "M12"K5      | M12           |  |
| "M16"K5      | M16           |  |
| "M20"K5      | M20           |  |
| "M20x1,5"K5  | M20x1.5       |  |

|     |                                  |  |
|-----|----------------------------------|--|
| 011 | Temperature range                |  |
|     | Standard                         |  |
| S6  | Heat-resistant seals max. 120 °C |  |

|     |                        |  |
|-----|------------------------|--|
| 012 | Constant motion        |  |
|     | Standard               |  |
| S10 | Uniform, slow movement |  |

|     |                         |  |
|-----|-------------------------|--|
| 013 | Running characteristics |  |
|     | Standard                |  |
| S11 | Low friction            |  |

|     |                                             |  |
|-----|---------------------------------------------|--|
| 014 | Improved running performance                |  |
|     | None                                        |  |
| K10 | Smooth anodised aluminium coated piston rod |  |

|     |                           |  |
|-----|---------------------------|--|
| 015 | Corrosion protection      |  |
|     | Standard                  |  |
| R3  | High corrosion protection |  |

|     |                           |  |
|-----|---------------------------|--|
| 016 | Captive rating plate      |  |
|     | Rating plate, glued       |  |
| TL  | Laser etched rating plate |  |


|     |                  |  |
|-----|------------------|--|
| 017 | Low temperature  |  |
|     | None             |  |
| TT  | -40 °C... +80 °C |  |

|     |                 |  |
|-----|-----------------|--|
| 018 | Scraper variant |  |
|     | Standard        |  |
| R8  | Dust protection |  |


|     |                  |  |
|-----|------------------|--|
| 019 | EU certification |  |
|     | None             |  |
| EX4 | II 2GD           |  |

## Datasheet


Function  
Elastic cushioning (P)



PPS cushioning



-  - Diameter  
12 ... 125 mm

-  - Stroke length  
1 ... 500 mm

Variants → page 3



www.festo.com



| General technical data |                                                   |    |                       |    |    |    |    |     |    |     |                    |  |
|------------------------|---------------------------------------------------|----|-----------------------|----|----|----|----|-----|----|-----|--------------------|--|
| Piston $\varnothing$   | 12                                                | 16 | 20                    | 25 | 32 | 40 | 50 | 63  | 80 | 100 | 125                |  |
| Standard               | Based on ISO 21287                                |    | Conforms to ISO 21287 |    |    |    |    |     |    |     | Based on ISO 21287 |  |
| Design                 | Piston                                            |    |                       |    |    |    |    |     |    |     |                    |  |
|                        | Piston rod                                        |    |                       |    |    |    |    |     |    |     |                    |  |
|                        | Cylinder barrel                                   |    |                       |    |    |    |    |     |    |     |                    |  |
| Operating mode         | Double-acting                                     |    |                       |    |    |    |    |     |    |     |                    |  |
| Cushioning             | Elastic cushioning rings/pads at both ends        |    |                       |    |    |    |    |     |    |     |                    |  |
| P                      | Elastic cushioning rings/pads at both ends        |    |                       |    |    |    |    |     |    |     |                    |  |
| PPS                    | Pneumatic cushioning, self-adjusting at both ends |    |                       |    |    |    |    |     |    |     | -                  |  |
| Cushioning length      | PPS [mm]                                          |    |                       |    |    |    |    |     |    |     |                    |  |
|                        | -                                                 | 3  | 3.5                   | 4  | 5  | 6  | 7  | 7.5 | 10 | -   | -                  |  |
| Position sensing       | Via proximity switch                              |    |                       |    |    |    |    |     |    |     |                    |  |
| Type of mounting       | With through-hole                                 |    |                       |    |    |    |    |     |    |     |                    |  |
|                        | With female thread                                |    |                       |    |    |    |    |     |    |     |                    |  |
|                        | Via accessories                                   |    |                       |    |    |    |    |     |    |     |                    |  |
| Mounting position      | Any                                               |    |                       |    |    |    |    |     |    |     |                    |  |

| Technical data – Basic version and variants |    |     |               |               |          |               |
|---------------------------------------------|----|-----|---------------|---------------|----------|---------------|
| Piston $\varnothing$                        | 12 | 16  | 20            | 25            | 32       | 40            |
| Pneumatic connection                        | -  |     |               |               |          |               |
|                                             | M5 | M5  | M5            | M5            | G1/8     | G1/8          |
| S1                                          | -  | -   | -             | M5            | -        | M5            |
| Female piston rod thread                    | -  |     |               |               |          |               |
|                                             | M3 | M4  | M6            | M6            | M8       | M8            |
| K5                                          | -  | -   | M5            | M5            | M6       | M6            |
| S1                                          | -  | -   | -             | M6            | -        | M10           |
| S1-K5                                       | -  | -   | -             | M5            | -        | M8            |
| Male piston rod thread                      | -  |     |               |               |          |               |
|                                             | M5 | M6  | M8            | M8            | M10x1.25 | M10x1.25      |
| K5                                          | M6 | M8  | M10; M10x1.25 | M10; M10x1.25 | M10; M12 | M10; M12      |
| S1                                          | -  | -   | -             | M8            | -        | M12x1.25      |
| S1-K5                                       | -  | -   | -             | M10; M10x1.25 | -        | M10x1.25; M12 |
| Q-K5                                        | M6 | M8  | M10; M10x1.25 | M10; M10x1.25 | M10      | M10           |
| Max. torsional backlash of piston rod [°]   | Q  |     |               |               |          |               |
|                                             | 2  | 1.8 | 1.6           | 1.6           | 1.2      | 1.2           |

## Datasheet

| Technical data – Basic version and variants  |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
|----------------------------------------------|-----------------------------------------------------------------------------------|---------------|-------------------|-------------------|-------------|-----------|-----------|----|------------|-----|-----|
| Piston ø                                     | 50                                                                                | 63            | 80                | 100               | 125         |           |           |    |            |     |     |
| Pneumatic connection                         |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | G1/8                                                                              | G1/8          | G1/8              | G1/8              | G1/4        |           |           |    |            |     |     |
| S1                                           | –                                                                                 | G1/8          | –                 | G1/8              | –           |           |           |    |            |     |     |
| Female piston rod thread                     |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | M10                                                                               | M10           | M12               | M12               | M16         |           |           |    |            |     |     |
| K5                                           | M8                                                                                | M8            | M10               | M10               | –           |           |           |    |            |     |     |
| S1                                           | –                                                                                 | M12           | –                 | M16               | –           |           |           |    |            |     |     |
| S1-K5                                        | –                                                                                 | M10           | –                 | –                 | –           |           |           |    |            |     |     |
| Male piston rod thread                       |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | M12x1.25                                                                          | M12x1.25      | M16x1.5           | M16x1.5           | M20x1.5     |           |           |    |            |     |     |
| K5                                           | M12; M16                                                                          | M12; M16      | M16; M20; M20x1.5 | M16; M20; M20x1.5 | M20         |           |           |    |            |     |     |
| S1                                           | –                                                                                 | M16x1.5       | –                 | M20x1.5           | –           |           |           |    |            |     |     |
| S1-K5                                        | –                                                                                 | M12x1.25; M16 | –                 | M16x1.5; M20      | –           |           |           |    |            |     |     |
| Q-K5                                         | M12                                                                               | M12           | M16               | M16               | M20         |           |           |    |            |     |     |
| Max. torsional backlash of piston rod [°]    |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| Q                                            | 1                                                                                 | 1             | 0.8               | 0.8               | 0.8         |           |           |    |            |     |     |
| Operating and environmental conditions       |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| Piston ø                                     | 12                                                                                | 16            | 20                | 25                | 32          | 40        | 50        | 63 | 80         | 100 | 125 |
| Operating medium                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                         |               |                   |                   |             |           |           |    |            |     |     |
| Note on the operating/<br>pilot medium       | Lubricated operation possible (in which case lubrication will always be required) |               |                   |                   |             |           |           |    |            |     |     |
| Operating pressure                           |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| in [MPa]                                     |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | 0.1 ... 1                                                                         |               | 0.06 ... 1        |                   |             |           |           |    |            |     |     |
| PPS                                          | –                                                                                 |               | 0.15 ... 1        |                   |             | 0.1 ... 1 |           |    | –          |     |     |
| Q                                            | 0.15 ... 1                                                                        |               | 0.1 ... 1         |                   |             |           |           |    |            |     |     |
| Q-S6                                         | 0.15 ... 0.6                                                                      |               | 0.1 ... 0.6       |                   |             |           |           |    |            |     |     |
| S1                                           | –                                                                                 |               | 0.1 ... 1         | –                 | 0.1 ... 1   | –         | 0.1 ... 1 | –  | 0.1 ... 1  | –   |     |
| S2, S20                                      | 0.15 ... 1                                                                        |               | 0.12 ... 1        |                   |             | 0.1 ... 1 |           |    | 0.08 ... 1 |     |     |
| S6                                           | 0.1 ... 1                                                                         |               | 0.06 ... 1        |                   |             |           |           |    |            |     |     |
| S11                                          | 0.045 ... 1                                                                       |               |                   |                   | 0.025 ... 1 |           |           |    |            |     |     |
| R8, TT                                       | –                                                                                 |               | 0.15 ... 1        |                   |             | 0.1 ... 1 |           |    | –          |     |     |
| in [bar]                                     |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | 1 ... 10                                                                          |               | 0.6 ... 10        |                   |             |           |           |    |            |     |     |
| PPS                                          | –                                                                                 |               | 1.5 ... 10        |                   |             | 1 ... 10  |           |    | –          |     |     |
| Q                                            | 1.5 ... 10                                                                        |               | 1 ... 10          |                   |             |           |           |    |            |     |     |
| Q-S6                                         | 1.5 ... 6                                                                         |               | 1 ... 6           |                   |             |           |           |    |            |     |     |
| S1                                           | –                                                                                 |               | 1 ... 10          | –                 | 1 ... 10    | –         | 1 ... 10  | –  | 1 ... 10   | –   |     |
| S2, S20                                      | 1.5 ... 10                                                                        |               | 1.2 ... 10        |                   |             | 1 ... 10  |           |    | 0.8 ... 10 |     |     |
| S6                                           | 1 ... 10                                                                          |               | 0.6 ... 10        |                   |             |           |           |    |            |     |     |
| S11                                          | 0.45 ... 10                                                                       |               |                   |                   | 0.25 ... 10 |           |           |    |            |     |     |
| R8, TT                                       | –                                                                                 |               | 1.5 ... 10        |                   |             | 1 ... 10  |           |    | –          |     |     |
| Ambient temperature <sup>1)</sup> [°C]       |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | –20 ... +80                                                                       |               |                   |                   |             |           |           |    |            |     |     |
| S6                                           | 0 ... +120                                                                        |               |                   |                   |             |           |           |    |            |     |     |
| S10, S11                                     | +5 ... +80                                                                        |               |                   |                   |             |           |           |    |            |     |     |
| R3                                           | –20 ... +80                                                                       |               |                   |                   |             |           |           |    |            |     |     |
| TT                                           | –                                                                                 |               | –40 ... +80       |                   |             |           |           |    |            |     |     |
| Corrosion resistance class CRC <sup>2)</sup> |                                                                                   |               |                   |                   |             |           |           |    |            |     |     |
| –                                            | 2                                                                                 |               |                   |                   |             |           |           |    |            |     |     |
| R3                                           | 3                                                                                 |               |                   |                   |             |           |           |    |            |     |     |
| F1A                                          | 0                                                                                 |               |                   |                   |             |           |           |    |            |     |     |
| ATEX                                         | Selected types → <a href="http://www.festo.com">www.festo.com</a>                 |               |                   |                   |             |           |           |    |            |     |     |

1) Note operating range of proximity switches

2) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Datasheet

| Forces [N] and impact energy [J]        |       |       |       |       |      |      |      |      |      |      |      |
|-----------------------------------------|-------|-------|-------|-------|------|------|------|------|------|------|------|
| Piston ø                                | 12    | 16    | 20    | 25    | 32   | 40   | 50   | 63   | 80   | 100  | 125  |
| Theoretical force at 6 bar, advancing   |       |       |       |       |      |      |      |      |      |      |      |
| –                                       | 68    | 121   | 188   | 295   | 483  | 754  | 1178 | 1870 | 3016 | 4712 | 7363 |
| S1                                      | –     | –     | –     | 295   | –    | 754  | –    | 1870 | –    | 4712 | –    |
| S2                                      | 51    | 90    | 141   | 247   | 415  | 686  | 1057 | 1750 | 2827 | 4524 | 7069 |
| Theoretical force at 6 bar, retracting  |       |       |       |       |      |      |      |      |      |      |      |
| –                                       | 51    | 90    | 141   | 247   | 415  | 686  | 1057 | 1750 | 2827 | 4524 | 7069 |
| S1                                      | –     | –     | –     | 247   | –    | 633  | –    | 1681 | –    | 4417 | –    |
| S2                                      | 51    | 90    | 141   | 247   | 415  | 686  | 1057 | 1750 | 2827 | 4524 | 7069 |
| Max. impact energy in the end positions |       |       |       |       |      |      |      |      |      |      |      |
| –                                       | 0.07  | 0.15  | 0.2   | 0.3   | 0.4  | 0.7  | 1    | 1.3  | 1.8  | 2.5  | 3.3  |
| S1                                      | –     | –     | –     | 0.3   | –    | 0.7  | –    | 1.3  | –    | 2.5  | –    |
| S6, S10, S11, TT                        | 0.035 | 0.075 | 0.1   | 0.15  | 0.2  | 0.35 | 0.5  | 0.65 | 0.9  | 1.25 | 1.75 |
| K10                                     | –     | –     | 0.16  | 0.24  | 0.32 | 0.56 | 0.8  | 1    | 1.4  | 2    | 2.6  |
| S20                                     | –     | 0.016 | 0.024 | 0.083 | 0.15 | 0.39 | 0.48 | 0.62 | 0.8  | 0.9  | 0.95 |



**Note**

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact speed:

$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

V Permissible impact velocity

E Max. impact energy

m1 Moving mass (drive)

m2 Moving payload

Maximum permissible mass:

$$m_2 = \frac{2 \times E}{v^2} - m_1$$



**Note**

The maximum impact energy is still maintained in combination with the self-adjusting cushioning PPS



**Max. energy conversion capacity [J]**

| Piston ø                            | 20   | 25  | 32 | 40  | 50  | 63  | 80 | 100 |
|-------------------------------------|------|-----|----|-----|-----|-----|----|-----|
| For self-adjusting cushioning (PPS) | 0.65 | 0.8 | 1  | 1.7 | 2.8 | 4.8 | 8  | 12  |

**Max. lateral force F<sub>q</sub> as a function of projection x**

ø 12 ... 63

ø 80 ... 125



- ø 12
- · - · - · ø 16
- - - - - ø 20
- · · · · ø 25
- · - · - · ø 32/40
- - - - - ø 50/63


- - - - - ø 80/100
- · - · - · ø 125

Datasheet

Max. lateral load  $F_q$  as a function of projection  $x$  and lever arm  $a$


Q – Square piston rod

$\varnothing 12$




- a = 5 mm
- · - · - a = 10 mm
- - - a = 15 mm
- · · · · a = 20 mm
- · - · - a = 25 mm
- - - a = 30 mm

$\varnothing 16$




- a = 5 mm
- · - · - a = 10 mm
- - - a = 15 mm
- · · · · a = 20 mm
- · - · - a = 25 mm
- - - a = 30 mm

$\varnothing 20/25$



- a = 5 mm
- · - · - a = 10 mm
- - - a = 15 mm
- · · · · a = 20 mm
- · - · - a = 25 mm
- - - a = 30 mm

$\varnothing 32/40$



- · - · - a = 10 mm
- · · · · a = 20 mm
- - - a = 30 mm
- - - a = 40 mm
- · - · - a = 50 mm
- · - · - a = 60 mm

Note

• For cantilevers that are larger than those shown in the diagrams, torques on the piston rod must be ruled out.

• If  $a = 0$ , the corresponding lateral load line of the basic version of the ADN can be used (→ page 15).




## Datasheet

### Max. lateral load $F_q$ as a function of projection $x$ and lever arm $a$


Q – Square piston rod

Ø 50/63




- ..... a = 10 mm
- ..... a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

Ø 80/100



- ..... a = 10 mm
- ..... a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

Ø 125



- ..... a = 10 mm
- ..... a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

#### Note


- For cantilevers that are larger than those shown in the diagrams, torques on the piston rod must be ruled out.

- If  $a = 0$ , the corresponding lateral load line of the basic version of the ADN can be used (→ page 15).

## Datasheet

### Max. lateral force $F_q$ as a function of projection $x$


S1 – Reinforced piston rod



| Weight [g]                         | 12 | 16 | 20  | 25  | 32  | 40  | 50  | 63  | 80   | 100  | 125  |
|------------------------------------|----|----|-----|-----|-----|-----|-----|-----|------|------|------|
| Piston $\varnothing$               | 12 | 16 | 20  | 25  | 32  | 40  | 50  | 63  | 80   | 100  | 125  |
| Product weight with 0 mm stroke    | 77 | 79 | 131 | 156 | 265 | 346 | 540 | 722 | 1121 | 2154 | 2880 |
| Additional weight per 10 mm stroke | 12 | 14 | 21  | 23  | 30  | 37  | 51  | 59  | 79   | 98   | 117  |
| Moving mass with 0 mm stroke       | 9  | 15 | 30  | 50  | 60  | 80  | 140 | 180 | 400  | 570  | 1080 |
| Additional mass per 10 mm stroke   | 2  | 4  | 6   | 6   | 9   | 9   | 16  | 16  | 25   | 25   | 39   |

### Materials

Sectional view



| Compact cylinder         | Basic version, Q                                                                                                                                                                                                              | R8                                | S6, S10, S11     | R3                                | K10                               | F1A                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------|-----------------------------------|-----------------------------------|---------------------------------|
| [1] Cover                |                                                                                                                                                                                                                               |                                   |                  |                                   |                                   |                                 |
| $\varnothing$ 12 ... 63  | Anodised aluminium                                                                                                                                                                                                            |                                   |                  |                                   |                                   |                                 |
| $\varnothing$ 80 ... 125 | Coated die-cast aluminium                                                                                                                                                                                                     |                                   |                  |                                   |                                   |                                 |
| [2] Cylinder barrel      | Anodised aluminium                                                                                                                                                                                                            |                                   |                  |                                   |                                   |                                 |
| [3] Piston rod           | High-alloy steel                                                                                                                                                                                                              | Hard-chrome-plated tempered steel | High-alloy steel |                                   | Anodised aluminium                | High-alloy steel                |
| [4] Flange screws        |                                                                                                                                                                                                                               |                                   |                  |                                   |                                   |                                 |
| $\varnothing$ 12 ... 16  | High-alloy steel                                                                                                                                                                                                              |                                   |                  | High-alloy steel                  | –                                 | Steel, chemically nickel-plated |
| $\varnothing$ 20 ... 63  | Galvanised steel                                                                                                                                                                                                              |                                   |                  | Tempered steel                    | Galvanised steel                  |                                 |
| $\varnothing$ 80 ... 125 | Standard screws, galvanised steel                                                                                                                                                                                             |                                   |                  | Standard screws, high-alloy steel | Standard screws, galvanised steel |                                 |
| – Seals                  | Polyurethane                                                                                                                                                                                                                  |                                   | Fluoro rubber    | Polyurethane                      |                                   | Polyurethane                    |
| Note on materials        |                                                                                                                                                                                                                               |                                   |                  |                                   |                                   |                                 |
| ADN-...                  | RoHS-compliant                                                                                                                                                                                                                |                                   |                  |                                   |                                   |                                 |
|                          | LABS (PWIS) conformity: VDMA24364-B1/B2-L                                                                                                                                                                                     |                                   |                  |                                   |                                   |                                 |
| ADN-...-S10/11           | Contains paint-wetting impairment substances                                                                                                                                                                                  |                                   |                  |                                   |                                   |                                 |
|                          | LABS (PWIS) conformity: VDMA24364-Zone III                                                                                                                                                                                    |                                   |                  |                                   |                                   |                                 |
| ADN-...-F1A              | Metals with copper, zinc or nickel as the main constituent are excluded from use.<br>Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils. |                                   |                  |                                   |                                   |                                 |

Datasheet





Dimensions – Basic version

Download CAD data → [www.festo.com](http://www.festo.com)

∅ 12 ... 63



∅ 80 ... 125

∅ 32 ... 63



∅ 12 ... 25

∅ 12



+ = plus stroke length

[1] = Drilled hole for centring pin/sleeve

| ∅<br>[mm] | BG<br>min. | D1<br>∅<br>H9 | D5<br>∅               | E                    | EE   | G    | J2  | J3  | PW<br>+0.2 |
|-----------|------------|---------------|-----------------------|----------------------|------|------|-----|-----|------------|
| 12        | 17         | 9             | 6 <sup>F9</sup>       | 27.5 <sup>+0.3</sup> | M5   | 10.5 | 2   | –   | 3.5        |
| 16        |            |               |                       | 29 <sup>+0.3</sup>   |      | 11   | 2.6 |     |            |
| 20        |            |               |                       | 35.5 <sup>+0.3</sup> |      | 12   |     |     |            |
| 25        | 19.5       |               | 9 <sup>F9</sup>       | 39.5 <sup>+0.3</sup> | G1/8 | 15   | 6   | 8   | 5          |
| 32        |            |               |                       | 47 <sup>+0.3</sup>   |      |      |     |     |            |
| 40        |            |               |                       | 54.5 <sup>+0.3</sup> |      |      |     |     |            |
| 50        | 26         | 12            | 12 <sup>F9</sup>      | 65.5 <sup>+0.3</sup> | 16.5 | 11.5 | 20  | 2.6 |            |
| 63        |            |               |                       | 75.5 <sup>+0.3</sup> |      |      |     |     |            |
| 80        | 17         |               | 15                    | 95.5 <sup>+0.6</sup> |      |      |     |     | G1/4       |
| 100       | 21.5       | –             | 113.5 <sup>+0.6</sup> |                      |      |      |     |     |            |
| 125       | 20         | –             | 134.6 <sup>+0.3</sup> |                      |      |      |     |     |            |



| ∅<br>[mm] | MM<br>∅ | PL<br>+0.2 | RT   | ST<br>h13 | T2<br>+0.1 | TG<br>±0.2 | ZA<br>±0.6 | ZB<br>+1.2 | PPS<br>+1.3 |
|-----------|---------|------------|------|-----------|------------|------------|------------|------------|-------------|
| 12        | 6       | 6          | M4   | 5         | 2.1        | 16         | 35         | 39.2       | –           |
| 16        | 8       |            |      | 7         |            | 18         |            | 39.7       |             |
| 20        | 10      |            |      | M5        |            | 9          |            | 22         |             |
| 25        |         |            | 26   |           |            | 39         | 44.5       |            |             |
| 32        |         |            | 12   |           |            | M6         | 10         | 32.5       | 44          |
| 40        | 38      |            |      | 45        |            |            | 51.1       | 51.7       |             |
| 50        | 16      | M8         |      |           | 13         |            | 46.5       | 52.7       | 53.2        |
| 63        |         |            | 56.5 |           | 49         | 56.5       | 57         |            |             |
| 80        |         |            | 20   | M10       | 17         | 72         | 54         | 62.9       | 63.4        |
| 100       | 10.5    | M12        |      |           | 21         | 89         | 67         | 76         | 76.8        |
| 125       |         |            |      |           | 110        | 81         | 92         | –          |             |

# Datasheet

## Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)



Basic version



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 125$

+ = plus stroke length

S2 – Through piston rod




[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 125$

+ = plus stroke length

++ = plus 2x stroke length

S20 – Through, hollow piston rod





[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 125$

+ = plus stroke length

++ = plus 2x stroke length

K2 – Extended male piston rod thread





**Note**

In combination with variants S2/  
S20, the piston rod thread is ex-  
tended at both ends

[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 125$

+ = plus stroke length

K5 – Custom piston rod thread




Datasheet

Dimensions – Variants


Download CAD data → [www.festo.com](http://www.festo.com)

K8 – Extended piston rod



**Note**  
 In combination with variants S2/ S20, the piston rod thread is extended at one end  
 [1] Hex nut DIN 439-B only with  $\varnothing 32 \dots 125$   
 + = plus stroke length

R8 – Dust protection / TT – Low temperature



[1] Hex nut DIN 439-B only with  $\varnothing 32 \dots 125$   
 + = plus stroke length

| $\varnothing$<br>[mm] | A  | A1       | A2        | AF<br>min. | AF5<br>min. | B<br>$\varnothing$ | D7<br>$\varnothing$ | D8   | D9<br>$\varnothing$ | L5  | KF  | KF5 | KK       |
|-----------------------|----|----------|-----------|------------|-------------|--------------------|---------------------|------|---------------------|-----|-----|-----|----------|
| 12                    | 10 | 1 ... 10 | 1 ... 300 | 8          | –           | –                  | –                   | –    | –                   | –   | M3  | –   | M5       |
| 16                    | 12 |          |           | 10         | –           | –                  | 4.5                 |      | 3.2                 | 3   | M4  | –   | M6       |
| 20                    | 16 | 1 ... 20 | 1 ... 400 | 14         | 12          | 18                 | 6                   | –    | 3.8                 | 2   | M6  | M5  | M8       |
| 25                    |    |          |           | 16         | 12          | 18                 | 6                   |      | 3.8                 | 2   | M6  | M5  | M8       |
| 32                    | 19 | 1 ... 20 | 1 ... 400 | 16         | 14          | 27                 | 8                   | –    | 4.5                 | 3   | M8  | M6  | M10x1.25 |
| 40                    |    |          |           | 19         | 14          | 27                 | 8                   |      | 4.5                 | 3   | M8  | M6  | M10x1.25 |
| 50                    | 22 | 1 ... 30 | 1 ... 500 | 20         | 16          | 31                 | 10                  | –    | 6                   | 3.5 | M10 | M8  | M12x1.25 |
| 63                    |    |          |           |            |             |                    |                     |      |                     |     |     |     |          |
| 80                    | 28 | 1 ... 30 | 1 ... 500 | 20         | 20          | 35                 | –                   | G1/8 | 8                   | –   | M12 | M10 | M16x1.5  |
| 100                   |    |          |           |            |             |                    |                     |      |                     |     |     |     |          |
| 125                   | 40 | 1 ... 40 | –         | 25         | –           | –                  | –                   | G1/4 | 11.7                | –   | M16 | –   | M20x1.5  |



| $\varnothing$<br>[mm] | KK5                   | T3  | T4  | VD  | WH   |             |               | ZB   |             |               | ZM                    |                      |
|-----------------------|-----------------------|-----|-----|-----|------|-------------|---------------|------|-------------|---------------|-----------------------|----------------------|
|                       |                       |     |     |     | +1.3 | PPS<br>+1.4 | R8/TT<br>+1.3 | +1.2 | PPS<br>+1.3 | R8/TT<br>+1.2 |                       | PPS                  |
| 12                    | M6                    | –   | 1.5 | –   | 4.2  | –           | –             | 39.2 | –           | –             | 44.5 <sup>+0.5</sup>  | –                    |
| 16                    | M8                    | –   | 1.5 | –   | 4.7  | –           | –             | 39.7 | –           | –             | 45.7 <sup>+0.5</sup>  | –                    |
| 20                    | M10x1.25<br>M10       | 2   | 2.6 | 5.2 | 5.5  | 5.5         | 10.5          | 42.5 | 42.5        | 47.5          | 49.5 <sup>+0.5</sup>  | 49.5 <sup>+0.5</sup> |
| 25                    |                       |     |     |     |      |             |               | 44.5 | 45.3        | 49.5          | 51.5 <sup>+0.5</sup>  | 51.5 <sup>+0.5</sup> |
| 32                    | M10<br>M12            | 2.6 | 3.3 | 6.4 | 6    | 6.5         | 12.5          | 50   | 50.6        | 56.5          | 57.5 <sup>+0.5</sup>  | 58.6 <sup>+0.6</sup> |
| 40                    |                       |     |     |     |      |             |               | 51.1 | 51.7        | 57.5          | 58.6 <sup>+0.6</sup>  | 59.7 <sup>+0.7</sup> |
| 50                    | M12<br>M16            | 3.3 | 4.7 | 6.4 | 7.7  | 8.2         | 14.7          | 52.7 | 53.2        | 59.7          | 62.0 <sup>+0.6</sup>  | 63.1 <sup>+0.7</sup> |
| 63                    |                       |     |     |     |      |             |               | 56.5 | 57          | 63.6          | 65.4 <sup>+0.6</sup>  | 66.5 <sup>+0.7</sup> |
| 80                    | M16<br>M20x1.5<br>M20 | 4.7 | 6.1 | 6.4 | 8.9  | 9.4         | 15.4          | 62.9 | 63.4        | 69.4          | 73.2 <sup>+0.6</sup>  | 74.3 <sup>+0.7</sup> |
| 100                   |                       |     |     |     |      |             |               | 76   | 76.8        | 82.5          | 86.4 <sup>+0.6</sup>  | 88 <sup>+0.7</sup>   |
| 125                   | M20                   | –   | 7   | –   | 11   | –           | –             | 92   | –           | –             | 104.4 <sup>+0.6</sup> | –                    |

## Datasheet

### Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)



#### Q – Square piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 125

+ = plus stroke length


#### Q-S2 – Square, through piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 125

+ = plus stroke length  
++ = plus 2x stroke length



#### Q-S20 – Square, through, hollow piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 125

+ = plus stroke length  
++ = plus 2x stroke length

#### Q-K2 – Square piston rod with extended male thread




#### Note

In combination with variants S2/  
S20, the piston rod thread is ex-  
tended at both ends.

[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 125

+ = plus stroke length

#### Q-K5 – Square piston rod with custom thread




+ = plus stroke length

## Datasheet

## Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)

Q-K8 – Square, extended piston rod



- **Note**

In combination with variants S2/  
S20, the piston rod thread is ex-  
tended at both ends.

[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 125$

+ = plus stroke length

| $\varnothing$<br>[mm] | A  | A1        | A2        | AF<br>min. | AF3<br>min. | B1<br>□ | D7<br>$\varnothing$ | D8   | D9<br>$\varnothing$ |      |
|-----------------------|----|-----------|-----------|------------|-------------|---------|---------------------|------|---------------------|------|
| 12                    | 10 | 1 ... 10  | 1 ... 300 | 8          | 8           | 5.5     | –                   | –    | –                   |      |
| 16                    | 12 |           |           | 10         | 10          | 7       | 4.5                 |      | 3.2                 |      |
| 20                    | 16 |           |           | 14         | 12          | 9       | 6                   |      | 3.8                 |      |
| 25                    |    | 1 ... 20  | 16        | 14         | 10          | 8       | 4.5                 |      |                     |      |
| 32                    | 19 | 1 ... 400 | 1 ... 500 | 20         | 16          | 12      | 10                  | –    | 6                   |      |
| 40                    |    |           |           | 20         | 16          | 12      | 10                  |      | 8                   |      |
| 50                    |    |           |           | 22         | 20          | 16      | 12                  |      | 10                  | 6    |
| 63                    | 28 | 1 ... 30  | 1 ... 500 | 20         | 20          | 16      | –                   | G1/8 | 8                   |      |
| 80                    |    |           |           | 25         | 24          | 20      |                     |      | G1/4                | 11.7 |
| 100                   |    |           |           | 1 ... 40   | 25          | 24      |                     |      |                     | 20   |
| 125                   | 40 | 1 ... 40  |           |            |             |         |                     |      |                     |      |


| $\varnothing$<br>[mm] | L5  | KF  | KF3 | KK       | KK5             | T2  | T4  | WH<br>+1.3 | ZB<br>+1.2           | ZM                    |
|-----------------------|-----|-----|-----|----------|-----------------|-----|-----|------------|----------------------|-----------------------|
| 12                    | –   | M3  | M3  | M5       | M6              | 1.5 | 1.5 | 4.2        | 39.2                 | 44.5 <sup>+0.5</sup>  |
| 16                    | 3   | M4  | M4  | M6       | M8              |     |     | 4.7        | 39.7                 | 45.7 <sup>+0.5</sup>  |
| 20                    | 2   | M6  | M5  | M8       | M10x1.25<br>M10 | 2   | 2.6 | 5.5        | 42.5                 | 49.5 <sup>+0.5</sup>  |
| 25                    |     |     |     |          |                 |     |     | 44.5       | 51.5 <sup>+0.5</sup> |                       |
| 32                    | 3   | M8  | M6  | M10x1.25 | M10             | 2.6 | 3.3 | 6          | 50                   | 57.5 <sup>+0.5</sup>  |
| 40                    |     |     |     |          |                 |     |     | 6.1        | 51.1                 | 58.6 <sup>+0.6</sup>  |
| 50                    |     |     |     |          |                 |     |     | 8.2        | 53.2                 | 62.8 <sup>+0.6</sup>  |
| 63                    | 3.5 | M10 | M8  | M12x1.25 | M12             | 3.3 | 4.7 | 8.1        | 57.1                 | 66.6 <sup>+0.6</sup>  |
| 80                    |     |     |     |          |                 |     |     | 8.9        | 62.9                 | 73.2 <sup>+0.6</sup>  |
| 100                   |     |     |     |          |                 |     |     | 9          | 76                   | 86.4 <sup>+0.6</sup>  |
| 125                   | –   | M16 | M12 | M20x1.5  | M20             | 6.1 | 7   | 11         | 92                   | 104.4 <sup>+0.6</sup> |

# Datasheet

**Dimensions – Variants**


Download CAD data → [www.festo.com](http://www.festo.com)

S1 – Reinforced piston rod  
 ∅ 25



+ = plus stroke length

∅ 40 ... 100



- [1] Cylinder advancing
- [2] Cylinder retracting

+ = plus stroke length

| ∅<br>[mm] | B<br>∅<br>f8 | BG<br>min. | D1<br>∅<br>H9 | E                     | EE   | J3 | PW | MM<br>∅ | PL  |
|-----------|--------------|------------|---------------|-----------------------|------|----|----|---------|-----|
| 25        | 22           | 15         | 9             | 39.5 <sup>+0.3</sup>  | M5   | –  | 5  | 10      | 6   |
| 40        | 35           | 16         |               | 54.5 <sup>+0.3</sup>  |      | 15 |    | 16      |     |
| 63        | 42           | 17         | 12            | 75.5 <sup>+0.3</sup>  | G1/8 | 23 |    | 20      | 8.2 |
| 100       | 55           |            |               | 113.5 <sup>+0.6</sup> |      | 40 | 25 | 10.5    |     |

| ∅<br>[mm] | RT  | ST  | T2   | TG   | VD   | WH   | ZA   | ZB   |
|-----------|-----|-----|------|------|------|------|------|------|
|           |     | h13 | +0.1 | ±0.2 |      | +1.3 | ±0.6 | +1.2 |
| 25        | M5  | 9   | 2.1  | 26   | 6    | 11.8 | 39   | 50.9 |
| 40        | M6  | 13  |      | 38   | 9.5  | 18   | 45   | 62.9 |
| 63        | M8  | 17  | 2.6  | 56.5 | 12   | 21   | 49   | 70.2 |
| 100       | M10 | 21  |      | 89   | 15.5 | 26.5 | 67   | 93.5 |





## Datasheet

## Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)


## S1 – Reinforced piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  40 ... 100

+ = plus stroke length



## S1-K2 – Reinforced piston rod with extended male piston rod thread



[1] Hex nut DIN 439-B  
only with  $\varnothing$  40 ... 100



+ = plus stroke length

## S1-K5 – Reinforced piston rod with custom piston rod thread



+ = plus stroke length

## S1-K8 – Reinforced piston rod with extended piston rod




[1] Hex nut DIN 439-B  
only with  $\varnothing$  40 ... 100

+ = plus stroke length

| $\varnothing$<br>[mm] | A  | A1       | A2        | AF | AF5 | KF  | KF5 | KK       | KK5             | T3  | T4  | WH   | ZB   |
|-----------------------|----|----------|-----------|----|-----|-----|-----|----------|-----------------|-----|-----|------|------|
| 25                    | 16 | 1 ... 20 | 1 ... 300 | 14 | 12  | M6  | M5  | M8       | M10x1.25<br>M10 | 2   | 2.6 | 11.8 | 50.9 |
| 40                    | 22 |          | 1 ... 400 | 20 | 16  | M10 | M8  | M12x1.25 | M10x1.25<br>M12 | 3.3 | 4.7 | 18   | 62.9 |
| 63                    | 28 |          |           |    | 20  | M12 | M10 | M16x1.5  | M12x1.25<br>M16 | 4.7 | 6.1 | 21   | 70.2 |
| 100                   | 40 | 1 ... 30 | 1 ... 500 | 25 | –   | M16 | –   | M20x1.5  | M16x1.5<br>M20  | –   | 7   | 26.5 | 93.5 |


Datasheet

★ Core Range

| Ordering data<br>Type | Piston ø<br>[mm] | Stroke<br>[mm] | I – Piston rod with female thread<br>P – Elastic cushioning rings/plates at both ends |                 | A – Piston rod with male thread<br>P – Elastic cushioning rings/plates at both ends |                 |
|-----------------------|------------------|----------------|---------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-----------------|
|                       |                  |                | Part no.                                                                              | Type            | Part no.                                                                            | Type            |
|                       |                  |                |       | 12              | 5                                                                                   | ★ 536211        |
|                       |                  | 10             | ★ 536212                                                                              | ADN-12-10-I-P-A | ★ 536205                                                                            | ADN-12-10-A-P-A |
|                       |                  | 15             | ★ 536213                                                                              | ADN-12-15-I-P-A | ★ 536206                                                                            | ADN-12-15-A-P-A |
|                       |                  | 20             | ★ 536214                                                                              | ADN-12-20-I-P-A | ★ 536207                                                                            | ADN-12-20-A-P-A |
|                       |                  | 25             | ★ 536215                                                                              | ADN-12-25-I-P-A | ★ 536208                                                                            | ADN-12-25-A-P-A |
|                       |                  | 30             | ★ 536216                                                                              | ADN-12-30-I-P-A | ★ 536209                                                                            | ADN-12-30-A-P-A |
|                       |                  | 40             | ★ 536217                                                                              | ADN-12-40-I-P-A | ★ 536210                                                                            | ADN-12-40-A-P-A |
|                       | 16               | 5              | ★ 536226                                                                              | ADN-16-5-I-P-A  | ★ 536219                                                                            | ADN-16-5-A-P-A  |
|                       |                  | 10             | ★ 536227                                                                              | ADN-16-10-I-P-A | ★ 536220                                                                            | ADN-16-10-A-P-A |
|                       |                  | 15             | ★ 536228                                                                              | ADN-16-15-I-P-A | ★ 536221                                                                            | ADN-16-15-A-P-A |
|                       |                  | 20             | ★ 536229                                                                              | ADN-16-20-I-P-A | ★ 536222                                                                            | ADN-16-20-A-P-A |
|                       |                  | 25             | ★ 536230                                                                              | ADN-16-25-I-P-A | ★ 536223                                                                            | ADN-16-25-A-P-A |
|                       |                  | 30             | ★ 536231                                                                              | ADN-16-30-I-P-A | ★ 536224                                                                            | ADN-16-30-A-P-A |
|                       |                  | 40             | ★ 536232                                                                              | ADN-16-40-I-P-A | ★ 536225                                                                            | ADN-16-40-A-P-A |
|                       |                  | 50             | ★ 536341                                                                              | ADN-16-50-I-P-A | ★ 536331                                                                            | ADN-16-50-A-P-A |
|                       | 20               | 5              | ★ 536242                                                                              | ADN-20-5-I-P-A  | ★ 536234                                                                            | ADN-20-5-A-P-A  |
|                       |                  | 10             | ★ 536243                                                                              | ADN-20-10-I-P-A | ★ 536235                                                                            | ADN-20-10-A-P-A |
|                       |                  | 15             | ★ 536244                                                                              | ADN-20-15-I-P-A | ★ 536236                                                                            | ADN-20-15-A-P-A |
|                       |                  | 20             | ★ 536245                                                                              | ADN-20-20-I-P-A | ★ 536237                                                                            | ADN-20-20-A-P-A |
|                       |                  | 25             | ★ 536246                                                                              | ADN-20-25-I-P-A | ★ 536238                                                                            | ADN-20-25-A-P-A |
|                       |                  | 30             | ★ 536247                                                                              | ADN-20-30-I-P-A | ★ 536239                                                                            | ADN-20-30-A-P-A |
|                       |                  | 40             | ★ 536248                                                                              | ADN-20-40-I-P-A | ★ 536240                                                                            | ADN-20-40-A-P-A |
|                       |                  | 50             | ★ 536249                                                                              | ADN-20-50-I-P-A | ★ 536241                                                                            | ADN-20-50-A-P-A |
|                       |                  | 60             | ★ 536362                                                                              | ADN-20-60-I-P-A | ★ 536352                                                                            | ADN-20-60-A-P-A |
|                       | 25               | 5              | ★ 536259                                                                              | ADN-25-5-I-P-A  | ★ 536251                                                                            | ADN-25-5-A-P-A  |
|                       |                  | 10             | ★ 536260                                                                              | ADN-25-10-I-P-A | ★ 536252                                                                            | ADN-25-10-A-P-A |
|                       |                  | 15             | ★ 536261                                                                              | ADN-25-15-I-P-A | ★ 536253                                                                            | ADN-25-15-A-P-A |
|                       |                  | 20             | ★ 536262                                                                              | ADN-25-20-I-P-A | ★ 536254                                                                            | ADN-25-20-A-P-A |
|                       |                  | 25             | ★ 536263                                                                              | ADN-25-25-I-P-A | ★ 536255                                                                            | ADN-25-25-A-P-A |
|                       |                  | 30             | ★ 536264                                                                              | ADN-25-30-I-P-A | ★ 536256                                                                            | ADN-25-30-A-P-A |
|                       |                  | 40             | ★ 536265                                                                              | ADN-25-40-I-P-A | ★ 536257                                                                            | ADN-25-40-A-P-A |
|                       |                  | 50             | ★ 536266                                                                              | ADN-25-50-I-P-A | ★ 536258                                                                            | ADN-25-50-A-P-A |
|                       |                  | 60             | ★ 536383                                                                              | ADN-25-60-I-P-A | ★ 536373                                                                            | ADN-25-60-A-P-A |
|                       | 32               | 5              | ★ 536278                                                                              | ADN-32-5-I-P-A  | ★ 536268                                                                            | ADN-32-5-A-P-A  |
|                       |                  | 10             | ★ 536279                                                                              | ADN-32-10-I-P-A | ★ 536269                                                                            | ADN-32-10-A-P-A |
|                       |                  | 15             | ★ 536280                                                                              | ADN-32-15-I-P-A | ★ 536270                                                                            | ADN-32-15-A-P-A |
|                       |                  | 20             | ★ 536281                                                                              | ADN-32-20-I-P-A | ★ 536271                                                                            | ADN-32-20-A-P-A |
|                       |                  | 25             | ★ 536282                                                                              | ADN-32-25-I-P-A | ★ 536272                                                                            | ADN-32-25-A-P-A |
|                       |                  | 30             | ★ 536283                                                                              | ADN-32-30-I-P-A | ★ 536273                                                                            | ADN-32-30-A-P-A |
|                       |                  | 40             | ★ 536284                                                                              | ADN-32-40-I-P-A | ★ 536274                                                                            | ADN-32-40-A-P-A |
|                       |                  | 50             | ★ 536285                                                                              | ADN-32-50-I-P-A | ★ 536275                                                                            | ADN-32-50-A-P-A |
|                       |                  | 60             | ★ 536286                                                                              | ADN-32-60-I-P-A | ★ 536276                                                                            | ADN-32-60-A-P-A |
|                       |                  | 80             | ★ 536287                                                                              | ADN-32-80-I-P-A | ★ 536277                                                                            | ADN-32-80-A-P-A |


## Datasheet

## ★ Core Range

| Ordering data                                                                     |          | Piston ø<br>[mm] | Stroke<br>[mm]  | I – Piston rod with female thread<br>P – Elastic cushioning rings/plates at both ends |                 | A – Piston rod with male thread<br>P – Elastic cushioning rings/plates at both ends |                 |
|-----------------------------------------------------------------------------------|----------|------------------|-----------------|---------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-----------------|
| Type                                                                              | Part no. |                  |                 | Type                                                                                  | Part no.        | Type                                                                                |                 |
|  | 40       | 5                | ★ 536299        | ADN-40-5-I-P-A                                                                        | ★ 536289        | ADN-40-5-A-P-A                                                                      |                 |
|                                                                                   |          | 10               | ★ 536300        | ADN-40-10-I-P-A                                                                       | ★ 536290        | ADN-40-10-A-P-A                                                                     |                 |
|                                                                                   |          | 15               | ★ 536301        | ADN-40-15-I-P-A                                                                       | ★ 536291        | ADN-40-15-A-P-A                                                                     |                 |
|                                                                                   |          | 20               | ★ 536302        | ADN-40-20-I-P-A                                                                       | ★ 536292        | ADN-40-20-A-P-A                                                                     |                 |
|                                                                                   |          | 25               | ★ 536303        | ADN-40-25-I-P-A                                                                       | ★ 536293        | ADN-40-25-A-P-A                                                                     |                 |
|                                                                                   |          | 30               | ★ 536304        | ADN-40-30-I-P-A                                                                       | ★ 536294        | ADN-40-30-A-P-A                                                                     |                 |
|                                                                                   |          | 40               | ★ 536305        | ADN-40-40-I-P-A                                                                       | ★ 536295        | ADN-40-40-A-P-A                                                                     |                 |
|                                                                                   |          | 50               | ★ 536306        | ADN-40-50-I-P-A                                                                       | ★ 536296        | ADN-40-50-A-P-A                                                                     |                 |
|                                                                                   | 60       | ★ 536307         | ADN-40-60-I-P-A | ★ 536297                                                                              | ADN-40-60-A-P-A |                                                                                     |                 |
|                                                                                   | 80       | ★ 536308         | ADN-40-80-I-P-A | ★ 536298                                                                              | ADN-40-80-A-P-A |                                                                                     |                 |
|                                                                                   | 50       | 5                | ★ 536320        | ADN-50-5-I-P-A                                                                        | ★ 536310        | ADN-50-5-A-P-A                                                                      |                 |
|                                                                                   |          | 10               | ★ 536321        | ADN-50-10-I-P-A                                                                       | ★ 536311        | ADN-50-10-A-P-A                                                                     |                 |
|                                                                                   |          | 15               | ★ 536322        | ADN-50-15-I-P-A                                                                       | ★ 536312        | ADN-50-15-A-P-A                                                                     |                 |
|                                                                                   |          | 20               | ★ 536323        | ADN-50-20-I-P-A                                                                       | ★ 536313        | ADN-50-20-A-P-A                                                                     |                 |
|                                                                                   |          | 25               | ★ 536324        | ADN-50-25-I-P-A                                                                       | ★ 536314        | ADN-50-25-A-P-A                                                                     |                 |
|                                                                                   |          | 30               | ★ 536325        | ADN-50-30-I-P-A                                                                       | ★ 536315        | ADN-50-30-A-P-A                                                                     |                 |
|                                                                                   |          | 40               | ★ 536326        | ADN-50-40-I-P-A                                                                       | ★ 536316        | ADN-50-40-A-P-A                                                                     |                 |
|                                                                                   |          | 50               | ★ 536327        | ADN-50-50-I-P-A                                                                       | ★ 536317        | ADN-50-50-A-P-A                                                                     |                 |
|                                                                                   |          | 60               | ★ 536328        | ADN-50-60-I-P-A                                                                       | ★ 536318        | ADN-50-60-A-P-A                                                                     |                 |
|                                                                                   |          | 80               | ★ 536329        | ADN-50-80-I-P-A                                                                       | ★ 536319        | ADN-50-80-A-P-A                                                                     |                 |
|                                                                                   | 63       | 10               | ★ 536342        | ADN-63-10-I-P-A                                                                       | ★ 536332        | ADN-63-10-A-P-A                                                                     |                 |
|                                                                                   |          | 15               | ★ 536343        | ADN-63-15-I-P-A                                                                       | ★ 536333        | ADN-63-15-A-P-A                                                                     |                 |
|                                                                                   |          | 20               | ★ 536344        | ADN-63-20-I-P-A                                                                       | ★ 536334        | ADN-63-20-A-P-A                                                                     |                 |
|                                                                                   |          | 25               | ★ 536345        | ADN-63-25-I-P-A                                                                       | ★ 536335        | ADN-63-25-A-P-A                                                                     |                 |
|                                                                                   |          | 30               | ★ 536346        | ADN-63-30-I-P-A                                                                       | ★ 536336        | ADN-63-30-A-P-A                                                                     |                 |
|                                                                                   |          | 40               | ★ 536347        | ADN-63-40-I-P-A                                                                       | ★ 536337        | ADN-63-40-A-P-A                                                                     |                 |
|                                                                                   |          | 50               | ★ 536348        | ADN-63-50-I-P-A                                                                       | ★ 536338        | ADN-63-50-A-P-A                                                                     |                 |
|                                                                                   |          | 60               | ★ 536349        | ADN-63-60-I-P-A                                                                       | ★ 536339        | ADN-63-60-A-P-A                                                                     |                 |
|                                                                                   |          | 80               | ★ 536350        | ADN-63-80-I-P-A                                                                       | ★ 536340        | ADN-63-80-A-P-A                                                                     |                 |
|                                                                                   |          | 80               | 10              | ★ 536363                                                                              | ADN-80-10-I-P-A | ★ 536353                                                                            | ADN-80-10-A-P-A |
|                                                                                   | 15       |                  | ★ 536364        | ADN-80-15-I-P-A                                                                       | ★ 536354        | ADN-80-15-A-P-A                                                                     |                 |
|                                                                                   | 20       |                  | ★ 536365        | ADN-80-20-I-P-A                                                                       | ★ 536355        | ADN-80-20-A-P-A                                                                     |                 |
| 25                                                                                | ★ 536366 |                  | ADN-80-25-I-P-A | ★ 536356                                                                              | ADN-80-25-A-P-A |                                                                                     |                 |
| 30                                                                                | ★ 536367 |                  | ADN-80-30-I-P-A | ★ 536357                                                                              | ADN-80-30-A-P-A |                                                                                     |                 |
| 40                                                                                | ★ 536368 |                  | ADN-80-40-I-P-A | ★ 536358                                                                              | ADN-80-40-A-P-A |                                                                                     |                 |
| 50                                                                                | ★ 536369 |                  | ADN-80-50-I-P-A | ★ 536359                                                                              | ADN-80-50-A-P-A |                                                                                     |                 |
| 60                                                                                | ★ 536370 |                  | ADN-80-60-I-P-A | ★ 536360                                                                              | ADN-80-60-A-P-A |                                                                                     |                 |
| 80                                                                                | ★ 536371 |                  | ADN-80-80-I-P-A | ★ 536361                                                                              | ADN-80-80-A-P-A |                                                                                     |                 |


## Datasheet

## ★ Core Range


| Ordering data<br>Type                                                            | Piston ø<br>[mm] | Stroke<br>[mm] | I – Piston rod with female thread                       |                   | A – Piston rod with male thread                         |                   |
|----------------------------------------------------------------------------------|------------------|----------------|---------------------------------------------------------|-------------------|---------------------------------------------------------|-------------------|
|                                                                                  |                  |                | PPS – Pneumatic cushioning, self-adjusting at both ends |                   | PPS – Pneumatic cushioning, self-adjusting at both ends |                   |
|                                                                                  |                  |                | Part no.                                                | Type              | Part no.                                                | Type              |
|  | 32               | 10             | ★ 572646                                                | ADN-32-10-I-PPS-A | ★ 572655                                                | ADN-32-10-A-PPS-A |
|                                                                                  |                  | 15             | ★ 572647                                                | ADN-32-15-I-PPS-A | ★ 572656                                                | ADN-32-15-A-PPS-A |
|                                                                                  |                  | 20             | ★ 572648                                                | ADN-32-20-I-PPS-A | ★ 572657                                                | ADN-32-20-A-PPS-A |
|                                                                                  |                  | 25             | ★ 572649                                                | ADN-32-25-I-PPS-A | ★ 572658                                                | ADN-32-25-A-PPS-A |
|                                                                                  |                  | 30             | ★ 572650                                                | ADN-32-30-I-PPS-A | ★ 572659                                                | ADN-32-30-A-PPS-A |
|                                                                                  |                  | 40             | ★ 572651                                                | ADN-32-40-I-PPS-A | ★ 572660                                                | ADN-32-40-A-PPS-A |
|                                                                                  |                  | 50             | ★ 572652                                                | ADN-32-50-I-PPS-A | ★ 572661                                                | ADN-32-50-A-PPS-A |
|                                                                                  |                  | 60             | ★ 572653                                                | ADN-32-60-I-PPS-A | ★ 572662                                                | ADN-32-60-A-PPS-A |
|                                                                                  | 80               | ★ 572654       | ADN-32-80-I-PPS-A                                       | ★ 572663          | ADN-32-80-A-PPS-A                                       |                   |
|                                                                                  | 40               | 10             | ★ 572664                                                | ADN-40-10-I-PPS-A | ★ 572673                                                | ADN-40-10-A-PPS-A |
|                                                                                  |                  | 15             | ★ 572665                                                | ADN-40-15-I-PPS-A | ★ 572674                                                | ADN-40-15-A-PPS-A |
|                                                                                  |                  | 20             | ★ 572666                                                | ADN-40-20-I-PPS-A | ★ 572675                                                | ADN-40-20-A-PPS-A |
|                                                                                  |                  | 25             | ★ 572667                                                | ADN-40-25-I-PPS-A | ★ 572676                                                | ADN-40-25-A-PPS-A |
|                                                                                  |                  | 30             | ★ 572668                                                | ADN-40-30-I-PPS-A | ★ 572677                                                | ADN-40-30-A-PPS-A |
|                                                                                  |                  | 40             | ★ 572669                                                | ADN-40-40-I-PPS-A | ★ 572678                                                | ADN-40-40-A-PPS-A |
|                                                                                  |                  | 50             | ★ 572670                                                | ADN-40-50-I-PPS-A | ★ 572679                                                | ADN-40-50-A-PPS-A |
|                                                                                  |                  | 60             | ★ 572671                                                | ADN-40-60-I-PPS-A | ★ 572680                                                | ADN-40-60-A-PPS-A |
|                                                                                  | 80               | ★ 572672       | ADN-40-80-I-PPS-A                                       | ★ 572681          | ADN-40-80-A-PPS-A                                       |                   |
|                                                                                  | 50               | 10             | ★ 572682                                                | ADN-50-10-I-PPS-A | ★ 572691                                                | ADN-50-10-A-PPS-A |
|                                                                                  |                  | 15             | ★ 572683                                                | ADN-50-15-I-PPS-A | ★ 572692                                                | ADN-50-15-A-PPS-A |
|                                                                                  |                  | 20             | ★ 572684                                                | ADN-50-20-I-PPS-A | ★ 572693                                                | ADN-50-20-A-PPS-A |
|                                                                                  |                  | 25             | ★ 572685                                                | ADN-50-25-I-PPS-A | ★ 572694                                                | ADN-50-25-A-PPS-A |
|                                                                                  |                  | 30             | ★ 572686                                                | ADN-50-30-I-PPS-A | ★ 572695                                                | ADN-50-30-A-PPS-A |
|                                                                                  |                  | 40             | ★ 572687                                                | ADN-50-40-I-PPS-A | ★ 572696                                                | ADN-50-40-A-PPS-A |
|                                                                                  |                  | 50             | ★ 572688                                                | ADN-50-50-I-PPS-A | ★ 572697                                                | ADN-50-50-A-PPS-A |
|                                                                                  |                  | 60             | ★ 572689                                                | ADN-50-60-I-PPS-A | ★ 572698                                                | ADN-50-60-A-PPS-A |
|                                                                                  | 80               | ★ 572690       | ADN-50-80-I-PPS-A                                       | ★ 572699          | ADN-50-80-A-PPS-A                                       |                   |

## Datasheet


## ★ Core Range

| Ordering data<br>Type                                                             | Piston ø<br>[mm] | Stroke<br>[mm] | I – Piston rod with female thread                       |                   | A – Piston rod with male thread                         |                   |
|-----------------------------------------------------------------------------------|------------------|----------------|---------------------------------------------------------|-------------------|---------------------------------------------------------|-------------------|
|                                                                                   |                  |                | PPS – Pneumatic cushioning, self-adjusting at both ends |                   | PPS – Pneumatic cushioning, self-adjusting at both ends |                   |
|                                                                                   |                  |                | Part no.                                                | Type              | Part no.                                                | Type              |
|  | 63               | 10             | ★ 572700                                                | ADN-63-10-I-PPS-A | ★ 572709                                                | ADN-63-10-A-PPS-A |
|                                                                                   |                  | 15             | ★ 572701                                                | ADN-63-15-I-PPS-A | ★ 572710                                                | ADN-63-15-A-PPS-A |
|                                                                                   |                  | 20             | ★ 572702                                                | ADN-63-20-I-PPS-A | ★ 572711                                                | ADN-63-20-A-PPS-A |
|                                                                                   |                  | 25             | ★ 572703                                                | ADN-63-25-I-PPS-A | ★ 572712                                                | ADN-63-25-A-PPS-A |
|                                                                                   |                  | 30             | ★ 572704                                                | ADN-63-30-I-PPS-A | ★ 572713                                                | ADN-63-30-A-PPS-A |
|                                                                                   |                  | 40             | ★ 572705                                                | ADN-63-40-I-PPS-A | ★ 572714                                                | ADN-63-40-A-PPS-A |
|                                                                                   |                  | 50             | ★ 572706                                                | ADN-63-50-I-PPS-A | ★ 572715                                                | ADN-63-50-A-PPS-A |
|                                                                                   |                  | 60             | ★ 572707                                                | ADN-63-60-I-PPS-A | ★ 572716                                                | ADN-63-60-A-PPS-A |
|                                                                                   | 80               | ★ 572708       | ADN-63-80-I-PPS-A                                       | ★ 572717          | ADN-63-80-A-PPS-A                                       |                   |
|                                                                                   | 80               | 10             | ★ 572718                                                | ADN-80-10-I-PPS-A | ★ 572727                                                | ADN-80-10-A-PPS-A |
|                                                                                   |                  | 15             | ★ 572719                                                | ADN-80-15-I-PPS-A | ★ 572728                                                | ADN-80-15-A-PPS-A |
|                                                                                   |                  | 20             | ★ 572720                                                | ADN-80-20-I-PPS-A | ★ 572729                                                | ADN-80-20-A-PPS-A |
|                                                                                   |                  | 25             | ★ 572721                                                | ADN-80-25-I-PPS-A | ★ 572730                                                | ADN-80-25-A-PPS-A |
|                                                                                   |                  | 30             | ★ 572722                                                | ADN-80-30-I-PPS-A | ★ 572731                                                | ADN-80-30-A-PPS-A |
|                                                                                   |                  | 40             | ★ 572723                                                | ADN-80-40-I-PPS-A | ★ 572732                                                | ADN-80-40-A-PPS-A |
|                                                                                   |                  | 50             | ★ 572724                                                | ADN-80-50-I-PPS-A | ★ 572733                                                | ADN-80-50-A-PPS-A |
|                                                                                   |                  | 60             | ★ 572725                                                | ADN-80-60-I-PPS-A | ★ 572734                                                | ADN-80-60-A-PPS-A |
|                                                                                   | 80               | ★ 572726       | ADN-80-80-I-PPS-A                                       | ★ 572735          | ADN-80-80-A-PPS-A                                       |                   |

## Datasheet

| Ordering data<br>Type | Piston ø<br>[mm] | Stroke<br>[mm] | I – Piston rod with female thread<br>P – Elastic cushioning rings/plates at both ends |                  | A – Piston rod with male thread<br>P – Elastic cushioning rings/plates at both ends |                  |
|-----------------------|------------------|----------------|---------------------------------------------------------------------------------------|------------------|-------------------------------------------------------------------------------------|------------------|
|                       |                  |                | Part no.                                                                              | Type             | Part no.                                                                            | Type             |
|                       |                  |                |       | 12               | 35                                                                                  | 8178328          |
|                       |                  | 50             | 8178550                                                                               | ADN-12-50-I-P-A  | 8178548                                                                             | ADN-12-50-A-P-A  |
|                       |                  | 60             | 604883                                                                                | ADN-12-60-I-P-A  | 8178549                                                                             | ADN-12-60-A-P-A  |
|                       | 16               | 35             | 8178765                                                                               | ADN-16-35-I-P-A  | 8178762                                                                             | ADN-16-35-A-P-A  |
|                       |                  | 60             | 8178766                                                                               | ADN-16-60-I-P-A  | 8178763                                                                             | ADN-16-60-A-P-A  |
|                       |                  | 70             | 8178767                                                                               | ADN-16-70-I-P-A  | 594950                                                                              | ADN-16-70-A-P-A  |
|                       | 20               | 35             | 578011                                                                                | ADN-20-35-I-P-A  | 8178859                                                                             | ADN-20-35-A-P-A  |
|                       |                  | 70             | 8178862                                                                               | ADN-20-70-I-P-A  | 595275                                                                              | ADN-20-70-A-P-A  |
|                       | 25               | 35             | 608920                                                                                | ADN-25-35-I-P-A  | 574647                                                                              | ADN-25-35-A-P-A  |
|                       |                  | 70             | 8178880                                                                               | ADN-25-70-I-P-A  | 8178877                                                                             | ADN-25-70-A-P-A  |
|                       |                  | 80             | 578450                                                                                | ADN-25-80-I-P-A  | 576652                                                                              | ADN-25-80-A-P-A  |
|                       | 32               | 35             | 8179019                                                                               | ADN-32-35-I-P-A  | 576645                                                                              | ADN-32-35-A-P-A  |
|                       |                  | 70             | 8173462                                                                               | ADN-32-70-I-P-A  | 564092                                                                              | ADN-32-70-A-P-A  |
|                       | 40               | 35             | 8179033                                                                               | ADN-40-35-I-P-A  | 8179031                                                                             | ADN-40-35-A-P-A  |
|                       |                  | 70             | 8179034                                                                               | ADN-40-70-I-P-A  | 582549                                                                              | ADN-40-70-A-P-A  |
|                       | 50               | 35             | 8178619                                                                               | ADN-50-35-I-P-A  | 8178336                                                                             | ADN-50-35-A-P-A  |
|                       |                  | 70             | 8178338                                                                               | ADN-50-70-I-P-A  | 572851                                                                              | ADN-50-70-A-P-A  |
|                       | 63               | 35             | 8178659                                                                               | ADN-63-35-I-P-A  | 8178283                                                                             | ADN-63-35-A-P-A  |
|                       |                  | 70             | 8178285                                                                               | ADN-63-70-I-P-A  | 8178284                                                                             | ADN-63-70-A-P-A  |
|                       | 100              | 10             | 536384                                                                                | ADN-100-10-I-P-A | 536374                                                                              | ADN-100-10-A-P-A |
|                       |                  | 15             | 536385                                                                                | ADN-100-15-I-P-A | 536375                                                                              | ADN-100-15-A-P-A |
|                       |                  | 20             | 536386                                                                                | ADN-100-20-I-P-A | 536376                                                                              | ADN-100-20-A-P-A |
|                       |                  | 25             | 536387                                                                                | ADN-100-25-I-P-A | 536377                                                                              | ADN-100-25-A-P-A |
|                       |                  | 30             | 536388                                                                                | ADN-100-30-I-P-A | 536378                                                                              | ADN-100-30-A-P-A |
|                       |                  | 40             | 536389                                                                                | ADN-100-40-I-P-A | 536379                                                                              | ADN-100-40-A-P-A |
|                       |                  | 50             | 536390                                                                                | ADN-100-50-I-P-A | 536380                                                                              | ADN-100-50-A-P-A |
|                       |                  | 60             | 536391                                                                                | ADN-100-60-I-P-A | 536381                                                                              | ADN-100-60-A-P-A |
|                       |                  | 80             | 536392                                                                                | ADN-100-80-I-P-A | 536382                                                                              | ADN-100-80-A-P-A |

## Datasheet

| Ordering data<br>Type | Piston ø<br>[mm] | Stroke<br>[mm] | I – Piston rod with female thread<br>PPS – Pneumatic cushioning, self-adjusting at both ends |                    | A – Piston rod with male thread<br>PPS – Pneumatic cushioning, self-adjusting at both ends |                    |
|-----------------------|------------------|----------------|----------------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------------------|--------------------|
|                       |                  |                | Part no.                                                                                     | Type               | Part no.                                                                                   | Type               |
|                       |                  |                |             | 20                 | 10                                                                                         | 577158             |
|                       |                  | 15             | 577159                                                                                       | ADN-20-15-I-PPS-A  | 577167                                                                                     | ADN-20-15-A-PPS-A  |
|                       |                  | 20             | 577160                                                                                       | ADN-20-20-I-PPS-A  | 577168                                                                                     | ADN-20-20-A-PPS-A  |
|                       |                  | 25             | 577161                                                                                       | ADN-20-25-I-PPS-A  | 577169                                                                                     | ADN-20-25-A-PPS-A  |
|                       |                  | 30             | 577162                                                                                       | ADN-20-30-I-PPS-A  | 577170                                                                                     | ADN-20-30-A-PPS-A  |
|                       |                  | 35             | 8178865                                                                                      | ADN-20-35-I-PPS-A  | 8178863                                                                                    | ADN-20-35-A-PPS-A  |
|                       |                  | 40             | 577163                                                                                       | ADN-20-40-I-PPS-A  | 577171                                                                                     | ADN-20-40-A-PPS-A  |
|                       |                  | 50             | 577164                                                                                       | ADN-20-50-I-PPS-A  | 577172                                                                                     | ADN-20-50-A-PPS-A  |
|                       |                  | 60             | 577165                                                                                       | ADN-20-60-I-PPS-A  | 577173                                                                                     | ADN-20-60-A-PPS-A  |
|                       |                  | 70             | 8178866                                                                                      | ADN-20-70-I-PPS-A  | 593451                                                                                     | ADN-20-70-A-PPS-A  |
|                       | 25               | 10             | 577174                                                                                       | ADN-25-10-I-PPS-A  | 577182                                                                                     | ADN-25-10-A-PPS-A  |
|                       |                  | 15             | 577175                                                                                       | ADN-25-15-I-PPS-A  | 577183                                                                                     | ADN-25-15-A-PPS-A  |
|                       |                  | 20             | 577176                                                                                       | ADN-25-20-I-PPS-A  | 577184                                                                                     | ADN-25-20-A-PPS-A  |
|                       |                  | 25             | 577177                                                                                       | ADN-25-25-I-PPS-A  | 577185                                                                                     | ADN-25-25-A-PPS-A  |
|                       |                  | 30             | 577178                                                                                       | ADN-25-30-I-PPS-A  | 577186                                                                                     | ADN-25-30-A-PPS-A  |
|                       |                  | 35             | 8178885                                                                                      | ADN-25-35-I-PPS-A  | 8178882                                                                                    | ADN-25-35-A-PPS-A  |
|                       |                  | 40             | 577179                                                                                       | ADN-25-40-I-PPS-A  | 577187                                                                                     | ADN-25-40-A-PPS-A  |
|                       |                  | 50             | 577180                                                                                       | ADN-25-50-I-PPS-A  | 577188                                                                                     | ADN-25-50-A-PPS-A  |
|                       |                  | 60             | 577181                                                                                       | ADN-25-60-I-PPS-A  | 577189                                                                                     | ADN-25-60-A-PPS-A  |
|                       |                  | 70             | 8178886                                                                                      | ADN-25-70-I-PPS-A  | 8178883                                                                                    | ADN-25-70-A-PPS-A  |
|                       |                  | 80             | 8178887                                                                                      | ADN-25-80-I-PPS-A  | 8178884                                                                                    | ADN-25-80-A-PPS-A  |
|                       | 32               | 35             | 8179023                                                                                      | ADN-32-35-I-PPS-A  | 8179021                                                                                    | ADN-32-35-A-PPS-A  |
|                       |                  | 70             | 8179024                                                                                      | ADN-32-70-I-PPS-A  | 8179022                                                                                    | ADN-32-70-A-PPS-A  |
|                       | 40               | 35             | 8179037                                                                                      | ADN-40-35-I-PPS-A  | 8179035                                                                                    | ADN-40-35-A-PPS-A  |
|                       |                  | 70             | 8179038                                                                                      | ADN-40-70-I-PPS-A  | 8179036                                                                                    | ADN-40-70-A-PPS-A  |
|                       | 50               | 35             | 8178620                                                                                      | ADN-50-35-I-PPS-A  | 8178339                                                                                    | ADN-50-35-A-PPS-A  |
|                       |                  | 70             | 8178341                                                                                      | ADN-50-70-I-PPS-A  | 8178340                                                                                    | ADN-50-70-A-PPS-A  |
|                       | 63               | 35             | 609539                                                                                       | ADN-63-35-I-PPS-A  | 610152                                                                                     | ADN-63-35-A-PPS-A  |
|                       |                  | 70             | 609538                                                                                       | ADN-63-70-I-PPS-A  | 8178287                                                                                    | ADN-63-70-A-PPS-A  |
|                       | 100              | 15             | 577191                                                                                       | ADN-100-15-I-PPS-A | 577200                                                                                     | ADN-100-15-A-PPS-A |
|                       |                  | 20             | 577192                                                                                       | ADN-100-20-I-PPS-A | 577201                                                                                     | ADN-100-20-A-PPS-A |
|                       |                  | 25             | 577193                                                                                       | ADN-100-25-I-PPS-A | 577202                                                                                     | ADN-100-25-A-PPS-A |
|                       |                  | 30             | 577194                                                                                       | ADN-100-30-I-PPS-A | 577203                                                                                     | ADN-100-30-A-PPS-A |
|                       |                  | 40             | 577195                                                                                       | ADN-100-40-I-PPS-A | 577204                                                                                     | ADN-100-40-A-PPS-A |
|                       |                  | 50             | 577196                                                                                       | ADN-100-50-I-PPS-A | 577205                                                                                     | ADN-100-50-A-PPS-A |
|                       |                  | 60             | 577197                                                                                       | ADN-100-60-I-PPS-A | 577206                                                                                     | ADN-100-60-A-PPS-A |
|                       |                  | 80             | 577198                                                                                       | ADN-100-80-I-PPS-A | 577207                                                                                     | ADN-100-80-A-PPS-A |

Ordering data – Modular product system, basic version and variants

| Ordering table    |                                            |               |                                                   |               |               |               |            |            |            |
|-------------------|--------------------------------------------|---------------|---------------------------------------------------|---------------|---------------|---------------|------------|------------|------------|
| Size              | 12                                         | 16            | 20                                                | 25            | 32            | 40            | Conditions | Code       | Enter code |
| Module no.        | <b>536203</b>                              | <b>536218</b> | <b>536233</b>                                     | <b>536250</b> | <b>536267</b> | <b>536288</b> |            |            |            |
| Function          | Compact cylinder, double-acting            |               |                                                   |               |               |               |            | <b>ADN</b> | ADN        |
| Standard          | Based on ISO 21287                         |               | Conforms to ISO 21287                             |               |               |               |            |            |            |
| Piston ø [mm]     | 12                                         | 16            | 20                                                | 25            | 32            | 40            |            | ★ -...     |            |
| Stroke [mm]       | 1 ... 300                                  |               |                                                   |               | 1 ... 400     |               |            | ★ -...     |            |
| Piston rod thread | Male thread                                |               |                                                   |               |               |               |            | ★ -A       |            |
|                   | Female thread                              |               |                                                   |               |               |               | [1]        | ★ -I       |            |
| Cushioning        | Elastic cushioning rings/pads at both ends |               |                                                   |               |               |               |            | ★ -P       |            |
|                   | -                                          |               | Pneumatic cushioning, self-adjusting at both ends |               |               |               | [8]        | ★ -PPS     |            |
| Position sensing  | Via proximity switch                       |               |                                                   |               |               |               |            | ★ -A       | -A         |

[1] I Not with piston rod type S20.  
Not with extended male thread K2

[8] PPS Not with improved running performance K10, temperature resistance S6, low temperature TT, wiper seal R8  
Minimum stroke 5 mm



## Ordering data – Modular product system, basic version and variants

| Ordering table               |                                                                            |                            |                                      |          |           |           |            |          |            |
|------------------------------|----------------------------------------------------------------------------|----------------------------|--------------------------------------|----------|-----------|-----------|------------|----------|------------|
| Size                         | 12                                                                         | 16                         | 20                                   | 25       | 32        | 40        | Conditions | Code     | Enter code |
| Piston rod type              | Through piston rod                                                         |                            |                                      |          |           |           | [2]        | ★ -S2    |            |
|                              | -                                                                          | Through, hollow piston rod |                                      |          |           | 1 ... 400 |            | [2]      | -S20       |
| [mm]                         |                                                                            |                            |                                      |          |           |           |            |          |            |
| Extended male thread         | Extended male piston rod thread                                            |                            |                                      |          |           |           |            |          |            |
|                              | 1 ... 10                                                                   |                            | 1 ... 20                             |          |           |           |            | -...K2   |            |
| Custom piston rod thread     | Male thread                                                                | M6                         | M8                                   | M10x1.25 | M10x1.25  | M10       | M10        | -“...”K5 |            |
|                              | Female thread                                                              | -                          | -                                    | M5       | M5        | M6        | M6         |          |            |
| Extended piston rod          | Extended piston rod                                                        |                            |                                      |          |           |           |            |          |            |
|                              | 1 ... 300                                                                  |                            |                                      |          | 1 ... 400 |           | [3]        | ★ -...K8 |            |
| Improved running performance | -                                                                          | -                          | Smooth anodised aluminium piston rod |          |           |           | [4]        | -K10     |            |
| Temperature resistance       | Heat-resistant seals max. 120°C                                            |                            |                                      |          |           |           |            | ★ -S6    |            |
| Corrosion protection         | High corrosion protection                                                  |                            |                                      |          |           |           | [5]        | ★ -R3    |            |
| Captive rating plate         | Laser-etched rating plate                                                  |                            |                                      |          |           |           |            | -TL      |            |
| Low temperature [°C]         | -                                                                          | -                          | -40 ... +80                          |          |           |           | [6] [7]    | -TT      |            |
| Wiper seal                   | -                                                                          | -                          | Dust protection                      |          |           |           | [6]        | -R8      |            |
| Custom material properties   | Without                                                                    |                            |                                      |          |           |           |            |          |            |
|                              | Recommended for production systems for manufacturing lithium-ion batteries |                            |                                      |          |           |           | [9]        | -F1A     |            |

[2] **S2, S20** Not with improved running performance K10.  
Not with corrosion protection R3.  
Not with wiper seal R8

[3] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[4] **K10** Not with extended male thread K2.  
Not with custom piston rod thread K5.  
Not with corrosion protection R3

[5] **R3** Not with captive rating plate TL  
Not with wiper seal R8

[6] **TT, R8** Not with improved running performance K10.  
Not with temperature resistance S6

[7] **TT** Not with wiper seal R8

[9] **F1A** Not with S6, S20, K10, R3, TL, TT, R8, PPS

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

## Ordering data – Modular product system, basic version and variants

| Ordering table    |                                                   |               |               |               |                    |            |            | Enter code |
|-------------------|---------------------------------------------------|---------------|---------------|---------------|--------------------|------------|------------|------------|
| Size              | 50                                                | 63            | 80            | 100           | 125                | Conditions | Code       |            |
| Module no.        | <b>536309</b>                                     | <b>536330</b> | <b>536351</b> | <b>536372</b> | <b>536393</b>      |            |            |            |
| Function          | Compact cylinder, double-acting                   |               |               |               |                    |            | <b>ADN</b> | ADN        |
| Standard          | Conforms to ISO 21287                             |               |               |               | Based on ISO 21287 |            |            |            |
| Piston ø [mm]     | 50                                                | 63            | 80            | –             | –                  |            | ★ -...     |            |
|                   | –                                                 | –             | –             | 100           | 125                |            | -...       |            |
| Stroke [mm]       | 1 ... 400                                         |               | 1 ... 500     |               |                    |            | ★ -...     |            |
| Piston rod thread | Male thread                                       |               |               |               |                    |            | ★ -A       |            |
|                   | Female thread                                     |               |               |               |                    | [1]        | ★ -I       |            |
| Cushioning        | Elastic cushioning rings/pads at both ends        |               |               |               |                    |            | ★ -P       |            |
|                   | Pneumatic cushioning, self-adjusting at both ends |               |               |               | –                  | [8]        | ★ -PPS     |            |
| Position sensing  | Via proximity switch                              |               |               |               |                    |            | ★ -A       | -A         |


[1] I Not with piston rod type S20.  
Not with extended male thread K2

[8] PPS Not with improved running performance K10, temperature resistance S6, low temperature TT, wiper seal R8  
Minimum stroke 5 mm

## Ordering data – Modular product system, basic version and variants

| Ordering table               |                                                                            |            |            |                       |                       |            |          | Enter code |
|------------------------------|----------------------------------------------------------------------------|------------|------------|-----------------------|-----------------------|------------|----------|------------|
| Size                         | 50                                                                         | 63         | 80         | 100                   | 125                   | Conditions | Code     |            |
| Piston rod type              | Through piston rod                                                         |            |            |                       |                       | [2]        | ★ -S2    |            |
|                              | Through, hollow piston rod                                                 |            |            |                       |                       | [2]        | -S20     |            |
| [mm]                         | 1 ... 400                                                                  |            | 1 ... 500  |                       |                       |            |          |            |
| Extended male thread         | Extended male piston rod thread                                            |            |            |                       |                       |            |          |            |
| [mm]                         | 1 ... 20                                                                   |            | 1 ... 30   |                       | 1 ... 40              |            | -...K2   |            |
| Custom piston rod thread     | Male thread                                                                | M12<br>M16 | M12<br>M16 | M16<br>M20<br>M20x1.5 | M16<br>M20<br>M20x1.5 | M20        | -“...”K5 |            |
|                              | Female thread                                                              | M8         | M8         | M10                   | M10                   | -          |          |            |
| Extended piston rod          | Extended piston rod                                                        |            |            |                       |                       |            |          |            |
| [mm]                         | 1 ... 400                                                                  |            | 1 ... 500  |                       |                       | [3]        | ★ -...K8 |            |
| Improved running performance | Smooth anodised aluminium piston rod                                       |            |            |                       |                       | [4]        | -K10     |            |
| [mm]                         | 2 ... 400                                                                  |            | 5 ... 400  | 5 ... 500             |                       |            |          |            |
| Temperature resistance       | Heat-resistant seals max. 120°C                                            |            |            |                       |                       |            | ★ -S6    |            |
| Corrosion protection         | High corrosion protection                                                  |            |            |                       |                       | [5]        | ★ -R3    |            |
| Captive rating plate         | Laser-etched rating plate                                                  |            |            |                       |                       |            | -TL      |            |
| Low temperature [°C]         | -40 ... +80                                                                |            |            |                       | -                     | [6] [7]    | -TT      |            |
| Wiper seal                   | Dust protection                                                            |            |            |                       | -                     | [6]        | -R8      |            |
| Custom material properties   | Without                                                                    |            |            |                       |                       |            |          |            |
|                              | Recommended for production systems for manufacturing lithium-ion batteries |            |            |                       |                       | [9]        | -F1A     |            |

- [2] **S2, S20** Not with improved running performance K10.  
Not with corrosion protection R3.  
Not with wiper seal R8
- [3] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length
- [4] **K10** Not with extended male thread K2.  
Not with custom piston rod thread K5.  
Not with corrosion protection R3
- [5] **R3** Not with captive rating plate TL  
Not with wiper seal R8
- [6] **TT, R8** Not with improved running performance K10.  
Not with temperature resistance S6
- [7] **TT** Not with wiper seal R8
- [9] **F1A** Not with S6, S20, K10, R3, TL, TT, R8, PPS


**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

## Ordering data – Modular product system, S10 – constant motion, S11 – low friction

| Ordering table               |                                                   |               |                                      |                 |                 |               |            |      | Conditions    | Code            | Enter code |
|------------------------------|---------------------------------------------------|---------------|--------------------------------------|-----------------|-----------------|---------------|------------|------|---------------|-----------------|------------|
| Size                         | 12                                                | 16            | 20                                   | 25              | 32              | 40            |            |      |               |                 |            |
| Module no.                   | <b>536203</b>                                     | <b>536218</b> | <b>536233</b>                        | <b>536250</b>   | <b>536267</b>   | <b>536288</b> |            |      |               |                 |            |
| Function                     | Compact cylinder, double-acting                   |               |                                      |                 |                 |               |            |      | <b>ADN</b>    |                 | ADN        |
| Standard                     | Based on ISO 21287                                |               | Conforms to ISO 21287                |                 |                 |               |            |      |               |                 |            |
| Piston ø [mm]                | 12                                                | 16            | 20                                   | 25              | 32              | 40            |            | -... |               |                 |            |
| Stroke [mm]                  | 1 ... 300                                         |               |                                      |                 | 1 ... 400       |               |            | -... |               |                 |            |
| Piston rod thread            | Male thread                                       |               |                                      |                 |                 |               |            |      | <b>-A</b>     |                 |            |
|                              | Female thread                                     |               |                                      |                 |                 |               |            | [1]  | <b>-I</b>     |                 |            |
| Cushioning                   | Elastic cushioning rings/pads at both ends        |               |                                      |                 |                 |               |            |      | <b>-P</b>     |                 | -P         |
| Position sensing             | Via proximity switch                              |               |                                      |                 |                 |               |            |      | <b>-A</b>     |                 | -A         |
| Extended male thread [mm]    | Extended male piston rod thread                   |               |                                      |                 |                 |               |            |      |               |                 |            |
|                              | 1 ... 10                                          |               | 1 ... 20                             |                 |                 |               |            |      | <b>-...K2</b> |                 |            |
| Custom piston rod thread     | Male thread                                       | M6            | M8                                   | M10x1.25<br>M10 | M10x1.25<br>M10 | M10<br>M12    | M10<br>M12 |      |               | <b>-“...”K5</b> |            |
|                              | Female thread                                     | -             | -                                    | M5              | M5              | M6            | M6         |      |               |                 |            |
| Extended piston rod [mm]     | Extended piston rod                               |               |                                      |                 | 1 ... 300       |               | 1 ... 400  |      | [2]           | <b>-...K8</b>   |            |
| Improved running performance | -                                                 | -             | Smooth anodised aluminium piston rod |                 |                 |               |            | [3]  | <b>-K10</b>   |                 |            |
| Constant motion [mm]         | Slow speed (constant motion at low piston speeds) |               |                                      |                 |                 |               |            |      | [4]           | <b>-S10</b>     |            |
|                              | Restricted stroke                                 |               |                                      |                 |                 |               |            |      |               |                 |            |
|                              | 20 ... 300                                        |               |                                      |                 | 20 ... 400      |               |            |      |               |                 |            |
| Low friction                 | Low friction                                      |               |                                      |                 |                 |               |            | [5]  | <b>-S11</b>   |                 |            |
| Corrosion protection         | High corrosion protection                         |               |                                      |                 |                 |               |            | [6]  | <b>-R3</b>    |                 |            |
| Captive rating plate         | Laser-etched rating plate                         |               |                                      |                 |                 |               |            |      | <b>-TL</b>    |                 |            |

- [1] **I** Not with extended male thread K2
- [2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length
- [3] **K10** Not with extended male thread K2  
Not with special piston rod thread K5  
Not with corrosion protection R3
- [4] **S10** Not with low friction S11
- [5] **S11** Not with constant motion S10
- [6] **R3** Not with captive rating plate TL



**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

## Ordering data – Modular product system, S10 – constant motion, S11 – low friction

| Ordering table                    |                                                        |               |               |               |                       |                       |               |                 |  |  |
|-----------------------------------|--------------------------------------------------------|---------------|---------------|---------------|-----------------------|-----------------------|---------------|-----------------|--|--|
| Size                              | 50                                                     | 63            | 80            | 100           | 125                   | Conditions            | Code          | Enter code      |  |  |
| Module no.                        | <b>536309</b>                                          | <b>536330</b> | <b>536351</b> | <b>536372</b> | <b>536393</b>         |                       |               |                 |  |  |
| Function                          | Compact cylinder, double-acting                        |               |               |               |                       |                       | <b>ADN</b>    | ADN             |  |  |
| Standard                          | Conforms to ISO 21287                                  |               |               |               | Based on ISO 21287    |                       |               |                 |  |  |
| Piston ø [mm]                     | 50                                                     | 63            | 80            | 100           | 125                   |                       | -...          |                 |  |  |
| Stroke [mm]                       | 1 ... 400                                              |               | 1 ... 500     |               |                       |                       | -...          |                 |  |  |
| Piston rod thread                 | Male thread                                            |               |               |               |                       |                       | <b>-A</b>     |                 |  |  |
|                                   | Female thread                                          |               |               |               |                       | [1]                   | <b>-I</b>     |                 |  |  |
| Cushioning                        | Elastic cushioning rings/pads at both ends             |               |               |               |                       |                       | <b>-P</b>     | -P              |  |  |
| Position sensing                  | Via proximity switch                                   |               |               |               |                       |                       | <b>-A</b>     | -A              |  |  |
| Extended male thread [mm]         | Extended male piston rod thread<br>1 ... 20            |               | 1 ... 30      |               | 1 ... 40              |                       | <b>-...K2</b> |                 |  |  |
| Custom piston rod thread          | Male thread                                            |               | M12<br>M16    | M12<br>M16    | M16<br>M20<br>M20x1.5 | M16<br>M20<br>M20x1.5 | M20           | <b>-“...”K5</b> |  |  |
|                                   | Female thread                                          |               | M8            | M8            | M10                   | M10                   | -             |                 |  |  |
| Extended piston rod [mm]          | Extended piston rod<br>1 ... 400                       |               | 1 ... 500     |               |                       |                       | [2]           | <b>-...K8</b>   |  |  |
| Improved running performance [mm] | Smooth anodised aluminium piston rod                   |               |               |               |                       |                       | [3]           | <b>-K10</b>     |  |  |
|                                   | Restricted stroke<br>2 ... 400   5 ... 400   5 ... 500 |               |               |               |                       |                       |               |                 |  |  |
| Constant motion [mm]              | Slow speed (constant motion at low piston speeds)      |               |               |               |                       |                       | [4]           | <b>-S10</b>     |  |  |
|                                   | Restricted stroke<br>20 ... 400                        |               | 20 ... 500    |               |                       |                       |               |                 |  |  |
| Low friction                      | Low friction                                           |               |               |               |                       |                       | [5]           | <b>-S11</b>     |  |  |
| Corrosion protection              | High corrosion protection                              |               |               |               |                       |                       | [6]           | <b>-R3</b>      |  |  |
| Captive rating plate              | Laser-etched rating plate                              |               |               |               |                       |                       |               | <b>-TL</b>      |  |  |

- [1] **I** Not with extended male thread K2  
 [2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length  
 [3] **K10** Not with extended male thread K2  
 Not with special piston rod thread K5  
 Not with corrosion protection R3  
 [4] **S10** Not with low friction S11  
 [5] **S11** Not with constant motion S10  
 [6] **R3** Not with captive rating plate TL

 **Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.


## Ordering data – Modular product system, Q – Square piston rod, non-rotating

| Ordering table                       |                                                        |                                                              |                       |                 |               |               |     | Conditions | Code       | Enter code |
|--------------------------------------|--------------------------------------------------------|--------------------------------------------------------------|-----------------------|-----------------|---------------|---------------|-----|------------|------------|------------|
| Size                                 | 12                                                     | 16                                                           | 20                    | 25              | 32            | 40            |     |            |            |            |
| Module no.                           | <b>536203</b>                                          | <b>536218</b>                                                | <b>536233</b>         | <b>536250</b>   | <b>536267</b> | <b>536288</b> |     |            |            |            |
| Function                             | Compact cylinder, double-acting                        |                                                              |                       |                 |               |               |     |            | <b>ADN</b> | ADN        |
| Standard                             | Based on ISO 21287                                     |                                                              | Conforms to ISO 21287 |                 |               |               |     |            |            |            |
| Piston ø [mm]                        | 12                                                     | 16                                                           | 20                    | 25              | 32            | 40            |     | ★ -...     |            |            |
| Stroke [mm]                          | 1 ... 300                                              |                                                              |                       |                 | 1 ... 400     |               |     | ★ -...     |            |            |
| Piston rod thread                    | Male thread                                            |                                                              |                       |                 |               |               |     |            | ★ -A       |            |
|                                      | Female thread                                          |                                                              |                       |                 |               |               |     | [1]        | ★ -I       |            |
| Cushioning                           | Elastic cushioning rings/pads at both ends             |                                                              |                       |                 |               |               |     |            | ★ -P       | -P         |
| Position sensing                     | Via proximity switch                                   |                                                              |                       |                 |               |               |     |            | ★ -A       | -A         |
| Protection against rotation          | Square piston rod                                      |                                                              |                       |                 |               |               |     |            | ★ -Q       | -Q         |
| Piston rod type                      | Through piston rod                                     |                                                              |                       |                 |               |               |     |            | ★ -S2      |            |
|                                      | -                                                      | Through, hollow piston rod<br>Restricted stroke<br>1 ... 200 |                       |                 |               | 1 ... 300     |     |            | -S20       |            |
| Extended male thread [mm]            | Extended male piston rod thread<br>1 ... 10   1 ... 20 |                                                              |                       |                 |               |               |     |            | -...K2     |            |
| Custom piston rod thread Male thread | M6                                                     | M8                                                           | M10x1.25<br>M10       | M10x1.25<br>M10 | M10           | M10           |     | -“...”K5   |            |            |
| Extended piston rod [mm]             | Extended piston rod<br>1 ... 300                       |                                                              |                       |                 | 1 ... 400     |               | [2] | ★ -...K8   |            |            |
| Temperature resistance               | Heat-resistant seals max. 120°C                        |                                                              |                       |                 |               |               |     |            | ★ -S6      |            |
| Corrosion protection                 | High corrosion protection                              |                                                              |                       |                 |               |               |     | [3]        | ★ -R3      |            |
| Captive rating plate                 | Laser-etched rating plate                              |                                                              |                       |                 |               |               |     |            | -TL        |            |

[1] I Not with piston rod type S20.  
Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] R3 Not with captive rating plate TL

 **Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

## Ordering data – Modular product system, Q – Square piston rod, non-rotating

| Ordering table                       |                                            |               |               |               |                    |            |            |            |  |
|--------------------------------------|--------------------------------------------|---------------|---------------|---------------|--------------------|------------|------------|------------|--|
| Size                                 | 50                                         | 63            | 80            | 100           | 125                | Conditions | Code       | Enter code |  |
| Module no.                           | <b>536309</b>                              | <b>536330</b> | <b>536351</b> | <b>536372</b> | <b>536393</b>      |            |            |            |  |
| Function                             | Compact cylinder, double-acting            |               |               |               |                    |            | <b>ADN</b> | ADN        |  |
| Standard                             | Conforms to ISO 21287                      |               |               |               | Based on ISO 21287 |            |            |            |  |
| Piston ø [mm]                        | 50                                         | 63            | 80            | 100           | 125                |            | ★ -...     |            |  |
| Stroke [mm]                          | 1 ... 400                                  |               | 1 ... 500     |               |                    |            | ★ -...     |            |  |
| Piston rod thread                    | Male thread                                |               |               |               |                    |            | ★ -A       |            |  |
|                                      | Female thread                              |               |               |               |                    | [1]        | ★ -I       |            |  |
| Cushioning                           | Elastic cushioning rings/pads at both ends |               |               |               |                    |            | ★ -P       | -P         |  |
| Position sensing                     | Via proximity switch                       |               |               |               |                    |            | ★ -A       | -A         |  |
| Protection against rotation          | Square piston rod                          |               |               |               |                    |            | ★ -Q       | -Q         |  |
| Piston rod type                      | Through piston rod                         |               |               |               |                    |            | ★ -S2      |            |  |
|                                      | Through, hollow piston rod                 |               |               |               |                    |            | -S20       |            |  |
|                                      | Restricted stroke [mm]                     | 1 ... 300     |               | 1 ... 400     |                    |            |            |            |  |
| Extended male thread [mm]            | Extended male piston rod thread            |               |               |               |                    |            | -...K2     |            |  |
| Custom piston rod thread Male thread | M12                                        | M12           | M16           | M16           | M20                |            | -“...”K5   |            |  |
| Extended piston rod [mm]             | 1 ... 400                                  |               | 1 ... 500     |               |                    | [2]        | ★ -...K8   |            |  |
| Temperature resistance               | Heat-resistant seals max. 120°C            |               |               |               |                    |            | ★ -S6      |            |  |
| Corrosion protection                 | High corrosion protection                  |               |               |               |                    | [3]        | ★ -R3      |            |  |
| Captive rating plate                 | Laser-etched rating plate                  |               |               |               |                    |            | -TL        |            |  |

[1] **I** Not with piston rod type S20.  
Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] **R3** Not with captive rating plate TL

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, S1 – Reinforced piston rod

| Ordering table            |                                                      |                 |                 |                 |                |                 |            |
|---------------------------|------------------------------------------------------|-----------------|-----------------|-----------------|----------------|-----------------|------------|
| Size                      | 25                                                   | 40              | 63              | 100             | Conditions     | Code            | Enter code |
| Module no.                | <b>536250</b>                                        | <b>536288</b>   | <b>536330</b>   | <b>536372</b>   |                |                 |            |
| Function                  | Compact cylinder, double-acting                      |                 |                 |                 |                | <b>ADN</b>      | ADN        |
| Standard                  | Conforms to ISO 21287                                |                 |                 |                 |                |                 |            |
| Piston Ø [mm]             | 25                                                   | 40              | 63              | 100             |                | -...            |            |
| Stroke [mm]               | 5 ... 300                                            | 10 ... 400      |                 | 10 ... 500      |                | -...            |            |
| Piston rod thread         | Male thread                                          |                 |                 |                 |                | <b>-A</b>       |            |
|                           | Female thread                                        |                 |                 |                 | [1]            | <b>-I</b>       |            |
| Cushioning                | Elastic cushioning rings/pads at both ends           |                 |                 |                 |                | <b>-P</b>       | -P         |
| Position sensing          | Via proximity switch                                 |                 |                 |                 |                | <b>-A</b>       | -A         |
| Extended male thread [mm] | Extended male piston rod thread<br>1 ... 20          |                 |                 | 1 ... 30        |                | <b>-...K2</b>   |            |
| Custom piston rod thread  | Male thread                                          | M10x1.25<br>M10 | M10x1.25<br>M12 | M12x1.25<br>M16 | M16x1.5<br>M20 | <b>-“...”K5</b> |            |
|                           | Female thread                                        | M5              | M8              | M10             | -              |                 |            |
| Extended piston rod [mm]  | Extended piston rod<br>1 ... 300                     |                 | 1 ... 400       | 1 ... 500       | [2]            | <b>-...K8</b>   |            |
| Temperature resistance    | Heat-resistant seals max. 120°C                      |                 |                 |                 |                | <b>-S6</b>      |            |
| Increased lateral force   | Reinforced piston rod or extended piston rod bearing |                 |                 |                 |                | <b>-S1</b>      | -S1        |
| Captive rating plate      | Laser-etched rating plate                            |                 |                 |                 |                | <b>-TL</b>      |            |

[1] **I** Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length



## Type codes

|     |                                                     |
|-----|-----------------------------------------------------|
| 001 | Series                                              |
| ADN | Compact cylinder, double-acting, based on ISO 21287 |

|     |                 |
|-----|-----------------|
| 002 | Piston diameter |
| 20  | 20              |
| 25  | 25              |
| 32  | 32              |
| 40  | 40              |
| 50  | 50              |
| 63  | 63              |
| 80  | 80              |
| 100 | 100             |

|     |            |
|-----|------------|
| 003 | Stroke     |
| ... | 10 ... 500 |

|     |               |
|-----|---------------|
| 004 | Clamping unit |
| KP  | Attached      |

|     |                        |
|-----|------------------------|
| 005 | Piston rod thread type |
| A   | Male thread            |
| I   | Female thread          |

|     |                                               |
|-----|-----------------------------------------------|
| 006 | Cushioning                                    |
| P   | Elastic cushioning rings/plates on both sides |

|     |                      |
|-----|----------------------|
| 007 | Position sensing     |
| A   | For proximity sensor |

|       |                             |
|-------|-----------------------------|
| 008   | Piston rod thread extension |
|       | None                        |
| ...K2 | 1 ... 30 mm                 |

|               |               |
|---------------|---------------|
| 009           | Custom thread |
| "M6"K5        | M6            |
| "M8"K5        | M8            |
| "M10"K5       | M10           |
| "M10x-1,25"K5 | M10x1.25      |
| "M12"K5       | M12           |
| "M16"K5       | M16           |
| "M20x-1,5"K5  | M20x1.5       |
| "M5"K5        | M5            |
| "M20"K5       | M20           |


|       |                      |
|-------|----------------------|
| 010   | Piston rod extension |
|       | None                 |
| ...K8 | 1 ... 500 mm         |

|     |                           |
|-----|---------------------------|
| 011 | Captive rating plate      |
|     | Rating plate, glued       |
| TL  | Laser etched rating plate |

# Compact cylinders ADN-KP, standard hole pattern, with clamping unit

## Datasheet

### Function



### Variants




K2



K5



K8



- - Diameter  
20 ... 100 mm

- - Stroke length  
10 ... 500 mm

### Note

If used in safety-oriented applications, additional measures are necessary, e.g. in Europe the standards listed in the EC Machinery Directive must be observed.

Without additional measures in accordance with legally specified minimum requirements, the product is not suitable as a safety-related component in control systems.

### General technical data

| Piston $\varnothing$                   | 20                                         | 25 | 32       | 40   | 50       | 63   | 80                | 100  |
|----------------------------------------|--------------------------------------------|----|----------|------|----------|------|-------------------|------|
| Pneumatic connection                   |                                            |    |          |      |          |      |                   |      |
| Cylinders                              | M5                                         | M5 | G1/8     | G1/8 | G1/8     | G1/8 | G1/8              | G1/8 |
| KP                                     | M5                                         | M5 | M5       | G1/8 | G1/8     | G1/8 | G1/8              | G1/8 |
| Female piston rod thread               |                                            |    |          |      |          |      |                   |      |
| -                                      | M6                                         |    | M8       |      | M10      |      | M12               |      |
| K5                                     | M5                                         |    | M6       |      | M8       |      | M10               |      |
| Male piston rod thread                 |                                            |    |          |      |          |      |                   |      |
| -                                      | M8                                         |    | M10x1.25 |      | M12x1.25 |      | M16x1.5           |      |
| K5                                     | M10; M10x1.25                              |    | M10; M12 |      | M12; M16 |      | M16; M20; M20x1.5 |      |
| Axial backlash under load              | [mm] 0.5                                   |    |          |      | 0.8      |      |                   |      |
| Design                                 | Piston                                     |    |          |      |          |      |                   |      |
|                                        | Piston rod                                 |    |          |      |          |      |                   |      |
|                                        | Cylinder barrel                            |    |          |      |          |      |                   |      |
| Cushioning                             | Elastic cushioning rings/pads at both ends |    |          |      |          |      |                   |      |
| Position sensing                       | Via proximity switch                       |    |          |      |          |      |                   |      |
| Type of mounting                       | With through-hole                          |    |          |      |          |      |                   |      |
|                                        | With female thread                         |    |          |      |          |      |                   |      |
|                                        | Via accessories                            |    |          |      |          |      |                   |      |
| Mounting position                      | Any                                        |    |          |      |          |      |                   |      |
| Clamping type with operating direction | At both ends                               |    |          |      |          |      |                   |      |

### Operating and environmental conditions

|                                              |                                                                                   |             |
|----------------------------------------------|-----------------------------------------------------------------------------------|-------------|
| Operating medium                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                         |             |
| Note on the operating/pilot medium           | Lubricated operation possible (in which case lubrication will always be required) |             |
| Operating pressure                           | [MPa]                                                                             | 0.15 ... 1  |
|                                              | [bar]                                                                             | 1.5 ... 10  |
| Min. release pressure                        | [MPa]                                                                             | 0.3         |
|                                              | [bar]                                                                             | 3           |
| Ambient temperature <sup>1)</sup>            | [°C]                                                                              | -10 ... +80 |
| Corrosion resistance class CRC <sup>2)</sup> | 2                                                                                 |             |

1) Note operating range of proximity switches

2) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Datasheet

| Impact energy [J]                       |     |     |     |     |    |     |     |     |
|-----------------------------------------|-----|-----|-----|-----|----|-----|-----|-----|
| Piston $\varnothing$                    | 20  | 25  | 32  | 40  | 50 | 63  | 80  | 100 |
| Max. impact energy in the end positions | 0.2 | 0.3 | 0.4 | 0.7 | 1  | 1.3 | 1.8 | 2.5 |


**Note**

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact speed:

$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

Maximum permissible mass:

$$m_2 = \frac{2 \times E}{v^2} - m_1$$

V Permissible impact velocity  
 E Max. impact energy  
 m1 Moving mass (drive)  
 m2 Moving payload

| Forces [N]                             |     |     |     |      |      |      |      |      |
|----------------------------------------|-----|-----|-----|------|------|------|------|------|
| Piston $\varnothing$                   | 20  | 25  | 32  | 40   | 50   | 63   | 80   | 100  |
| Theoretical force at 6 bar, advancing  | 188 | 295 | 483 | 754  | 1178 | 1870 | 3016 | 4712 |
| Theoretical force at 6 bar, retracting | 141 | 247 | 415 | 633  | 990  | 1682 | 2721 | 4418 |
| Static holding force                   | 350 | 350 | 600 | 1000 | 1400 | 2000 | 5000 | 5000 |


**Note.**


The specified holding force refers to a static load. If this value is exceeded, slippage may occur. Dynamic forces occurring during operation must

not exceed the static holding force. The clamping unit is not backlash-free in the clamped condition if varying loads are applied to the piston rod

**Actuation**

The clamping unit may only be released if the forces at the piston have reached equilibrium. Otherwise, there is a risk of accidents due to sudden movement of the piston rod.

Blocking off the compressed air supply at both ends (e.g. with a 5/3-way valve) does not provide any safety.


**Max. lateral force  $F_q$  as a function of projection  $x$** 


| Weight [g]                         |     |     |     |     |      |      |      |      |
|------------------------------------|-----|-----|-----|-----|------|------|------|------|
| Piston $\varnothing$               | 20  | 25  | 32  | 40  | 50   | 63   | 80   | 100  |
| Product weight with 0 mm stroke    | 282 | 344 | 503 | 789 | 1268 | 1894 | 3973 | 5497 |
| Additional weight per 10 mm stroke | 22  | 26  | 29  | 45  | 60   | 68   | 93   | 112  |
| Moving mass with 0 mm stroke       | 53  | 63  | 100 | 173 | 296  | 368  | 755  | 932  |
| Additional mass per 10 mm stroke   | 6   | 6   | 9   | 16  | 25   | 25   | 39   | 39   |

## Datasheet

### Materials

#### Sectional view



#### Compact cylinder


|     |                   |              |                                   |
|-----|-------------------|--------------|-----------------------------------|
| [1] | Cover             |              | Anodised aluminium                |
| [2] | Cylinder barrel   |              | Anodised aluminium                |
| [3] | Piston rod        |              | High-alloy steel                  |
| [4] | Flange screws     | ∅ 20 ... 63  | Galvanised steel                  |
|     |                   | ∅ 80 ... 100 | Standard screws, galvanised steel |
| –   | Seals             |              | Polyurethane, nitrile rubber      |
|     | Note on materials |              | RoHS-compliant                    |

Datasheet


Dimensions – Basic version

Download CAD data → [www.festo.com](http://www.festo.com)

∅ 20 ... 63



Only direct mounting is possible with this variant.




+ = plus stroke length


Dimensions – Basic version

Download CAD data → [www.festo.com](http://www.festo.com)

∅ 80, 100



Only direct mounting is possible with this variant.



+ = plus stroke length

| ∅<br>[mm] | BG<br>min. | D1<br>∅<br>H9 | D2<br>∅ | D5<br>∅          | E                     | E1   | EE   | G    | G1   | H1   | J2   |     |
|-----------|------------|---------------|---------|------------------|-----------------------|------|------|------|------|------|------|-----|
| 20        | 19.5       | 9             | 20      | 9 <sup>F9</sup>  | 35.5 <sup>+0.3</sup>  | M5   | M5   | 49.8 | 12   | 63   | 2.6  |     |
| 25        |            |               |         |                  | 39.5 <sup>+0.3</sup>  |      |      | 50.6 |      |      |      | 65  |
| 32        |            |               |         |                  | 47 <sup>+0.3</sup>    |      |      | 56.4 |      |      |      | 68  |
| 40        | 26         | 12            | 24      | 12 <sup>F9</sup> | 54.5 <sup>+0.3</sup>  | G1/8 | G1/8 | 60.4 | 15   | 89   | 8    |     |
| 50        |            |               | 30      |                  | 65.5 <sup>+0.3</sup>  |      |      | 67.4 |      | 108  |      |     |
| 63        |            |               | 38      |                  | 75.5 <sup>+0.3</sup>  |      |      | 76.8 |      | 120  |      |     |
| 80        | 17         | 12            | 48      | 15               | 95.5 <sup>+0.6</sup>  | G1/8 | G1/8 | 99   | 16.5 | 167  | 11.5 |     |
| 100       | 21.5       |               |         |                  | 113.5 <sup>+0.6</sup> |      |      | 99.6 |      | 21.5 |      | 176 |



| ∅<br>[mm] | PW<br>+0.2 | MM<br>∅ | PL<br>+0.2 | PL1<br>+0.2 | RT    | ST<br>h13 | T2<br>+0.2 | TG<br>±0.2 | ZA<br>±0.6 | ZB<br>+1.2 |
|-----------|------------|---------|------------|-------------|-------|-----------|------------|------------|------------|------------|
| 20        | 5          | 10      | 42.8       | 6           | M5    | 9         | 2.1        | 22         | 74.8       | 80.8       |
| 25        |            |         | 44.6       |             |       |           |            | 26         | 77.6       | 83.1       |
| 32        |            |         | 49.6       |             |       |           |            | 32.5       | 85.4       | 91.4       |
| 40        |            | 12      | 53.6       | 38          | 90.4  | 96.5      |            |            |            |            |
| 50        |            | 16      | 60.6       | 46.5        | 97.4  | 105.6     |            |            |            |            |
| 63        |            | 20      | 70         | 56.5        | 110.8 | 118.9     |            |            |            |            |
| 80        | 2.6        | 25      | 90.7       | 8.2         | M8    | 17        | 2.6        | 72         | 136.5      | 145.4      |
| 100       |            |         | 10.5       |             |       |           |            | M10        | 21         | 89         |

## Datasheet

### Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)


Basic version



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length



K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$



+ = plus stroke length

K5 – Custom piston rod thread



+ = plus stroke length

K8 – Extended piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length

## Datasheet

| ∅    | A    | A1       | A2        | AF   | AF5  | KF  | KF5 |
|------|------|----------|-----------|------|------|-----|-----|
| [mm] | -0.5 |          |           | min. | min. |     |     |
| 20   | 16   | 1 ... 20 | 1 ... 300 | 14   | 12   | M6  | M5  |
| 25   |      |          |           |      |      |     |     |
| 32   | 19   |          | 1 ... 400 | 16   | 14   | M8  | M6  |
| 40   |      |          |           |      |      |     |     |
| 50   | 22   | 1 ... 30 | 1 ... 500 | 20   | 16   | M10 | M8  |
| 63   |      |          |           |      |      |     |     |
| 80   | 28   |          |           |      | 20   | M12 | M10 |
| 100  |      |          |           |      |      |     |     |

| ∅    | KK       | KK5                   | T3  | T4  | WH   | ZB    |
|------|----------|-----------------------|-----|-----|------|-------|
| [mm] |          |                       |     |     | +1.3 | +1.2  |
| 20   | M8       | M10x1.25<br>M10       | 2   | 2.6 | 5.5  | 80.8  |
| 25   |          |                       |     |     |      | 83.1  |
| 32   | M10x1.25 | M10<br>M12            | 2.6 | 3.3 | 6    | 91.4  |
| 40   |          |                       |     |     |      | 96.5  |
| 50   | M12x1.25 | M12<br>M16            | 3.3 | 4.7 | 8.2  | 105.6 |
| 63   |          |                       |     |     |      | 118.9 |
| 80   | M16x1.5  | M16<br>M20x1.5<br>M20 | 4.7 | 6.1 | 8.9  | 145.4 |
| 100  |          |                       |     |     |      | 154.1 |

## Compact cylinders ADN-KP, standard hole pattern, with clamping unit

### Ordering data – Modular product system

| Ordering table            |                                                                            |               |                 |                 |            |            | Conditions      | Code | Enter code |
|---------------------------|----------------------------------------------------------------------------|---------------|-----------------|-----------------|------------|------------|-----------------|------|------------|
| Size                      | 20                                                                         | 25            | 32              | 40              |            |            |                 |      |            |
| Module no.                | <b>548206</b>                                                              | <b>548207</b> | <b>548208</b>   | <b>548209</b>   |            |            |                 |      |            |
| Function                  | Compact cylinder, double-acting, standard hole pattern, with clamping unit |               |                 |                 |            |            | <b>ADN</b>      | ADN  |            |
| Piston ø [mm]             | 20                                                                         | 25            | 32              | 40              |            |            | -...            |      |            |
| Stroke [mm]               | 10 ... 300                                                                 |               | 10 ... 400      |                 |            |            | -...            |      |            |
| Clamping unit             | Attached                                                                   |               |                 |                 |            |            | <b>-KP</b>      | -KP  |            |
| Piston rod thread         | Male thread                                                                |               |                 |                 |            |            | <b>-A</b>       |      |            |
|                           | Female thread                                                              |               |                 |                 |            | [1]        | <b>-I</b>       |      |            |
| Cushioning                | Elastic cushioning rings/pads at both ends                                 |               |                 |                 |            |            | <b>-P</b>       | -P   |            |
| Position sensing          | Via proximity switch                                                       |               |                 |                 |            |            | <b>-A</b>       | -A   |            |
| Extended male thread [mm] | Extended male piston rod thread<br>1 ... 20                                |               |                 |                 |            |            | <b>-...K2</b>   |      |            |
| Custom piston rod thread  | Male thread                                                                |               | M10x1.25<br>M10 | M10x1.25<br>M10 | M10<br>M12 | M10<br>M12 | <b>-“...”K5</b> |      |            |
|                           | Female thread                                                              |               | M5              | M5              | M6         | M6         |                 |      |            |
| Extended piston rod [mm]  | Extended piston rod<br>1 ... 300                                           |               | 1 ... 400       |                 |            | [2]        | <b>-...K8</b>   |      |            |
| Captive rating plate      | Laser-etched rating plate                                                  |               |                 |                 |            |            | <b>-TL</b>      |      |            |

[1] **I** Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length



## Ordering data – Modular product system

| Ordering table            |                                                                            |               |               |                       |                       |               |                 | Enter code |
|---------------------------|----------------------------------------------------------------------------|---------------|---------------|-----------------------|-----------------------|---------------|-----------------|------------|
| Size                      | 50                                                                         | 63            | 80            | 100                   | Conditions            | Code          |                 |            |
| Module no.                | <b>548210</b>                                                              | <b>548211</b> | <b>548212</b> | <b>548213</b>         |                       |               |                 |            |
| Function                  | Compact cylinder, double-acting, standard hole pattern, with clamping unit |               |               |                       |                       | <b>ADN</b>    |                 | ADN        |
| Piston ø [mm]             | 50                                                                         | 63            | 80            | 100                   |                       | -...          |                 |            |
| Stroke [mm]               | 10 ... 400                                                                 |               | 10 ... 500    |                       |                       | -...          |                 |            |
| Clamping unit             | Attached                                                                   |               |               |                       |                       | <b>-KP</b>    |                 | -KP        |
| Piston rod thread         | Male thread                                                                |               |               |                       |                       | <b>-A</b>     |                 |            |
|                           | Female thread                                                              |               |               |                       | [1]                   | <b>-I</b>     |                 |            |
| Cushioning                | Elastic cushioning rings/pads at both ends                                 |               |               |                       |                       | <b>-P</b>     |                 | -P         |
| Position sensing          | Via proximity switch                                                       |               |               |                       |                       | <b>-A</b>     |                 | -A         |
| Extended male thread [mm] | Extended male piston rod thread                                            |               |               |                       |                       |               |                 |            |
|                           | 1 ... 20                                                                   |               | 1 ... 30      |                       |                       | <b>-...K2</b> |                 |            |
| Custom piston rod thread  | Male thread                                                                | M12<br>M16    | M12<br>M16    | M16<br>M20<br>M20x1.5 | M16<br>M20<br>M20x1.5 |               | <b>-“...”K5</b> |            |
|                           | Female thread                                                              | M8            | M8            | M10                   | M10                   |               |                 |            |
| Extended piston rod [mm]  | Extended piston rod                                                        |               | 1 ... 500     |                       | [2]                   | <b>-...K8</b> |                 |            |
| Captive rating plate      | Laser-etched rating plate                                                  |               |               |                       |                       | <b>-TL</b>    |                 |            |

[1] **I** Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

## Type codes

|            |                                                     |  |
|------------|-----------------------------------------------------|--|
| <b>001</b> | <b>Series</b>                                       |  |
| <b>ADN</b> | Compact cylinder, double-acting, based on ISO 21287 |  |

|            |                        |  |
|------------|------------------------|--|
| <b>002</b> | <b>Piston diameter</b> |  |
| <b>20</b>  | 20                     |  |
| <b>25</b>  | 25                     |  |
| <b>32</b>  | 32                     |  |
| <b>40</b>  | 40                     |  |
| <b>50</b>  | 50                     |  |
| <b>63</b>  | 63                     |  |
| <b>80</b>  | 80                     |  |
| <b>100</b> | 100                    |  |

|            |               |  |
|------------|---------------|--|
| <b>003</b> | <b>Stroke</b> |  |
| <b>...</b> | 10 ... 500    |  |

|            |                             |  |
|------------|-----------------------------|--|
| <b>004</b> | <b>End-position locking</b> |  |
| <b>ELB</b> | Both sides                  |  |
| <b>ELH</b> | Rear                        |  |
| <b>ELV</b> | Front                       |  |

|            |                               |  |
|------------|-------------------------------|--|
| <b>005</b> | <b>Piston rod thread type</b> |  |
| <b>A</b>   | Male thread                   |  |
| <b>I</b>   | Female thread                 |  |

|            |                                               |  |
|------------|-----------------------------------------------|--|
| <b>006</b> | <b>Cushioning</b>                             |  |
| <b>P</b>   | Elastic cushioning rings/plates on both sides |  |

|            |                         |  |
|------------|-------------------------|--|
| <b>007</b> | <b>Position sensing</b> |  |
| <b>A</b>   | For proximity sensor    |  |

|              |                                    |  |
|--------------|------------------------------------|--|
| <b>008</b>   | <b>Piston rod thread extension</b> |  |
|              | None                               |  |
| <b>...K2</b> | 1 ... 30 mm                        |  |


|                     |                      |  |
|---------------------|----------------------|--|
| <b>009</b>          | <b>Custom thread</b> |  |
| <b>"M6"K5</b>       | M6                   |  |
| <b>"M8"K5</b>       | M8                   |  |
| <b>"M10"K5</b>      | M10                  |  |
| <b>"M10x1,25"K5</b> | M10x1.25             |  |
| <b>"M12"K5</b>      | M12                  |  |
| <b>"M16"K5</b>      | M16                  |  |
| <b>"M20x1,5"K5</b>  | M20x1.5              |  |
| <b>"M5"K5</b>       | M5                   |  |
| <b>"M20"K5</b>      | M20                  |  |

|              |                             |  |
|--------------|-----------------------------|--|
| <b>010</b>   | <b>Piston rod extension</b> |  |
|              | None                        |  |
| <b>...K8</b> | 1 ... 500 mm                |  |


|            |                             |  |
|------------|-----------------------------|--|
| <b>011</b> | <b>Captive rating plate</b> |  |
|            | Rating plate, glued         |  |
| <b>TL</b>  | Laser etched rating plate   |  |

## Datasheet

## Function



-  Diameter  
 20 ... 100 mm

-  Stroke length  
 10 ... 500 mm

## Variants




K2




K5



K8




 **Note**

If used in safety-oriented applications, additional measures are necessary, e.g. in Europe the standards listed in the EC Machinery Directive must be observed.

Without additional measures in accordance with legally specified minimum requirements, the product is not suitable as a safety-related component in control systems.

**General technical data**

| Piston $\varnothing$                              | 20                                         | 25       | 32   | 40       | 50   | 63                | 80   | 100  |
|---------------------------------------------------|--------------------------------------------|----------|------|----------|------|-------------------|------|------|
| Pneumatic connection                              | M5                                         | M5       | G1/8 | G1/8     | G1/8 | G1/8              | G1/8 | G1/8 |
| Female piston rod thread                          |                                            |          |      |          |      |                   |      |      |
| -                                                 | M6                                         | M8       |      | M10      |      | M12               |      |      |
| K5                                                | M5                                         | M6       |      | M8       |      | M10               |      |      |
| Male piston rod thread                            |                                            |          |      |          |      |                   |      |      |
| -                                                 | M8                                         | M10x1.25 |      | M12x1.25 |      | M16x1.5           |      |      |
| K5                                                | M10; M10x1.25                              | M10; M12 |      | M12; M16 |      | M16; M20; M20x1.5 |      |      |
| Max. axial backlash with end position locked [mm] | 1.3                                        |          |      |          |      |                   | 2.1  |      |
| Design                                            | Piston                                     |          |      |          |      |                   |      |      |
|                                                   | Piston rod                                 |          |      |          |      |                   |      |      |
|                                                   | Cylinder barrel                            |          |      |          |      |                   |      |      |
| End-position locking                              |                                            |          |      |          |      |                   |      |      |
| ELB                                               | At both ends                               |          |      |          |      |                   |      |      |
| ELV                                               | Advanced                                   |          |      |          |      |                   |      |      |
| ELH                                               | Rear                                       |          |      |          |      |                   |      |      |
| Cushioning                                        | Elastic cushioning rings/pads at both ends |          |      |          |      |                   |      |      |
| Position sensing                                  | Via proximity switch                       |          |      |          |      |                   |      |      |
| Type of mounting                                  | With female thread                         |          |      |          |      |                   |      |      |
|                                                   | Via accessories                            |          |      |          |      |                   |      |      |
| Mounting position                                 | Any                                        |          |      |          |      |                   |      |      |

 **Note**

- Screws with a head or similar must not be used in place of end-position locking, as there is a risk that the function will be impaired if they are screwed in too deeply.
- The exhaust bore must not be closed.
- The piston rod can be locked in any stroke position once the drive is brought mechanically into its end position.
- End-position locking has been designed to prevent the load from dropping in case of pressure failure.
- Avoid operating the cylinder using a 3-way valve, especially with the function "mid-position closed" and those with "metallic sealing". The residual pressure that is enclosed on the locking side of the cylinder can release the locking function.
- The cylinder must not be operated with external stops (e.g. shock absorber, buffer, oil brake, etc.):
  - It may not be possible to reliably reach the internal end position.
  - The locking mechanism can wear out prematurely. (If the pressure in the opposite chamber drops to less than the locking pressure, the locking piston will prematurely fall to its lower end position.)

## Datasheet

| Operating and environmental conditions       |                                                                                   |             |    |    |            |    |    |     |
|----------------------------------------------|-----------------------------------------------------------------------------------|-------------|----|----|------------|----|----|-----|
| Piston $\varnothing$                         | 20                                                                                | 25          | 32 | 40 | 50         | 63 | 80 | 100 |
| Operating medium                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                         |             |    |    |            |    |    |     |
| Note on the operating/pilot medium           | Lubricated operation possible (in which case lubrication will always be required) |             |    |    |            |    |    |     |
| Operating pressure                           | [MPa]                                                                             | 0.25 ... 1  |    |    | 0.15 ... 1 |    |    |     |
|                                              | [bar]                                                                             | 2.5 ... 10  |    |    | 1.5 ... 10 |    |    |     |
| Ambient temperature <sup>1)</sup>            | [°C]                                                                              | -20 ... +80 |    |    |            |    |    |     |
| Corrosion resistance class CRC <sup>2)</sup> | 2                                                                                 |             |    |    |            |    |    |     |

- 1) Note operating range of proximity switches  
 2) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

| Forces [N]                             |     |     |     |     |      |      |      |      |
|----------------------------------------|-----|-----|-----|-----|------|------|------|------|
| Piston $\varnothing$                   | 20  | 25  | 32  | 40  | 50   | 63   | 80   | 100  |
| Theoretical force at 6 bar, advancing  | 188 | 295 | 483 | 754 | 1178 | 1870 | 3016 | 4712 |
| Theoretical force at 6 bar, retracting | 141 | 247 | 415 | 686 | 1057 | 1750 | 2827 | 4524 |
| Static holding force                   | 250 | 500 |     |     | 2000 |      | 5000 |      |

### Sizing example

**Note**  
 When sizing pneumatic cylinders it is recommended as a basic principle that only 50% of the indicated theoretical forces (see above) be used

**Assuming:**  
 Mounting position = vertical  
 Workpiece load = 44 kg  
 $F = m \times g = 44 \text{ kg} \times 9.81 \text{ m/s}^2 = 431.6 \text{ N}$

**To be determined:**  
 Suitable piston diameter

**Example with 32 mm piston diameter:**  
 Theoretical force at 6 bar, advancing = 483 N  
 50% of the theoretical force = 241.5 N  
 Static holding force with 32 mm piston diameter = 500 N  
 The static holding force of end-position locking is within the permissible range (max. 500 N) for a workpiece load of 44 kg (431.6 N); however, the cylinder would be at 89% capacity.  
**Results:**  
 A cylinder with a piston diameter of 40 mm is therefore recommended for this application.

| Impact energy [J]                       |     |     |     |     |    |     |     |     |
|-----------------------------------------|-----|-----|-----|-----|----|-----|-----|-----|
| Piston $\varnothing$                    | 20  | 25  | 32  | 40  | 50 | 63  | 80  | 100 |
| Max. impact energy in the end positions | 0.2 | 0.3 | 0.4 | 0.7 | 1  | 1.3 | 1.8 | 2.5 |


**Note**  
 These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact speed:  $V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$

Maximum permissible mass:  $m_2 = \frac{2 \times E}{v^2} - m_1$

V Permissible impact velocity  
 E Max. impact energy  
 m1 Moving mass (drive)  
 m2 Moving payload

### Max. lateral force Fq as a function of projection x




## Datasheet

| Weight [g]                               |     |     |     |     |      |      |      |      |
|------------------------------------------|-----|-----|-----|-----|------|------|------|------|
| Piston $\varnothing$                     | 20  | 25  | 32  | 40  | 50   | 63   | 80   | 100  |
| <b>End position locking at both ends</b> |     |     |     |     |      |      |      |      |
| Product weight with 0 mm stroke          | 234 | 339 | 518 | 665 | 1334 | 1734 | 3300 | 4735 |
| Additional weight per 10 mm stroke       | 22  | 26  | 29  | 38  | 51   | 59   | 79   | 98   |
| Moving mass with 0 mm stroke             | 43  | 53  | 85  | 101 | 199  | 248  | 475  | 637  |
| Additional mass per 10 mm stroke         | 6   | 6   | 9   | 9   | 16   | 16   | 25   | 25   |
| <b>End-position locking at front</b>     |     |     |     |     |      |      |      |      |
| Product weight with 0 mm stroke          | 177 | 248 | 387 | 498 | 922  | 1228 | 2296 | 3448 |
| Additional weight per 10 mm stroke       | 22  | 26  | 29  | 38  | 51   | 59   | 79   | 98   |
| Moving mass with 0 mm stroke             | 35  | 46  | 75  | 98  | 175  | 225  | 464  | 626  |
| Additional mass per 10 mm stroke         | 6   | 6   | 9   | 9   | 16   | 16   | 25   | 25   |
| <b>End-position locking at rear</b>      |     |     |     |     |      |      |      |      |
| Product weight with 0 mm stroke          | 181 | 252 | 380 | 505 | 920  | 1217 | 2233 | 3409 |
| Additional weight per 10 mm stroke       | 22  | 26  | 29  | 38  | 51   | 59   | 79   | 98   |
| Moving mass with 0 mm stroke             | 37  | 45  | 73  | 89  | 168  | 217  | 413  | 582  |
| Additional mass per 10 mm stroke         | 6   | 6   | 9   | 9   | 16   | 16   | 25   | 25   |

## Materials

## Sectional view



| Compact cylinder |                   |                                                     |
|------------------|-------------------|-----------------------------------------------------|
| [1]              | Cover             | Anodised aluminium                                  |
| [2]              | Cylinder barrel   | Anodised aluminium                                  |
| [3]              | Piston rod        | High-alloy steel                                    |
| [4]              | Flange screws     | $\varnothing$ 20 ... 63<br>$\varnothing$ 80 ... 100 |
| -                | Seals             | Polyurethane, nitrile rubber                        |
|                  | Note on materials | RoHS-compliant                                      |

Datasheet


Dimensions – Basic version

Download CAD data → [www.festo.com](http://www.festo.com)


ELB – End-position locking at both ends

∅ 20 ... 63


∅ 32 ... 63




∅ 80 ... 100



ELV – End-position locking at front



ELH – End-position locking at rear



## Datasheet

| ∅<br>[mm] | BG<br>min. | D1<br>∅<br>H9 | D2<br>∅               | D5<br>∅          | E                    | EE   | G    | G1   | H1    | J2   | L4   | L5   |
|-----------|------------|---------------|-----------------------|------------------|----------------------|------|------|------|-------|------|------|------|
| 20        | 18         | 9             | 9                     | 9 <sup>F9</sup>  | 35.5 <sup>+0.3</sup> | M5   | 25   | 12   | 45.5  | 2.6  | 18.5 | 12.5 |
| 25        |            |               | 39.5 <sup>+0.3</sup>  |                  | 29.5                 |      | 53.3 |      | 20.8  |      | 14   |      |
| 32        |            |               | 13                    |                  | 47 <sup>+0.3</sup>   | 33   | 15   | 58   | 6     | 22.5 | 15   |      |
| 40        |            |               | 54.5 <sup>+0.3</sup>  |                  | 43                   |      | 77   | 8    |       |      |      |      |
| 50        | 20         | 12            | 20                    | 12 <sup>F9</sup> | 65.5 <sup>+0.3</sup> | G1/8 | 43   | 15   | 82    | 11.5 | 27.5 | 20.5 |
| 63        |            |               | 75.5 <sup>+0.3</sup>  | 55               | 16.5                 |      |      |      | 103.5 |      | 34   | 25   |
| 80        |            |               | 30                    | 15               | 95.5 <sup>+0.6</sup> |      | 57   | 21.5 | 113.5 | 20   | 35   | 27   |
| 100       |            |               | 113.5 <sup>+0.6</sup> |                  |                      |      |      |      |       |      |      |      |



| ∅<br>[mm] | PW<br>+0.2 | MM<br>∅ | PL  | PL1 | RT   | ST<br>h13 | T2<br>+0.1 | TG<br>±0.2 | ZA<br>±0.6 |          | ZB<br>+1.2 |          |
|-----------|------------|---------|-----|-----|------|-----------|------------|------------|------------|----------|------------|----------|
|           |            |         |     |     |      |           |            |            | ELB        | ELV, ELH | ELB        | ELV, ELH |
| 20        | 5          | 10      | 6   | 6   | M5   | 9         | 2.1        | 22         | 63         | 50       | 68.8       | 55.5     |
| 25        |            |         |     |     |      |           |            | 26         | 74         | 56.5     | 79.5       | 62       |
| 32        |            | 12      | 16  | 8.2 | M6   | 10        |            | 32.5       | 80         | 62       | 86         | 68       |
| 40        |            |         |     |     |      |           |            | 38         | 81         | 63       | 87.1       | 69       |
| 50        | 16         | 21      | M8  |     | 13   | 2.6       | 46.5       | 101        | 73         | 109.2    | 81.2       |          |
| 63        |            |         |     |     |      |           | 56.5       | 105        | 77         | 113.1    | 85.1       |          |
| 80        | 20         | 28      | M10 | 17  | 72   |           | 131        | 92.5       | 139.9      | 101.4    |            |          |
| 100       |            |         |     |     | 10.5 |           | 89         | 138        | 102.5      | 147      | 111.5      |          |

Datasheet

Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)


Basic version



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length



K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$



+ = plus stroke length

K5 – Custom piston rod thread



+ = plus stroke length

K8 – Extended piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length



## Datasheet

| ∅    | A    | A1       | A2        | AF   | AF5  | KF  | KF5 |
|------|------|----------|-----------|------|------|-----|-----|
| [mm] | -0.5 |          |           | min. | min. |     |     |
| 20   | 16   | 1 ... 20 | 1 ... 300 | 14   | 12   | M6  | M5  |
| 25   |      |          |           |      |      |     |     |
| 32   | 19   |          | 1 ... 400 | 16   | 14   | M8  | M6  |
| 40   |      |          |           |      |      |     |     |
| 50   | 22   | 1 ... 30 | 1 ... 500 | 20   | 16   | M10 | M8  |
| 63   |      |          |           |      |      |     |     |
| 80   | 28   |          |           |      | 20   | M12 | M10 |
| 100  |      |          |           |      |      |     |     |

| ∅    | KK       | KK5                   | T3  | T4  | WH   | ZB<br>+1.2 |          |
|------|----------|-----------------------|-----|-----|------|------------|----------|
| [mm] |          |                       |     |     | +1.3 | ELB        | ELV, ELH |
| 20   | M8       | M10x1.25<br>M10       | 2   | 2.6 | 5.5  | 68.8       | 55.5     |
| 25   |          |                       |     |     |      | 79.5       | 62       |
| 32   | M10x1.25 | M10<br>M12            | 2.6 | 3.3 | 6    | 86         | 68       |
| 40   |          |                       |     |     |      | 6.1        | 87.1     |
| 50   | M12x1.25 | M12<br>M16            | 3.3 | 4.7 | 8.2  | 109.2      | 81.2     |
| 63   |          |                       |     |     |      | 8.1        | 113.1    |
| 80   | M16x1.5  | M16<br>M20x1.5<br>M20 | 4.7 | 6.1 | 8.9  | 139.9      | 101.4    |
| 100  |          |                       |     |     |      | 9          | 147      |

Ordering data – Modular product system

| Ordering table            |                                                                                   |                 |                 |               |            |               |                 | Enter code |
|---------------------------|-----------------------------------------------------------------------------------|-----------------|-----------------|---------------|------------|---------------|-----------------|------------|
| Size                      | 20                                                                                | 25              | 32              | 40            | Conditions | Code          |                 | Enter code |
| Module no.                | <b>548214</b>                                                                     | <b>548215</b>   | <b>548216</b>   | <b>548217</b> |            |               |                 |            |
| Function                  | Compact cylinder, double-acting, standard hole pattern, with end-position locking |                 |                 |               |            | <b>ADN</b>    |                 | ADN        |
| Piston ø [mm]             | 20                                                                                | 25              | 32              | 40            |            | -...          |                 |            |
| Stroke [mm]               | 10 ... 300                                                                        |                 | 10 ... 400      |               |            | -...          |                 |            |
| End-position locking      | At both ends                                                                      |                 |                 |               |            | <b>-ELB</b>   |                 |            |
|                           | Advanced                                                                          |                 |                 |               |            | <b>-ELV</b>   |                 |            |
|                           | Rear                                                                              |                 |                 |               |            | <b>-ELH</b>   |                 |            |
| Piston rod thread         | Male thread                                                                       |                 |                 |               |            | <b>-A</b>     |                 |            |
|                           | Female thread                                                                     |                 |                 |               | [1]        | <b>-I</b>     |                 |            |
| Cushioning                | Elastic cushioning rings/pads at both ends                                        |                 |                 |               |            | <b>-P</b>     |                 | -P         |
| Position sensing          | Via proximity switch                                                              |                 |                 |               |            | <b>-A</b>     |                 | -A         |
| Extended male thread [mm] | Extended male piston rod thread                                                   |                 |                 |               |            |               |                 |            |
|                           | 1 ... 20                                                                          |                 |                 |               |            | <b>-...K2</b> |                 |            |
| Custom piston rod thread  | Male thread                                                                       | M10x1.25<br>M10 | M10x1.25<br>M10 | M10<br>M12    | M10<br>M12 |               | <b>-“...”K5</b> |            |
|                           | Female thread                                                                     | M5              | M5              | M6            | M6         |               |                 |            |
| Extended piston rod [mm]  | Extended piston rod                                                               |                 |                 |               |            |               |                 |            |
|                           | 1 ... 300                                                                         |                 | 1 ... 400       |               | [2]        | <b>-...K8</b> |                 |            |
| Captive rating plate      | Laser-etched rating plate                                                         |                 |                 |               |            | <b>-TL</b>    |                 |            |

[1] **I** Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

## Ordering data – Modular product system

| Ordering table            |                                                                                   |               |               |               |                       |                       |               | Enter code      |
|---------------------------|-----------------------------------------------------------------------------------|---------------|---------------|---------------|-----------------------|-----------------------|---------------|-----------------|
| Size                      | 50                                                                                | 63            | 80            | 100           | Conditions            | Code                  |               |                 |
| Module no.                | <b>548218</b>                                                                     | <b>548219</b> | <b>548220</b> | <b>548221</b> |                       |                       |               |                 |
| Function                  | Compact cylinder, double-acting, standard hole pattern, with end-position locking |               |               |               |                       | <b>ADN</b>            |               | ADN             |
| Piston Ø [mm]             | 50                                                                                | 63            | 80            | 100           |                       | -...                  |               |                 |
| Stroke [mm]               | 10 ... 400                                                                        |               | 10 ... 500    |               |                       | -...                  |               |                 |
| End-position locking      | At both ends                                                                      |               |               |               |                       | <b>-ELB</b>           |               |                 |
|                           | Advanced                                                                          |               |               |               |                       | <b>-ELV</b>           |               |                 |
|                           | Rear                                                                              |               |               |               |                       | <b>-ELH</b>           |               |                 |
| Piston rod thread         | Male thread                                                                       |               |               |               |                       | <b>-A</b>             |               |                 |
|                           | Female thread                                                                     |               |               |               | [1]                   | <b>-I</b>             |               |                 |
| Cushioning                | Elastic cushioning rings/pads at both ends                                        |               |               |               |                       | <b>-P</b>             |               | -P              |
| Position sensing          | Via proximity switch                                                              |               |               |               |                       | <b>-A</b>             |               | -A              |
| Extended male thread [mm] | Extended male piston rod thread                                                   |               | 1 ... 20      |               | 1 ... 30              |                       | <b>-...K2</b> |                 |
|                           | Custom piston rod thread                                                          | Male thread   | M12<br>M16    | M12<br>M16    | M16<br>M20<br>M20x1.5 | M16<br>M20<br>M20x1.5 |               | <b>-“...”K5</b> |
| Female thread             |                                                                                   | M8            | M8            | M10           | M10                   |                       |               |                 |
| Extended piston rod [mm]  | Extended piston rod                                                               |               |               |               |                       | <b>-...K8</b>         |               |                 |
|                           | 1 ... 400                                                                         |               | 1 ... 500     |               | [2]                   |                       |               |                 |
| Captive rating plate      | Laser-etched rating plate                                                         |               |               |               |                       | <b>-TL</b>            |               |                 |

[1] **I** Not with extended male thread K2

[2] **K8** The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

## Type codes

|            |                                                     |  |
|------------|-----------------------------------------------------|--|
| <b>001</b> | <b>Series</b>                                       |  |
| <b>AEN</b> | Compact cylinder, single-acting, based on ISO 21287 |  |

|            |                             |  |
|------------|-----------------------------|--|
| <b>002</b> | <b>Piston diameter [mm]</b> |  |
| <b>12</b>  | 12                          |  |
| <b>16</b>  | 16                          |  |
| <b>20</b>  | 20                          |  |
| <b>25</b>  | 25                          |  |
| <b>32</b>  | 32                          |  |
| <b>40</b>  | 40                          |  |
| <b>50</b>  | 50                          |  |
| <b>63</b>  | 63                          |  |
| <b>80</b>  | 80                          |  |
| <b>100</b> | 100                         |  |

|            |                    |  |
|------------|--------------------|--|
| <b>003</b> | <b>Stroke [mm]</b> |  |
| <b>...</b> | 1 ... 25           |  |

|            |                               |  |
|------------|-------------------------------|--|
| <b>004</b> | <b>Piston rod thread type</b> |  |
| <b>A</b>   | Male thread                   |  |
| <b>I</b>   | Female thread                 |  |

|            |                                               |  |
|------------|-----------------------------------------------|--|
| <b>005</b> | <b>Cushioning</b>                             |  |
| <b>P</b>   | Elastic cushioning rings/plates on both sides |  |

|            |                         |  |
|------------|-------------------------|--|
| <b>006</b> | <b>Position sensing</b> |  |
| <b>A</b>   | For proximity sensor    |  |

|            |                         |  |
|------------|-------------------------|--|
| <b>007</b> | <b>Active direction</b> |  |
| <b>Z</b>   | Single-acting, pulling  |  |
|            | Single-acting, pushing  |  |

|              |                                    |  |
|--------------|------------------------------------|--|
| <b>008</b>   | <b>Piston rod thread extension</b> |  |
|              | None                               |  |
| <b>...K2</b> | 1 ... 30 mm                        |  |

|                     |                      |  |
|---------------------|----------------------|--|
| <b>009</b>          | <b>Custom thread</b> |  |
| <b>"M5"K5</b>       | M5                   |  |
| <b>"M6"K5</b>       | M6                   |  |
| <b>"M8"K5</b>       | M8                   |  |
| <b>"M10"K5</b>      | M10                  |  |
| <b>"M10x1,25"K5</b> | M10x1.25             |  |
| <b>"M12"K5</b>      | M12                  |  |
| <b>"M16"K5</b>      | M16                  |  |
| <b>"M20"K5</b>      | M20                  |  |
| <b>"M20x1,5"K5</b>  | M20x1.5              |  |

|              |                             |  |
|--------------|-----------------------------|--|
| <b>010</b>   | <b>Piston rod extension</b> |  |
|              | None                        |  |
| <b>...K8</b> | 1 ... 25 mm                 |  |



|            |                                             |  |
|------------|---------------------------------------------|--|
| <b>011</b> | <b>Improved running performance</b>         |  |
|            | None                                        |  |
| <b>K10</b> | Smooth anodised aluminium coated piston rod |  |

|            |                                  |  |
|------------|----------------------------------|--|
| <b>012</b> | <b>Temperature resistance</b>    |  |
|            | Standard                         |  |
| <b>S6</b>  | Heat-resistant seals max. 120 °C |  |

|            |                             |  |
|------------|-----------------------------|--|
| <b>013</b> | <b>Captive rating plate</b> |  |
|            | Rating plate, glued         |  |
| <b>TL</b>  | Laser etched rating plate   |  |

## Datasheet

## Function



## Pulling

⊘ Diameter  
12 ... 100 mm

— Stroke length  
1 ... 25 mm



www.festo.com

## Variants



S6



K2



K5




K8




K10



Q



AEN- ... -A-P-A



AEN- ... -A-P-A-Z

## General technical data

| Piston Ø          | 12                                                         | 16 | 20 | 25 | 32 | 40 | 50 | 63 | 80 | 100 |
|-------------------|------------------------------------------------------------|----|----|----|----|----|----|----|----|-----|
| Design            | Piston<br>Piston rod<br>Cylinder barrel                    |    |    |    |    |    |    |    |    |     |
| Cushioning        | Elastic cushioning rings/pads at both ends                 |    |    |    |    |    |    |    |    |     |
| Position sensing  | Via proximity switch                                       |    |    |    |    |    |    |    |    |     |
| Type of mounting  | With through-hole<br>With female thread<br>Via accessories |    |    |    |    |    |    |    |    |     |
| Mounting position | Any                                                        |    |    |    |    |    |    |    |    |     |

## Technical data – Basic version and variants

| Piston Ø                 | 12 | 16 | 20            | 25            | 32       |
|--------------------------|----|----|---------------|---------------|----------|
| Pneumatic connection     | M5 | M5 | M5            | M5            | G1/8     |
| Female piston rod thread |    |    |               |               |          |
| —                        | M3 | M4 | M6            | M6            | M8       |
| K5                       | —  | —  | M5            | M5            | M6       |
| Male piston rod thread   |    |    |               |               |          |
| —                        | M5 | M6 | M8            | M8            | M10x1.25 |
| K5                       | M6 | M8 | M10; M10x1.25 | M10; M10x1.25 | M10; M12 |
| Q-K5                     | —  | M8 | M10; M10x1.25 | M10; M10x1.25 | M10      |

| Piston Ø                 | 40       | 50       | 63       | 80                | 100               |
|--------------------------|----------|----------|----------|-------------------|-------------------|
| Pneumatic connection     | G1/8     | G1/8     | G1/8     | G1/8              | G1/8              |
| Female piston rod thread |          |          |          |                   |                   |
| —                        | M8       | M10      | M10      | M12               | M12               |
| K5                       | M6       | M8       | M8       | M10               | M10               |
| Male piston rod thread   |          |          |          |                   |                   |
| —                        | M10x1.25 | M12x1.25 | M12x1.25 | M16x1.5           | M16x1.5           |
| K5                       | M10; M12 | M12; M16 | M12; M16 | M16; M20; M20x1.5 | M16; M20; M20x1.5 |
| Q-K5                     | M10      | M12      | M12      | M16               | M16               |

## Datasheet

| Operating and environmental conditions       |                                                                                   |            |             |    |            |            |    |    |    |     |
|----------------------------------------------|-----------------------------------------------------------------------------------|------------|-------------|----|------------|------------|----|----|----|-----|
| Piston ø                                     | 12                                                                                | 16         | 20          | 25 | 32         | 40         | 50 | 63 | 80 | 100 |
| Operating medium                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                         |            |             |    |            |            |    |    |    |     |
| Note on the operating/pilot medium           | Lubricated operation possible (in which case lubrication will always be required) |            |             |    |            |            |    |    |    |     |
| Operating pressure                           |                                                                                   |            |             |    |            |            |    |    |    |     |
| in [MPa]                                     |                                                                                   |            |             |    |            |            |    |    |    |     |
| –                                            | 0.15 ... 1                                                                        |            | 0.1 ... 1   |    |            |            |    |    |    |     |
| Z                                            | 0.17 ... 1                                                                        | 0.22 ... 1 | 0.13 ... 1  |    | 0.07 ... 1 | 0.06 ... 1 |    |    |    |     |
| Q                                            | 0.15 ... 1                                                                        |            | 0.1 ... 1   |    |            |            |    |    |    |     |
| Q-S6                                         | 0.15 ... 0.6                                                                      |            | 0.1 ... 0.6 |    |            |            |    |    |    |     |
| in [bar]                                     |                                                                                   |            |             |    |            |            |    |    |    |     |
| –                                            | 1.5 ... 10                                                                        |            | 1 ... 10    |    |            |            |    |    |    |     |
| Z                                            | 1.7 ... 10                                                                        | 2.2 ... 10 | 1.3 ... 10  |    | 0.7 ... 10 | 0.6 ... 10 |    |    |    |     |
| Q                                            | 1.5 ... 10                                                                        |            | 1 ... 10    |    |            |            |    |    |    |     |
| Q-S6                                         | 1.5 ... 6                                                                         |            | 1 ... 6     |    |            |            |    |    |    |     |
| Ambient temperature <sup>1)</sup> [°C]       |                                                                                   |            |             |    |            |            |    |    |    |     |
| –                                            | –20 ... +80                                                                       |            |             |    |            |            |    |    |    |     |
| S6                                           | 0 ... +120                                                                        |            |             |    |            |            |    |    |    |     |
| Corrosion resistance class CRC <sup>2)</sup> | 2                                                                                 |            |             |    |            |            |    |    |    |     |

1) Note operating range of proximity switches

2) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

| Forces [N] and impact energy [J]        |      |      |      |      |     |      |      |      |      |      |
|-----------------------------------------|------|------|------|------|-----|------|------|------|------|------|
| Piston ø                                | 12   | 16   | 20   | 25   | 32  | 40   | 50   | 63   | 80   | 100  |
| <b>AEN</b>                              |      |      |      |      |     |      |      |      |      |      |
| Theoretical force at 6 bar, advancing   | 56   | 95   | 162  | 259  | 441 | 702  | 1098 | 1783 | 2899 | 4511 |
| <b>AEN-...-Z, pulling</b>               |      |      |      |      |     |      |      |      |      |      |
| Theoretical force at 6 bar, retracting  | 39   | 65   | 115  | 211  | 373 | 634  | 977  | 1663 | 2610 | 4323 |
| Max. impact energy at the end positions | 0.04 | 0.04 | 0.04 | 0.08 | 0.1 | 0.15 | 0.18 | 0.28 | 0.35 | 0.7  |



### Note

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact speed:

$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

Maximum permissible mass:


$$m_2 = \frac{2 \times E}{v^2} - m_1$$

V Permissible impact velocity  
 E Max. impact energy  
 m1 Moving mass (drive)  
 m2 Moving payload


## Datasheet

### Spring return force F as a function of stroke l

∅ 12 ... 20



∅ 25 ... 100



### Note


The degree of friction depends on the mounting position and the type of load involved. Single-acting cylinders should as far as possible be operated without transverse loads.

### Weight [g]

| Piston ∅                           | 12 | 16 | 20  | 25  | 32  | 40  | 50  | 63  | 80   | 100  |
|------------------------------------|----|----|-----|-----|-----|-----|-----|-----|------|------|
| Product weight with 0 mm stroke    | 77 | 79 | 131 | 156 | 265 | 346 | 540 | 722 | 1300 | 2154 |
| Additional weight per 10 mm stroke | 12 | 14 | 21  | 23  | 30  | 37  | 51  | 59  | 79   | 98   |
| Moving mass with 0 mm stroke       | 9  | 15 | 30  | 50  | 60  | 80  | 140 | 180 | 400  | 570  |
| Additional mass per 10 mm stroke   | 2  | 4  | 6   | 6   | 9   | 9   | 16  | 16  | 25   | 25   |

### Materials

#### Sectional view



| Compact cylinder    | Basic version                              | S6                                                                        |
|---------------------|--------------------------------------------|---------------------------------------------------------------------------|
| [1] Cover           | ∅ 12 ... 80<br>∅ 100                       | Anodised aluminium<br>Coated die-cast aluminium                           |
| [2] Cylinder barrel |                                            | Anodised aluminium                                                        |
| [3] Piston rod      |                                            | High-alloy steel                                                          |
| [4] Flange screws   | ∅ 12 ... 16<br>∅ 20 ... 63<br>∅ 80 ... 100 | High-alloy steel<br>Galvanised steel<br>Standard screws, galvanised steel |
| – Seals             |                                            | Polyurethane<br>Fluoro rubber                                             |
| Note on materials   |                                            | RoHS-compliant                                                            |



Datasheet

Dimensions – Basic version


Download CAD data → [www.festo.com](http://www.festo.com)

∅ 12 ... 63


∅ 32 ... 63



∅ 12 ... 25





∅ 12



+ = plus stroke length

∅ 80 ... 100



+ = plus stroke length



## Datasheet

| ∅<br>[mm] | BG<br>min. | D1<br>∅<br>H9         | D5<br>∅              | E                    | EE   | G    | J2   | J3  | PW<br>+0.2 |
|-----------|------------|-----------------------|----------------------|----------------------|------|------|------|-----|------------|
| 12        | 17         | 9                     | 6 <sup>F9</sup>      | 27.5 <sup>+0.3</sup> | M5   | 10.5 | 2    | –   | 3.5        |
| 16        |            |                       |                      | 29 <sup>+0.3</sup>   |      | 11   | 2.6  |     |            |
| 20        | 19.5       |                       | 9 <sup>F9</sup>      | 35.5 <sup>+0.3</sup> |      | 12   |      |     |            |
| 25        |            |                       |                      | 39.5 <sup>+0.3</sup> | 15   | 6    | 5    |     |            |
| 32        | 26         |                       | 47 <sup>+0.3</sup>   | 8                    |      |      |      |     |            |
| 40        |            |                       | 54.5 <sup>+0.3</sup> | 11.5                 |      |      |      |     |            |
| 50        | 27         | 12                    | 12 <sup>F9</sup>     | 65.5 <sup>+0.3</sup> | G1/8 | 15   | 11.5 | 2.6 |            |
| 63        |            |                       | 75.5 <sup>+0.3</sup> |                      |      |      |      |     |            |
| 80        | 17         |                       | 15                   | 95.5 <sup>+0.6</sup> |      |      |      |     | 16.5       |
| 100       | 21.5       | 113.5 <sup>+0.6</sup> |                      | 21.5                 | 20   |      |      |     |            |



| ∅<br>[mm] | MM<br>∅ | PL<br>+0.2 | RT  | ST<br>h13 | T2<br>+0.1 | TG<br>±0.2 | ZA<br>±0.3 | ZB<br>+1.2 |
|-----------|---------|------------|-----|-----------|------------|------------|------------|------------|
| 12        | 6       | 6          | M4  | 5         | 2.1        | 16         | 35         | 39.2       |
| 16        | 8       |            |     | 7         |            | 18         |            | 39.7       |
| 20        | 10      |            | M5  | 9         |            | 22         | 42.5       |            |
| 25        |         |            |     | 26        |            | 39         | 44.5       |            |
| 32        | 12      | 8.2        | M6  | 10        |            | 32.5       | 44         | 50         |
| 40        |         |            |     | 38        | 45         | 51.1       |            |            |
| 50        | 16      |            | M8  | 13        | 46.5       | 49         | 53.2       |            |
| 63        |         | 56.5       |     | 57.1      |            |            |            |            |
| 80        | 20      | 10.5       | M10 | 17        | 72         | 54         | 62.9       |            |
| 100       |         |            |     | 89        | 67         | 76         |            |            |

## Datasheet

### Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)



Basic version



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length

### Z – Pulling




[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length

++ = plus 2x stroke length



### K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$



+ = plus stroke length

### K5 – Custom piston rod thread



+ = plus stroke length

### K8 – Extended piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing 32 \dots 100$

+ = plus stroke length

## Datasheet

| ∅    | A    | A1       | A2        | AF   | AF5  | KF  | KF5 |
|------|------|----------|-----------|------|------|-----|-----|
| [mm] | -0.5 |          |           | min. | min. |     |     |
| 12   | 10   | 1 ... 10 | 1 ... 300 | 8    | -    | M3  | -   |
| 16   | 12   |          |           | 10   |      | M4  |     |
| 20   | 16   | 1 ... 20 |           | 14   | 12   | M6  | M5  |
| 25   |      |          | 16        | 14   | M8   | M6  |     |
| 32   | 19   |          | 16        | 20   | 16   | M10 | M8  |
| 40   | 22   |          |           | 20   | 20   | M12 | M10 |
| 50   | 28   | 1 ... 30 | 1 ... 500 | 20   | 20   | M12 | M10 |
| 63   |      |          |           |      |      |     |     |
| 80   |      |          |           |      |      |     |     |
| 100  |      |          |           |      |      |     |     |



| ∅    | KK       | KK5                   | T3  | T4  | WH   | ZB   |
|------|----------|-----------------------|-----|-----|------|------|
| [mm] |          |                       |     |     | +1.3 | +1.2 |
| 12   | M5       | M6                    | -   | 1.5 | 4.2  | 39.2 |
| 16   | M6       | M8                    |     |     | 4.7  | 39.7 |
| 20   | M8       | M10x1.25<br>M10       | 2   | 2.6 | 5.5  | 42.5 |
| 25   |          |                       |     |     | 44.5 |      |
| 32   | M10x1.25 | M10<br>M12            | 2.6 | 3.3 | 6    | 50   |
| 40   |          |                       |     |     | 6.1  | 51.1 |
| 50   | M12x1.25 | M12<br>M16            | 3.3 | 4.7 | 8.2  | 53.2 |
| 63   |          |                       |     |     | 8.1  | 57.1 |
| 80   | M16x1.5  | M16<br>M20x1.5<br>M20 | 4.7 | 6.1 | 8.9  | 62.9 |
| 100  |          |                       |     |     | 9    | 76   |

# Datasheet

## Dimensions – Variants

Download CAD data → [www.festo.com](http://www.festo.com)



Q – Square piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 100


+ = plus stroke length  
++ = plus 2x stroke length

Q – Z – Pulling



+ = plus stroke length


Q-K2 – Square piston rod with extended male thread



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 100



+ = plus stroke length

Q-K5 – Square piston rod with custom thread



+ = plus stroke length

Q-K8 – Square, extended piston rod



[1] Hex nut DIN 439-B  
only with  $\varnothing$  32 ... 100

+ = plus stroke length

## Datasheet

| ∅<br>[mm] | A<br>-0.5 | A1       | A2        | AF3<br>min. | B1<br>□ | KF3 |
|-----------|-----------|----------|-----------|-------------|---------|-----|
| 16        | 12        | 1 ... 10 | 1 ... 300 | 10          | 7       | M4  |
| 20<br>25  | 16        | 1 ... 20 |           | 12          | 9       | M5  |
| 32<br>40  | 19        |          | 14        | 10          | M6      |     |
| 50<br>63  | 22        |          | 16        | 12          | M8      |     |
| 80<br>100 | 28        |          | 1 ... 30  | 1 ... 500   | 20      | 16  |

| ∅<br>[mm] | KK       | KK5             | T2  | WH<br>+1.3 | ZB<br>+1.2 |
|-----------|----------|-----------------|-----|------------|------------|
| 16        | M6       | M8              | 1.5 | 4.7        | 39.7       |
| 20<br>25  | M8       | M10x1.25<br>M10 | 2   | 5.5        | 42.5       |
| 32        |          |                 |     |            | 44.5       |
| 40        | M10x1.25 | M10             | 2.6 | 6          | 50         |
| 50        | M12x1.25 | M12             | 3.3 | 6.1        | 51.1       |
| 63        |          |                 |     | 8.2        | 53.2       |
| 80        |          |                 |     | 8.1        | 57.1       |
| 100       | M16x1.5  | M16             | 4.7 | 8.9        | 62.9       |
|           |          |                 |     | 9          | 76         |

Ordering data – Modular product system, basic version and variants

| Ordering table               |                                            |               |                                      |                 |                 |            |               | Conditions      | Code | Enter code |
|------------------------------|--------------------------------------------|---------------|--------------------------------------|-----------------|-----------------|------------|---------------|-----------------|------|------------|
| Size                         | 12                                         | 16            | 20                                   | 25              | 32              |            |               |                 |      |            |
| Module no.                   | <b>536414</b>                              | <b>536415</b> | <b>536416</b>                        | <b>536417</b>   | <b>536418</b>   |            |               |                 |      |            |
| Function                     | Compact cylinder, single-acting            |               |                                      |                 |                 |            |               | <b>AEN</b>      | AEN  |            |
| Standard                     | Based on ISO 21287                         |               | Conforms to ISO 21287                |                 |                 |            |               |                 |      |            |
| Piston ø [mm]                | 12                                         | 16            | 20                                   | 25              | 32              |            | -...          |                 |      |            |
| Stroke [mm]                  | 1 ... 10                                   |               | 1 ... 25                             |                 |                 |            |               |                 |      |            |
| Thread type                  | Male thread                                |               |                                      |                 |                 |            |               | <b>-A</b>       |      |            |
|                              | Female thread                              |               |                                      |                 |                 |            | [1]           | <b>-I</b>       |      |            |
| Cushioning                   | Elastic cushioning rings/pads at both ends |               |                                      |                 |                 |            |               | <b>-P</b>       | -P   |            |
| Position sensing             | Via proximity switch                       |               |                                      |                 |                 |            |               | <b>-A</b>       | -A   |            |
| Effective direction          | Single-acting, pulling                     |               |                                      |                 |                 |            |               | <b>-Z</b>       |      |            |
| Extended male thread [mm]    | Extended male piston rod thread            |               |                                      |                 |                 |            |               |                 |      |            |
|                              | 1 ... 10                                   |               | 1 ... 20                             |                 |                 | [2]        | <b>-...K2</b> |                 |      |            |
| Custom piston rod thread     | Male thread                                | M6            | M8                                   | M10x1.25<br>M10 | M10x1.25<br>M10 | M10<br>M12 | [2]           | <b>-“...”K5</b> |      |            |
|                              | Female thread                              | -             | -                                    | M5              | M5              | M6         |               |                 |      |            |
| Extended piston rod [mm]     | Extended piston rod                        |               |                                      |                 |                 |            |               |                 |      |            |
|                              | 1 ... 10                                   |               | 1 ... 25                             |                 |                 |            | <b>-...K8</b> |                 |      |            |
| Improved running performance | -                                          |               | Smooth anodised aluminium piston rod |                 |                 |            | <b>-K10</b>   |                 |      |            |
| Temperature resistance       | Heat-resistant seals max. 120°C            |               |                                      |                 |                 |            |               | <b>-S6</b>      |      |            |
| Captive rating plate         | Laser-etched rating plate                  |               |                                      |                 |                 |            |               | <b>-TL</b>      |      |            |

[1] I Not with extended male thread K2

[2] K2, K5 Not with improved running performance K10

## Ordering data – Modular product system, basic version and variants

| Ordering table               |                                            |               |               |               |               |            |               |               |                 |  |
|------------------------------|--------------------------------------------|---------------|---------------|---------------|---------------|------------|---------------|---------------|-----------------|--|
| Size                         | 40                                         | 50            | 63            | 80            | 100           | Conditions | Code          | Enter code    |                 |  |
| Module no.                   | <b>536419</b>                              | <b>536420</b> | <b>536421</b> | <b>536422</b> | <b>536423</b> |            |               |               |                 |  |
| Function                     | Compact cylinder, single-acting            |               |               |               |               |            | <b>AEN</b>    | AEN           |                 |  |
| Standard                     | Conforms to ISO 21287                      |               |               |               |               |            |               |               |                 |  |
| Piston Ø [mm]                | 40                                         | 50            | 63            | 80            | 100           |            | -...          |               |                 |  |
| Stroke [mm]                  | 1 ... 25                                   |               |               |               |               |            | -...          |               |                 |  |
| Thread type                  | Male thread                                |               |               |               |               |            | <b>-A</b>     |               |                 |  |
|                              | Female thread                              |               |               |               |               | [1]        | <b>-I</b>     |               |                 |  |
| Cushioning                   | Elastic cushioning rings/pads at both ends |               |               |               |               |            | <b>-P</b>     | -P            |                 |  |
| Position sensing             | Via proximity switch                       |               |               |               |               |            | <b>-A</b>     | -A            |                 |  |
| Effective direction          | Single-acting, pulling                     |               |               |               |               |            | <b>-Z</b>     |               |                 |  |
| Extended male thread [mm]    | Extended male piston rod thread            |               |               |               |               |            |               |               |                 |  |
|                              | 1 ... 20                                   |               |               | 1 ... 30      |               | [2]        | <b>-...K2</b> |               |                 |  |
| Custom piston rod thread     | Male thread                                |               | M10           | M12           | M12           | M16        | M16           | [2]           | <b>-“...”K5</b> |  |
|                              |                                            |               | M12           | M16           | M16           | M20        | M20           |               |                 |  |
| Female thread                |                                            | M6            | M8            | M8            | M10           | M10        |               |               |                 |  |
| Extended piston rod [mm]     | Extended piston rod                        |               |               |               |               |            |               |               |                 |  |
|                              |                                            | 1 ... 25      |               |               |               |            |               | <b>-...K8</b> |                 |  |
| Improved running performance | Smooth anodised aluminium piston rod       |               |               |               |               |            | <b>-K10</b>   |               |                 |  |
| Temperature resistance       | Heat-resistant seals max. 120°C            |               |               |               |               |            | <b>-S6</b>    |               |                 |  |
| Captive rating plate         | Laser-etched rating plate                  |               |               |               |               |            | <b>-TL</b>    |               |                 |  |

[1] I Not with extended male thread K2

[2] K2, K5 Not with improved running performance K10

## Ordering data – Modular product system, Q – Square piston rod, non-rotating

| Ordering table                       |                                            |                       |               |               |            |                 |            |
|--------------------------------------|--------------------------------------------|-----------------------|---------------|---------------|------------|-----------------|------------|
| Size                                 | 16                                         | 20                    | 25            | 32            | Conditions | Code            | Enter code |
| Module no.                           | <b>536415</b>                              | <b>536416</b>         | <b>536417</b> | <b>536418</b> |            |                 |            |
| Function                             | Compact cylinder, single-acting            |                       |               |               |            | <b>AEN</b>      | AEN        |
| Standard                             | Based on ISO 21287                         | Conforms to ISO 21287 |               |               |            |                 |            |
| Piston ø [mm]                        | 16                                         | 20                    | 25            | 32            |            | -...            |            |
| Stroke [mm]                          | 1 ... 25                                   |                       |               |               |            | -...            |            |
| Thread type                          | Male thread                                |                       |               |               |            | <b>-A</b>       |            |
|                                      | Female thread                              |                       |               |               | [1]        | <b>-I</b>       |            |
| Cushioning                           | Elastic cushioning rings/pads at both ends |                       |               |               |            | <b>-P</b>       | -P         |
| Position sensing                     | Via proximity switch                       |                       |               |               |            | <b>-A</b>       | -A         |
| Effective direction                  | Single-acting, pulling                     |                       |               |               |            | <b>-Z</b>       |            |
| Protection against rotation          | Square piston rod                          |                       |               |               |            | <b>-Q</b>       | -Q         |
| Extended male thread [mm]            | Extended male piston rod thread            |                       |               |               |            |                 |            |
|                                      | 1 ... 10                                   | 1 ... 20              |               |               |            | <b>-...K2</b>   |            |
| Custom piston rod thread Male thread | M8                                         | M10x1.25              | M10x1.25      | M10           |            | <b>-“...”K5</b> |            |
|                                      |                                            | M10                   | M10           |               |            |                 |            |
| Extended piston rod [mm]             | Extended piston rod                        |                       |               |               |            |                 |            |
|                                      | 1 ... 25                                   |                       |               |               |            | <b>-...K8</b>   |            |
| Temperature resistance               | Heat-resistant seals max. 120°C            |                       |               |               |            | <b>-S6</b>      |            |
| Captive rating plate                 | Laser-etched rating plate                  |                       |               |               |            | <b>-TL</b>      |            |

[1] I Not with extended male thread K2



## Ordering data – Modular product system, Q – Square piston rod, non-rotating

| Ordering table                       |                                            |               |               |               |               |            |                 |            |
|--------------------------------------|--------------------------------------------|---------------|---------------|---------------|---------------|------------|-----------------|------------|
| Size                                 | 40                                         | 50            | 63            | 80            | 100           | Conditions | Code            | Enter code |
| Module no.                           | <b>536419</b>                              | <b>536420</b> | <b>536421</b> | <b>536422</b> | <b>536423</b> |            |                 |            |
| Function                             | Compact cylinder, single-acting            |               |               |               |               |            | <b>AEN</b>      | AEN        |
| Standard                             | Conforms to ISO 21287                      |               |               |               |               |            |                 |            |
| Piston ø [mm]                        | 40                                         | 50            | 63            | 80            | 100           |            | -...            |            |
| Stroke [mm]                          | 1 ... 25                                   |               |               |               |               |            | -...            |            |
| Thread type                          | Male thread                                |               |               |               |               |            | <b>-A</b>       |            |
|                                      | Female thread                              |               |               |               |               | [1]        | <b>-I</b>       |            |
| Cushioning                           | Elastic cushioning rings/pads at both ends |               |               |               |               |            | <b>-P</b>       | -P         |
| Position sensing                     | Via proximity switch                       |               |               |               |               |            | <b>-A</b>       | -A         |
| Effective direction                  | Single-acting, pulling                     |               |               |               |               |            | <b>-Z</b>       |            |
| Protection against rotation          | Square piston rod                          |               |               |               |               |            | <b>-Q</b>       | -Q         |
| Extended male thread [mm]            | Extended male piston rod thread            |               |               |               |               |            |                 |            |
|                                      | 1 ... 20                                   |               |               | 1 ... 30      |               |            | <b>-...K2</b>   |            |
| Custom piston rod thread Male thread | M10                                        | M12           | M12           | M16           | M16           |            | <b>-“...”K5</b> |            |
| Extended piston rod [mm]             | Extended piston rod<br>1 ... 25            |               |               |               |               |            | <b>-...K8</b>   |            |
| Temperature resistance               | Heat-resistant seals max. 120°C            |               |               |               |               |            | <b>-S6</b>      |            |
| Captive rating plate                 | Laser-etched rating plate                  |               |               |               |               |            | <b>-TL</b>      |            |


[1] I Not with extended male thread K2

## Accessories

### Foot mounting HNA/HNA-...-R3

Material:

HNA: galvanised steel  
 HNA-...-R3: steel,  
 with protective coating  
 Free of copper and PTFE  
 RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | AB<br>$\varnothing$<br>H14 | AH<br>JS14 | AO   | AT<br>$\pm 0.5$ | AU<br>$\pm 0.2$ | SA  | TR<br>$\pm 0.2$ | US<br>$-0.5$ | XA   |
|---------------------------|----------------------------|------------|------|-----------------|-----------------|-----|-----------------|--------------|------|
| 12                        | 5.8                        | 21         | 5    | 3               | 13              | 61  | 16              | 26           | 52.2 |
| 16                        |                            | 22         | 4.75 |                 |                 |     |                 | 27.5         |      |
| 20                        | 7                          | 27         | 6.25 | 4               | 16              | 69  | 22              | 34.5         | 58.7 |
| 25                        |                            | 29         |      |                 |                 |     |                 | 38.5         |      |
| 32                        |                            | 33.5       |      |                 |                 |     |                 | 7            |      |
| 40                        | 10                         | 38         | 9    | 5               | 18              | 81  | 36              | 54           | 69.2 |
| 50                        |                            | 45         | 8    |                 |                 |     |                 | 64           |      |
| 63                        |                            | 50         |      |                 |                 |     |                 | 75           |      |
| 80                        | 12                         | 63         | 10.5 | 6               | 26              | 106 | 63              | 93           | 89   |
| 100                       | 14.5                       | 74         | 12.5 |                 |                 |     |                 | 27           |      |


| For $\varnothing$<br>[mm] | Basic version     |               |          |         | R3 – High corrosion protection |               |          |            |
|---------------------------|-------------------|---------------|----------|---------|--------------------------------|---------------|----------|------------|
|                           | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type    | CRC <sup>1)</sup>              | Weight<br>[g] | Part no. | Type       |
| 12                        | 1                 | 39            | 537237   | HNA-12  | 3                              | 39            | 537252   | HNA-12-R3  |
| 16                        | 1                 | 42            | 537238   | HNA-16  | 3                              | 42            | 537253   | HNA-16-R3  |
| 20                        | 1                 | 84            | 537239   | HNA-20  | 3                              | 84            | 537254   | HNA-20-R3  |
| 25                        | 1                 | 90            | 537240   | HNA-25  | 3                              | 90            | 537255   | HNA-25-R3  |
| 32                        | 1                 | 123           | 537241   | HNA-32  | 3                              | 123           | 537256   | HNA-32-R3  |
| 40                        | 1                 | 157           | 537242   | HNA-40  | 3                              | 157           | 537257   | HNA-40-R3  |
| 50                        | 1                 | 278           | 537243   | HNA-50  | 3                              | 278           | 537258   | HNA-50-R3  |
| 63                        | 1                 | 328           | 537244   | HNA-63  | 3                              | 328           | 537259   | HNA-63-R3  |
| 80                        | 1                 | 634           | 537249   | HNA-80  | 3                              | 634           | 537260   | HNA-80-R3  |
| 100                       | 1                 | 814           | 537250   | HNA-100 | 3                              | 814           | 537261   | HNA-100-R3 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Flange mounting FNC

Material:  
Galvanised steel  
Free of copper and PTFE  
RoHS-compliant



#### Dimensions and ordering data


| For $\varnothing$<br>[mm] | E   | FB<br>$\varnothing$ | MF | R  | TF  | UF<br>$\pm 1$ | ZF   | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type    |
|---------------------------|-----|---------------------|----|----|-----|---------------|------|-------------------|---------------|----------|---------|
| 12                        | 28  | 5.5                 | 8  | -  | 40  | 50            | 47.2 | 1                 | 79            | 537245   | FNC-12  |
| 16                        | 29  |                     |    |    | 43  | 55            | 47.9 | 1                 | 88            | 537246   | FNC-16  |
| 20                        | 36  | 6.6                 |    |    | 55  | 70            | 50.7 | 1                 | 141           | 537247   | FNC-20  |
| 25                        | 40  |                     |    |    | 60  | 76            | 52.7 | 1                 | 165           | 537248   | FNC-25  |
| 32                        | 45  | 7                   | 10 | 32 | 64  | 80            | 60.2 | 1                 | 221           | ★ 174376 | FNC-32  |
| 40                        | 54  | 9                   |    | 36 | 72  | 90            | 61.2 | 1                 | 291           | ★ 174377 | FNC-40  |
| 50                        | 65  | 9                   | 12 | 45 | 90  | 110           | 65.2 | 1                 | 536           | ★ 174378 | FNC-50  |
| 63                        | 75  |                     |    | 50 | 100 | 120           | 69.2 | 1                 | 679           | ★ 174379 | FNC-63  |
| 80                        | 93  | 12                  | 16 | 63 | 126 | 150           | 79   | 1                 | 1495          | ★ 174380 | FNC-80  |
| 100                       | 110 | 14                  |    | 75 | 150 | 175           | 92   | 1                 | 2041          | 174381   | FNC-100 |
| 125                       | 132 | 16                  |    | 20 | 90  | 180           | 210  | 112               | 1             | 3775     | 174382  |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Swivel flange SNCL/SNCL-...-R3

Material:  
 SNCL 12 ... 25:  
 Wrought aluminium alloy  
 SNCL 32 ... 125:  
 Die-cast aluminium  
 SNCL-...-R3: Wrought aluminium alloy  
 with protective coating  
 Free of copper and PTFE  
 RoHS-compliant



| Dimensions and ordering data |                            |                          |                         |                 |    |    |      |      |
|------------------------------|----------------------------|--------------------------|-------------------------|-----------------|----|----|------|------|
| For $\varnothing$<br>[mm]    | CD<br>$\varnothing$<br>H10 | E                        | EW                      | FL<br>$\pm 0.2$ | L  | MR | TG   | XC   |
| 12                           | 6                          | 25 <sub>-0.6</sub>       | 12 <sub>h12</sub>       | 16              | 10 | 6  | 16   | 55.2 |
| 16                           |                            | 27.5 <sub>-0.6</sub>     |                         |                 |    |    | 18   |      |
| 20                           | 8                          | 34.5 <sub>-0.6</sub>     | 16 <sub>h12</sub>       | 20              | 14 | 8  | 22   | 62.7 |
| 25                           |                            | 38.5 <sub>-0.6</sub>     |                         |                 |    |    | 26   |      |
| 32                           | 10                         | 45 <sub>+0.2/-0.5</sub>  | 26 <sub>-0.2/-0.6</sub> | 22              | 13 | 10 | 32.5 | 72.2 |
| 40                           | 12                         | 54 <sub>-0.5</sub>       | 28 <sub>-0.2/-0.6</sub> | 25              | 16 | 12 | 38   | 75.2 |
| 50                           |                            | 64 <sub>-0.6</sub>       | 32 <sub>-0.2/-0.6</sub> | 27              |    |    | 46.5 |      |
| 63                           | 16                         | 75 <sub>-0.6</sub>       | 40 <sub>-0.2/-0.6</sub> | 32              | 21 | 16 | 56.5 | 89.2 |
| 80                           |                            | 93 <sub>-0.8</sub>       | 50 <sub>-0.2/-0.6</sub> | 36              |    |    | 72   |      |
| 100                          | 20                         | 110 <sub>+0.3/-0.8</sub> | 60 <sub>-0.2/-0.6</sub> | 41              | 27 | 20 | 89   | 117  |
| 125                          | 25                         | 131 <sub>-0.8</sub>      | 70 <sub>-0.2/-0.6</sub> | 50              | 30 | 25 | 110  | 142  |

| For $\varnothing$<br>[mm] | Basic version     |               |          |          | R3 – High corrosion protection |               |          |            |
|---------------------------|-------------------|---------------|----------|----------|--------------------------------|---------------|----------|------------|
|                           | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type     | CRC <sup>1)</sup>              | Weight<br>[g] | Part no. | Type       |
| 12                        | 2                 | 20            | 537790   | SNCL-12  | 3                              | 20            | 537794   | SNCL-12-R3 |
| 16                        | 2                 | 21            | 537791   | SNCL-16  | 3                              | 21            | 537795   | SNCL-16-R3 |
| 20                        | 2                 | 38            | 537792   | SNCL-20  | 3                              | 38            | 537796   | SNCL-20-R3 |
| 25                        | 2                 | 41            | 537793   | SNCL-25  | 3                              | 41            | 537797   | SNCL-25-R3 |
| 32                        | 1                 | 71            | ★ 174404 | SNCL-32  | –                              | –             | –        | –          |
| 40                        | 1                 | 95            | ★ 174405 | SNCL-40  | –                              | –             | –        | –          |
| 50                        | 1                 | 158           | ★ 174406 | SNCL-50  | –                              | –             | –        | –          |
| 63                        | 1                 | 225           | ★ 174407 | SNCL-63  | –                              | –             | –        | –          |
| 80                        | 1                 | 436           | ★ 174408 | SNCL-80  | –                              | –             | –        | –          |
| 100                       | 1                 | 606           | 174409   | SNCL-100 | –                              | –             | –        | –          |
| 125                       | 1                 | 1135          | 174410   | SNCL-125 | –                              | –             | –        | –          |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Swivel flange

#### SNCS/CRSNCS/SNCS-...-R3

Material:

SNCS 32 ... 50: Die-cast aluminium  
 SNCS 63 ... 125: Wrought aluminium alloy



CRSNCS 32 ... 80:

High-alloy stainless steel

SNCS-...-R3 100 ... 125:

Wrought aluminium alloy with protective coating

RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | CN<br>$\varnothing$  |                | E                  |                    | EP<br>$\pm 0.2$ | EX | FL<br>$\pm 0.2$ |
|---------------------------|----------------------|----------------|--------------------|--------------------|-----------------|----|-----------------|
|                           | ADN-...              | ADN-...-R3     | ADN-...            | ADN-...-R3         |                 |    |                 |
| 32                        | 10 <sup>+0.013</sup> | 10+0.015/-0.04 | 45+0.2/-0.5        | 45 <sub>-0.5</sub> | 10.5            | 14 | 22              |
| 40                        | 12 <sup>+0.015</sup> | 12+0.018/-0.04 | 54 <sub>-0.5</sub> | 54 <sub>-0.5</sub> | 12              | 16 | 25              |
| 50                        | 16 <sup>+0.015</sup> | 16+0.018/-0.04 | 64 <sub>-0.6</sub> | 64 <sub>-0.6</sub> | 15              | 21 | 27              |
| 63                        | 16 <sup>+0.015</sup> | 16+0.018/-0.04 | 74.5 $\pm 0.5$     | 75 <sub>-0.6</sub> | 15              | 21 | 32              |
| 80                        | 20 <sup>+0.018</sup> | 20+0.021/-0.04 | 92.2 $\pm 0.8$     | 93 <sub>-0.8</sub> | 18              | 25 | 36              |
| 100                       | 20 <sup>+0.018</sup> | 20+0.021/-0.04 | 109+1/-0.7         | 109+1/-0.7         | 18              | 25 | 41              |
| 125                       | 30 <sup>+0.018</sup> | 30+0.021/-0.04 | 132+1/-0.7         | 132+1/-0.7         | 25              | 37 | 50              |

| For $\varnothing$<br>[mm] | LT | MS                 |                    | RA            |                  | TG   | XC   |
|---------------------------|----|--------------------|--------------------|---------------|------------------|------|------|
|                           |    | ADN-...            | ADN-...-R3         | ADN-...<br>+1 | ADN-...-R3<br>+1 |      |      |
| 32                        | 13 | 15 <sup>+0.5</sup> | 15 <sup>+0.5</sup> | 14.5          | 14.5             | 32.5 | 72.2 |
| 40                        | 16 | 17 <sup>+0.5</sup> | 17 <sup>+0.5</sup> | 17.5          | 17.5             | 38   | 75.2 |
| 50                        | 16 | 20 <sup>+0.5</sup> | 20 <sup>+0.5</sup> | 18.5          | 19               | 46.5 | 80.2 |
| 63                        | 21 | 23 <sub>-0.5</sub> | 22 <sup>+0.5</sup> | 23            | 23               | 56.5 | 89.2 |
| 80                        | 22 | 28 <sub>-0.5</sub> | 27 <sup>+0.5</sup> | 25            | 25               | 72   | 99   |
| 100                       | 27 | 30 $\pm 0.5$       | 30 $\pm 0.5$       | 95            | 100              | 89   | 117  |
| 125                       | 30 | 39 $\pm 0.5$       | 39 $\pm 0.5$       | 100           | 100              | 110  | 142  |

| For $\varnothing$<br>[mm] | Basic version     |               |          |          | High corrosion protection |               |          |             |
|---------------------------|-------------------|---------------|----------|----------|---------------------------|---------------|----------|-------------|
|                           | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type     | CRC <sup>1)</sup>         | Weight<br>[g] | Part no. | Type        |
| 32                        | 1                 | 86            | ★ 174397 | SNCS-32  | 4                         | 161           | 2895920  | CRSNCS-32   |
| 40                        | 1                 | 122           | ★ 174398 | SNCS-40  | 4                         | 239           | 2895921  | CRSNCS-40   |
| 50                        | 1                 | 216           | ★ 174399 | SNCS-50  | 4                         | 403           | 2895922  | CRSNCS-50   |
| 63                        | 2                 | 281           | ★ 174400 | SNCS-63  | 4                         | 576           | 2895923  | CRSNCS-63   |
| 80                        | 2                 | 557           | ★ 174401 | SNCS-80  | 4                         | 1173          | 2895924  | CRSNCS-80   |
| 100                       | 2                 | 683           | 174402   | SNCS-100 | 3                         | 684           | 2895925  | SNCS-100-R3 |
| 125                       | 2                 | 1369          | 174403   | SNCS-125 | 3                         | 1369          | 2895926  | SNCS-125-R3 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Clevis foot LBG/LBG-...-R3

The pivot pin is secured against rotation with a spring pin.

Material:


LBG 32 ... 63: Stainless steel casting

LBG 80 ... 125: Spheroidal graphite cast iron

LBG-...-R3: High-alloy stainless steel

Free of copper and PTFE

RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | BR |            | CB   | CK<br>$\varnothing$ | D3<br>$\varnothing$ | GL | HB<br>$\varnothing$ | L2 | LE | PH | RA | TE  | UB | UL  | UR   |
|---------------------------|----|------------|------|---------------------|---------------------|----|---------------------|----|----|----|----|-----|----|-----|------|
|                           |    | ADN-...-R3 |      |                     |                     |    |                     |    |    |    |    |     |    |     |      |
| 32                        | 12 | 12         | 14.1 | 10                  | 4.8                 | 16 | 6.8                 | 35 | 24 | 32 | 20 | 42  | 28 | 56  | 36   |
| 40                        | 14 | 14         | 16.1 | 12                  | 5.8                 | 20 | 6.8                 | 39 | 26 | 36 | 26 | 44  | 30 | 58  | 41.5 |
| 50                        | 15 | 15         | 21.1 | 16                  | 5.8                 | 25 | 9.2                 | 50 | 33 | 45 | 31 | 56  | 40 | 70  | 47   |
| 63                        | 17 | 17         | 21.1 | 16                  | 7.8                 | 25 | 9.2                 | 50 | 38 | 50 | 31 | 56  | 40 | 70  | 49   |
| 80                        | 17 | 17         | 25.1 | 20                  | 7.8                 | 30 | 11                  | 60 | 49 | 63 | 36 | 70  | 50 | 89  | 55   |
| 100                       | 20 | 22         | 25.1 | 20                  | 9.8                 | 41 | 11                  | 60 | 56 | 71 | 46 | 70  | 50 | 89  | 65   |
| 125                       | 25 | 25         | 37.2 | 30                  | 11.8                | 60 | 14                  | 89 | 70 | 90 | 70 | 106 | 80 | 128 | 96   |

| For $\varnothing$<br>[mm] | Basic version     |               |              |                | R3 – High corrosion protection |               |                |                   |
|---------------------------|-------------------|---------------|--------------|----------------|--------------------------------|---------------|----------------|-------------------|
|                           | CRC <sup>1)</sup> | Weight<br>[g] | Part no.     | Type           | CRC <sup>1)</sup>              | Weight<br>[g] | Part no.       | Type              |
| 32                        | 2                 | 220           | <b>31761</b> | <b>LBG-32</b>  | 3                              | 220           | <b>2078790</b> | <b>LBG-32-R3</b>  |
| 40                        | 2                 | 300           | <b>31762</b> | <b>LBG-40</b>  | 3                              | 300           | <b>2078792</b> | <b>LBG-40-R3</b>  |
| 50                        | 2                 | 540           | <b>31763</b> | <b>LBG-50</b>  | 3                              | 540           | <b>2078794</b> | <b>LBG-50-R3</b>  |
| 63                        | 2                 | 580           | <b>31764</b> | <b>LBG-63</b>  | 3                              | 580           | <b>2078795</b> | <b>LBG-63-R3</b>  |
| 80                        | 2                 | 1050          | <b>31765</b> | <b>LBG-80</b>  | 3                              | 1050          | <b>2078797</b> | <b>LBG-80-R3</b>  |
| 100                       | 2                 | 1375          | <b>31766</b> | <b>LBG-100</b> | 3                              | 1375          | <b>2078799</b> | <b>LBG-100-R3</b> |
| 125                       | 2                 | 4140          | <b>31767</b> | <b>LBG-125</b> | 3                              | 4140          | <b>2078837</b> | <b>LBG-125-R3</b> |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Multi-position kit DPNA

Material:


Flange:

Wrought aluminium alloy

Screws: Galvanised steel

Free of copper and PTFE

RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | L2 | B1   | Max.<br>overall stroke length<br>[mm] | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type <sup>1)</sup> |
|---------------------------|----|------|---------------------------------------|-------------------|---------------|----------|--------------------|
| 12                        | 35 | 13   | 600                                   | 2                 | 28            | 537263   | DPNA-12            |
| 16                        |    |      |                                       |                   | 33            | 537264   | DPNA-16            |
| 20                        |    |      |                                       |                   | 50            | 537265   | DPNA-20            |
| 25                        |    |      |                                       |                   | 60            | 537266   | DPNA-25            |
| 32                        | 45 | 15   | 800                                   |                   | 99            | 537267   | DPNA-32            |
| 40                        |    |      |                                       |                   | 129           | 537268   | DPNA-40            |
| 50                        |    |      |                                       |                   | 16            | 537269   | DPNA-50            |
| 63                        |    |      |                                       |                   | 249           | 537270   | DPNA-63            |
| 80                        | 67 | 17   | 1000                                  |                   | 474           | 537271   | DPNA-80            |
| 100                       |    | 19.5 |                                       |                   | 712           | 537272   | DPNA-100           |

- - **Note**


The maximum total stroke length must not be exceeded when combining cylinders and multi-position kits.

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Clevis foot LBN

Material:  
Galvanised steel  
Free of copper and PTFE  
RoHS-compliant





#### Dimensions and ordering data

| For $\varnothing$ | CM   | EK<br>$\varnothing$ | FL           | GL | HB<br>$\varnothing$ | LE | MR | RG | UX | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type      |
|-------------------|------|---------------------|--------------|----|---------------------|----|----|----|----|-------------------|---------------|----------|-----------|
| 12/16             | 12.1 | 6                   | 27 +0.3/-0.2 | 13 | 5.5                 | 24 | 7  | 15 | 25 | 1                 | 40            | ★ 6058   | LBN-12/16 |
| 20/25             | 16.1 | 8                   | 30 +0.4/-0.2 | 16 | 6.6                 | 26 | 10 | 20 | 32 | 1                 | 84            | ★ 6059   | LBN-20/25 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

### Clevis foot CRLBN, stainless steel

Material:  
High-alloy steel  
Free of copper and PTFE  
RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$ | CM   | EK<br>$\varnothing$ | FL           | GL | HB<br>$\varnothing$ | LE | MR | RG | UX | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type        |
|-------------------|------|---------------------|--------------|----|---------------------|----|----|----|----|-------------------|---------------|----------|-------------|
| 12/16             | 12.1 | 6                   | 27 +0.3/-0.2 | 13 | 5.5                 | 24 | 7  | 15 | 25 | 4                 | 39            | 161862   | CRLBN-12/16 |
| 20/25             | 16.1 | 8                   | 30 +0.4/-0.2 | 16 | 6.6                 | 26 | 10 | 20 | 32 | 4                 | 82            | 161863   | CRLBN-20/25 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)



## Accessories

### Swivel flange SNCB/SNCB-...-R3


Material:

SNCB: Die-cast aluminium

SNCB-...-R3: Die-cast aluminium with  
protective coating

Free of copper and PTFE

RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$ | CB  | E                 | EK<br>$\varnothing$ | FL        | L  | MR   | TG   | UB  | XC  |
|-------------------|-----|-------------------|---------------------|-----------|----|------|------|-----|-----|
| [mm]              | H14 |                   | H9/e8               | $\pm 0.2$ |    | -0.5 |      | h14 |     |
| 32                | 26  | $45_{+0.2/-0.5}$  | 10                  | 22        | 13 | 8.5  | 32.5 | 45  | 72  |
| 40                | 28  | $54_{-0.5}$       | 12                  | 25        | 16 | 12   | 38   | 52  | 76  |
| 50                | 32  | $64_{-0.6}$       | 12                  | 27        | 16 | 12   | 46.5 | 60  | 80  |
| 63                | 40  | $75_{-0.6}$       | 16                  | 32        | 21 | 16   | 56.5 | 70  | 89  |
| 80                | 50  | $93_{-0.8}$       | 16                  | 36        | 22 | 16   | 72   | 90  | 99  |
| 100               | 60  | $110_{+0.3/-0.8}$ | 20                  | 41        | 27 | 20   | 89   | 110 | 117 |
| 125               | 70  | $131_{-0.8}$      | 25                  | 50        | 30 | 25   | 110  | 130 | 142 |


| For $\varnothing$ | Basic version     |            |          |          | R3 – High corrosion protection |            |          |             |
|-------------------|-------------------|------------|----------|----------|--------------------------------|------------|----------|-------------|
|                   | CRC <sup>1)</sup> | Weight [g] | Part no. | Type     | CRC <sup>1)</sup>              | Weight [g] | Part no. | Type        |
| 32                | 1                 | 103        | ★ 174390 | SNCB-32  | 3                              | 100        | 176944   | SNCB-32-R3  |
| 40                | 1                 | 155        | ★ 174391 | SNCB-40  | 3                              | 151        | 176945   | SNCB-40-R3  |
| 50                | 1                 | 233        | ★ 174392 | SNCB-50  | 3                              | 228        | 176946   | SNCB-50-R3  |
| 63                | 1                 | 375        | ★ 174393 | SNCB-63  | 3                              | 371        | 176947   | SNCB-63-R3  |
| 80                | 1                 | 636        | ★ 174394 | SNCB-80  | 3                              | 632        | 176948   | SNCB-80-R3  |
| 100               | 1                 | 1035       | 174395   | SNCB-100 | 3                              | 986        | 176949   | SNCB-100-R3 |
| 125               | 1                 | 1860       | 174396   | SNCB-125 | 3                              | 1776       | 176950   | SNCB-125-R3 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Trunnion flange ZNCF/CRZNG

Material:  
 ZNCF: Stainless steel casting  
 CRZNG: Electropolished stainless steel casting  
 Free of copper and PTFE  
 RoHS-compliant



#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | C2) | C3) | TD<br>$\varnothing$<br>e9 | TK | TL | TM  | US  | XH | XL   |
|---------------------------|-----|-----|---------------------------|----|----|-----|-----|----|------|
| 32                        | 71  | 86  | 12                        | 16 | 12 | 50  | 45  | 2  | 58   |
| 40                        | 87  | 105 | 16                        | 20 | 16 | 63  | 54  | 4  | 61.1 |
| 50                        | 99  | 117 | 16                        | 24 | 16 | 75  | 64  | 4  | 64.7 |
| 63                        | 116 | 136 | 20                        | 24 | 20 | 90  | 75  | 4  | 68.5 |
| 80                        | 136 | 156 | 20                        | 28 | 20 | 110 | 93  | 5  | 76.9 |
| 100                       | 164 | 189 | 25                        | 38 | 25 | 132 | 110 | 10 | 95   |
| 125                       | 192 | 217 | 25                        | 50 | 25 | 160 | 131 | 14 | 117  |

| For $\varnothing$<br>[mm] | Basic version     |               |          |          | R3 – High corrosion protection |               |          |           |
|---------------------------|-------------------|---------------|----------|----------|--------------------------------|---------------|----------|-----------|
|                           | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type     | CRC <sup>1)</sup>              | Weight<br>[g] | Part no. | Type      |
| 32                        | 2                 | 150           | 174411   | ZNCF-32  | 4                              | 150           | 161852   | CRZNG-32  |
| 40                        | 2                 | 285           | 174412   | ZNCF-40  | 4                              | 285           | 161853   | CRZNG-40  |
| 50                        | 2                 | 473           | 174413   | ZNCF-50  | 4                              | 473           | 161854   | CRZNG-50  |
| 63                        | 2                 | 687           | 174414   | ZNCF-63  | 4                              | 687           | 161855   | CRZNG-63  |
| 80                        | 2                 | 1296          | 174415   | ZNCF-80  | 4                              | 1296          | 161856   | CRZNG-80  |
| 100                       | 2                 | 2254          | 174416   | ZNCF-100 | 4                              | 2254          | 161857   | CRZNG-100 |
| 125                       | 2                 | 3484          | 174417   | ZNCF-125 | 4                              | 3484          | 185362   | CRZNG-125 |

1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Trunnion support LNZG



Material:

Trunnion support: Anodised aluminium

Plain bearing: Plastic

Free of copper and PTFE

RoHS-compliant








#### Dimensions and ordering data

| For $\varnothing$<br>[mm] | CR<br>$\varnothing$<br>D11 | DA<br>$\varnothing$<br>H13 | FK<br>$\varnothing$<br>$\pm 0.1$ | FN | FS   | H1   | HB<br>$\varnothing$<br>H13 | KE  | NH   | TH<br>$\pm 0.2$ | UL | CRC <sup>1)</sup> | Weight<br>[g] | Part no. | Type         |
|---------------------------|----------------------------|----------------------------|----------------------------------|----|------|------|----------------------------|-----|------|-----------------|----|-------------------|---------------|----------|--------------|
| 32                        | 12                         | 11                         | 15                               | 30 | 10.5 | 15   | 6.6                        | 6.8 | 18   | 32              | 46 | 2                 | 83            | 32959    | LNZG-32      |
| 40, 50                    | 16                         | 15                         | 18                               | 36 | 12   | 18   | 9                          | 9   | 21   | 36              | 55 | 2                 | 129           | 32960    | LNZG-40/50   |
| 63, 80                    | 20                         | 18                         | 20                               | 40 | 13   | 20   | 11                         | 11  | 23   | 42              | 65 | 2                 | 178           | 32961    | LNZG-63/80   |
| 100, 125                  | 25                         | 20                         | 25                               | 50 | 16   | 24.5 | 14                         | 13  | 28.5 | 50              | 75 | 2                 | 306           | 32962    | LNZG-100/125 |





1) More information [www.festo.com/x/topic/crc](http://www.festo.com/x/topic/crc)

## Accessories

### Ordering data – Piston rod attachments



| Designation                                                                        | For ø          | Part no. | Type            |
|------------------------------------------------------------------------------------|----------------|----------|-----------------|
| <b>Rod eye SGS</b>                                                                 |                |          |                 |
|    | 16             | ★ 9254   | SGS-M6          |
|                                                                                    | 20, 25         | ★ 9255   | SGS-M8          |
|                                                                                    | 32, 40         | ★ 9261   | SGS-M10x1.25    |
|                                                                                    | 50, 63         | ★ 9262   | SGS-M12x1.25    |
|                                                                                    | 80, 100        | ★ 9263   | SGS-M16x1.5     |
|                                                                                    | 125            | ★ 9264   | SGS-M20x1.5     |
| <b>Rod clevis SG</b>                                                               |                |          |                 |
|    | 12             | –        |                 |
|                                                                                    | 16             | ★ 3110   | SG-M6           |
|                                                                                    | 20, 25         | ★ 3111   | SG-M8           |
|                                                                                    | 32, 40         | ★ 6144   | SG-M10x1.25     |
|                                                                                    | 50, 63         | ★ 6145   | SG-M12x1.25     |
|                                                                                    | 80, 100        | ★ 6146   | SG-M16x1.5      |
|    | 125            | ★ 6147   | SG-M20x1.5      |
|                                                                                    |                |          |                 |
| <b>Coupling piece KSG</b>                                                          |                |          |                 |
|  | 12, 16, 20, 25 | –        |                 |
|                                                                                    | 32, 40         | 32963    | KSG-M10x1.25    |
|                                                                                    | 50, 63         | 32964    | KSG-M12x1.25    |
|                                                                                    | 80, 100        | 32965    | KSG-M16x1.5     |
|                                                                                    | 125            | 32966    | KSG-M20x1.5     |
|                                                                                    |                |          |                 |
| <b>Adapter AD</b>                                                                  |                |          |                 |
|  | 12             | –        |                 |
|                                                                                    | 16             | 157328   | AD-M6-M5        |
|                                                                                    |                | 157329   | AD-M6-1/8       |
|                                                                                    |                | 157330   | AD-M6-1/4       |
|                                                                                    | 20             | 157331   | AD-M8-1/8       |
|                                                                                    | 25             | 157332   | AD-M8-1/4       |
|                                                                                    | 32             | 157333   | AD-M10x1.25-1/8 |
|                                                                                    | 40             | 157334   | AD-M10x1.25-1/4 |
|                                                                                    | 50             | 160256   | AD-M12x1.25-1/4 |
|                                                                                    | 63             | 160257   | AD-M12x1.25-3/8 |

Datasheets → Internet: piston rod attachment


| Designation                                                                         | For ø          | Part no. | Type         |
|-------------------------------------------------------------------------------------|----------------|----------|--------------|
| <b>Rod clevis SGA for rod eye SGS</b>                                               |                |          |              |
|    | 12, 16, 20, 25 | –        |              |
|                                                                                     | 32, 40         | 32954    | SGA-M10x1.25 |
|                                                                                     | 50, 63         | 10767    | SGA-M12x1.25 |
|                                                                                     | 80, 100        | 10768    | SGA-M16x1.5  |
|                                                                                     | 125            | 10769    | SGA-M20x1.5  |
|                                                                                     |                |          |              |
| <b>Self-aligning rod coupler FK</b>                                                 |                |          |              |
|    | 12             | 30984    | FK-M5        |
|                                                                                     | 16             | ★ 2061   | FK-M6        |
|                                                                                     | 20, 25         | ★ 2062   | FK-M8        |
|                                                                                     | 32, 40         | ★ 6140   | FK-M10x1.25  |
|                                                                                     | 50, 63         | ★ 6141   | FK-M12x1.25  |
|                                                                                     | 80, 100        | ★ 6142   | FK-M16x1.5   |
|                                                                                     | 125            | ★ 6143   | FK-M20x1.5   |
|                                                                                     |                |          |              |
| <b>Self-aligning rod coupler DARP</b>                                               |                |          |              |
|    | 12             | 8170112  | DARP-M5-F    |
|                                                                                     | 16             | 8170115  | DARP-M6-F    |
|                                                                                     | 20, 25         | 8170116  | DARP-M8-F    |
|                                                                                     | 32, 40         | 8170119  | DARP-M10P-F  |
|                                                                                     | 50, 63         | 8170120  | DARP-M12P-F  |
|                                                                                     | 80, 100        | 8170121  | DARP-M16P-F  |
|                                                                                     | 125            | 8170124  | DARP-M20P-F  |
|                                                                                     |                |          |              |
| <b>Coupling piece KSZ</b>                                                           |                |          |              |
|  | 12             | –        |              |
|                                                                                     | 16             | 36123    | KSZ-M6       |
|                                                                                     | 20, 25         | 36124    | KSZ-M8       |
|                                                                                     | 32, 40         | 36125    | KSZ-M10x1.25 |
|                                                                                     | 50, 63         | 36126    | KSZ-M12x1.25 |
|                                                                                     | 80, 100        | 36127    | KSZ-M16x1.5  |
|                                                                                     | 125            | 36128    | KSZ-M20x1.5  |
|                                                                                     |                |          |              |

## Accessories


### Ordering data – Piston-rod attachments, corrosion-resistant

| Designation                                                                       | For ø   | Part no. | Type           |
|-----------------------------------------------------------------------------------|---------|----------|----------------|
| <b>Rod eye CRSGS</b>                                                              |         |          |                |
|  | 12      | –        |                |
|                                                                                   | 16      | 195580   | CRSGS-M6       |
|                                                                                   | 20, 25  | 195581   | CRSGS-M8       |
|                                                                                   | 32, 40  | 195582   | CRSGS-M10x1.25 |
|                                                                                   | 50, 63  | 195583   | CRSGS-M12x1.25 |
|                                                                                   | 80, 100 | 195584   | CRSGS-M16x1.5  |
|                                                                                   | 125     | 195585   | CRSGS-M20x1.5  |
| <b>Self-aligning rod coupler CRFK</b>                                             |         |          |                |
|  | 32, 40  | 2305778  | CRFK-M10x1.25  |
|                                                                                   | 50, 63  | 2305779  | CRFK-M12x1.25  |
|                                                                                   | 80, 100 | 2490673  | CRFK-M16x1.5   |
|                                                                                   | 125     | 2545677  | CRFK-M20x1.5   |


Datasheets → Internet: piston rod attachment

| Designation                                                                       | For ø   | Part no. | Type          |
|-----------------------------------------------------------------------------------|---------|----------|---------------|
| <b>Rod clevis CRSG</b>                                                            |         |          |               |
|  | 12      | –        |               |
|                                                                                   | 16, 20  | 13567    | CRSG-M6       |
|                                                                                   | 20, 25  | 13568    | CRSG-M8       |
|                                                                                   | 32, 40  | 13569    | CRSG-M10x1.25 |
|                                                                                   | 50, 63  | 13570    | CRSG-M12x1.25 |
|                                                                                   | 80, 100 | 13571    | CRSG-M16x1.5  |
|                                                                                   | 125     | 13572    | CRSG-M20x1.5  |


### Ordering data – Mounting components

| Designation                                                                       | For ø   | Part no. | Type    |
|-----------------------------------------------------------------------------------|---------|----------|---------|
| <b>Right-angle clevis foot LQG for rod eye SGS</b>                                |         |          |         |
|  | 32, 40  | 31761    | LBG-32  |
|                                                                                   | 50, 63  | 31762    | LBG-40  |
|                                                                                   | 80, 100 | 31763    | LBG-50  |
|                                                                                   |         | 31764    | LBG-63  |
|                                                                                   | 125     | 31765    | LBG-80  |
|                                                                                   |         | 31766    | LBG-100 |

Datasheets → Internet: clevis foot


| Designation                                                                       | For ø   | Part no. | Type    |
|-----------------------------------------------------------------------------------|---------|----------|---------|
| <b>Right-angle clevis foot LQG for rod eye SGS</b>                                |         |          |         |
|  | 32, 40  | 31768    | LQG-32  |
|                                                                                   | 50, 63  | 31769    | LQG-40  |
|                                                                                   | 80, 100 | 31770    | LQG-50  |
|                                                                                   |         | 31771    | LQG-63  |
|                                                                                   | 125     | 31772    | LQG-80  |
|                                                                                   |         | 31773    | LQG-100 |

### Ordering data – Mounting components, high corrosion protection


| Designation                                                                         | For ø   | Part no. | Type       |
|-------------------------------------------------------------------------------------|---------|----------|------------|
| <b>Clevis foot LBG-R3 for rod eye CRSGS</b>                                         |         |          |            |
|  | 32, 40  | 2078790  | LBG-32-R3  |
|                                                                                     | 50, 63  | 2078792  | LBG-40-R3  |
|                                                                                     | 80, 100 | 2078794  | LBG-50-R3  |
|                                                                                     |         | 2078795  | LBG-63-R3  |
|                                                                                     | 125     | 2078797  | LBG-80-R3  |
|                                                                                     |         | 2078799  | LBG-100-R3 |


Datasheets → Internet: clevis foot



### Ordering data – One-way flow control valves


| Connection                                                                          | For ø                   | For tubing O.D. | Material     | Part no.                    | Type            |
|-------------------------------------------------------------------------------------|-------------------------|-----------------|--------------|-----------------------------|-----------------|
|                                                                                     |                         |                 |              | Datasheets → Internet: grla |                 |
| <b>For exhaust air</b>                                                              |                         |                 |              |                             |                 |
|  | 12, 16, 20, 25          | 3               | Metal design | ★ 193137                    | GRLA-M5-QS-3-D  |
|                                                                                     |                         | 4               |              | ★ 193138                    | GRLA-M5-QS-4-D  |
|                                                                                     |                         | 6               |              | ★ 193139                    | GRLA-M5-QS-6-D  |
|                                                                                     | 32, 40, 50, 63, 80, 100 | 3               |              | ★ 193142                    | GRLA-1/8-QS-3-D |
|                                                                                     |                         | 4               |              | ★ 193143                    | GRLA-1/8-QS-4-D |
|                                                                                     |                         | 6               |              | ★ 193144                    | GRLA-1/8-QS-6-D |
|                                                                                     |                         | 8               |              | ★ 193145                    | GRLA-1/8-QS-8-D |
|                                                                                     |                         | 125             |              | 6                           | ★ 193146        |
|                                                                                     | 8                       | ★ 193147        |              | GRLA-1/4-QS-8-D             |                 |
|                                                                                     | 10                      | ★ 193148        |              | GRLA-1/4-QS-10-D            |                 |

## Accessories









| Ordering data – One-way flow control valves                                      |                         |                 |              |          | Datasheets → Internet: grlz |            |  |
|----------------------------------------------------------------------------------|-------------------------|-----------------|--------------|----------|-----------------------------|------------|--|
|                                                                                  | Connection              |                 | Material     | Part no. | Type                        |            |  |
|                                                                                  | For $\varnothing$       | For tubing O.D. |              |          |                             |            |  |
| <b>For supply air</b>                                                            |                         |                 |              |          |                             |            |  |
|  | 12, 16, 20, 25          | 3               | Metal design | ★ 193153 | GRLZ-M5-QS-3-D              |            |  |
|                                                                                  |                         | 4               |              | ★ 193154 | GRLZ-M5-QS-4-D              |            |  |
|                                                                                  |                         | 6               |              | ★ 193155 | GRLZ-M5-QS-6-D              |            |  |
|                                                                                  | 32, 40, 50, 63, 80, 100 | 3               |              | ★ 193156 | GRLZ-1/8-QS-3-D             |            |  |
|                                                                                  |                         | 4               |              | ★ 193157 | GRLZ-1/8-QS-4-D             |            |  |
|                                                                                  |                         | 6               |              | ★ 193158 | GRLZ-1/8-QS-6-D             |            |  |
|                                                                                  |                         | 8               |              | ★ 193159 | GRLZ-1/8-QS-8-D             |            |  |
|                                                                                  | 125                     | –               |              |          | 151195                      | GRLZ-1/4-B |  |

| Ordering data – One-way flow control valves for cylinders ADNH and ADN           |                   |                 |              |          | Datasheets → Internet: grla |  |
|----------------------------------------------------------------------------------|-------------------|-----------------|--------------|----------|-----------------------------|--|
|                                                                                  | Connection        |                 | Material     | Part no. | Type                        |  |
|                                                                                  | For $\varnothing$ | For tubing O.D. |              |          |                             |  |
| <b>For exhaust air</b>                                                           |                   |                 |              |          |                             |  |
|  | 25, 40            | 3               | Metal design | 193137   | GRLA-M5-QS-3-D              |  |
|                                                                                  |                   | 4               |              | 193138   | GRLA-M5-QS-4-D              |  |
|                                                                                  | 63, 100           | 4               |              | 193143   | GRLA-1/8-QS-4-D             |  |
|                                                                                  |                   | 6               |              | 193144   | GRLA-1/8-QS-6-D             |  |
|                                                                                  |                   | 8               |              | 193145   | GRLA-1/8-QS-8-D             |  |

| Ordering data – Proximity switch for T-slot, magneto-resistive                     |                                                                                |                  |                       |                  |          | Datasheets → Internet: smt |  |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|------------------|-----------------------|------------------|----------|----------------------------|--|
|                                                                                    | Type of mounting                                                               | Switching output | Electrical connection | Cable length [m] | Part no. | Type                       |  |
| <b>N/O</b>                                                                         |                                                                                |                  |                       |                  |          |                            |  |
|  | Inserted in the slot from above, flush with the cylinder profile, short design | PNP              | Cable, 3-core         | 2.5              | ★ 574335 | SMT-8M-A-PS-24V-E-2.5-OE   |  |
|                                                                                    |                                                                                |                  | Plug M8x1, 3-pin      | 0.3              | ★ 574334 | SMT-8M-A-PS-24V-E-0.3-M8D  |  |
|                                                                                    |                                                                                |                  | Plug M12x1, 3-pin     | 0.3              | ★ 574337 | SMT-8M-A-PS-24V-E-0.3-M12  |  |
|                                                                                    |                                                                                | NPN              | Cable, 3-core         | 2.5              | ★ 574338 | SMT-8M-A-NS-24V-E-2.5-OE   |  |
|                                                                                    |                                                                                |                  | Plug M8x1, 3-pin      | 0.3              | ★ 574339 | SMT-8M-A-NS-24V-E-0.3-M8D  |  |
| <b>N/C</b>                                                                         |                                                                                |                  |                       |                  |          |                            |  |
|  | Inserted in the slot from above, flush with the cylinder profile, short design | PNP              | Cable, 3-core         | 7.5              | ★ 574340 | SMT-8M-A-PO-24V-E-7.5-OE   |  |

| Ordering data – Proximity switch for T-slot, magneto-resistive                     |                                   |                                                       |                  |                  |          | Datasheets → Internet: smt |  |
|------------------------------------------------------------------------------------|-----------------------------------|-------------------------------------------------------|------------------|------------------|----------|----------------------------|--|
|                                                                                    | Type of mounting                  | Electrical connection, outlet direction of connection | Switching output | Cable length [m] | Part no. | Type                       |  |
| <b>N/O</b>                                                                         |                                   |                                                       |                  |                  |          |                            |  |
|  | Inserted into the slot lengthwise | Cable, 3-wire, crosswise                              | PNP              | 2.5              | 547859   | SMT-8G-PS-24V-E-2.5Q-OE    |  |
|                                                                                    |                                   | Plug M8x1, 3-pin, crosswise                           |                  | 0.3              | 547860   | SMT-8G-PS-24V-E-0.3Q-M8D   |  |
|                                                                                    |                                   | Cable, 3-wire, crosswise                              | NPN              | 2.5              | 8065028  | SMT-8G-NS-24V-E-2.5Q-OE    |  |
|                                                                                    |                                   | Plug M8x1, 3-pin, crosswise                           |                  | 0.3              | 8065027  | SMT-8G-NS-24V-E-0.3Q-M8D   |  |

## Accessories

| Ordering data – Proximity switches for T-slot, magnetic reed                        |                                                                  |                              |                       |                  |          | Datasheets → Internet: sme  |  |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------|------------------------------|-----------------------|------------------|----------|-----------------------------|--|
|                                                                                     | Type of mounting                                                 | Switching output             | Electrical connection | Cable length [m] | Part no. | Type                        |  |
| <b>N/O</b>                                                                          |                                                                  |                              |                       |                  |          |                             |  |
|    | Inserted in the slot from above, flush with the cylinder profile | Contacting                   | Cable, 3-core         | 2.5              | ★ 543862 | SME-8M-DS-24V-K-2.5-OE      |  |
|                                                                                     |                                                                  |                              |                       | 5.0              | ★ 543863 | SME-8M-DS-24V-K-5.0-OE      |  |
|                                                                                     |                                                                  |                              | Plug M8x1, 3-pin      | 2.5              | ★ 543872 | SME-8M-ZS-24V-K-2.5-OE      |  |
|                                                                                     |                                                                  |                              |                       | 0.3              | ★ 543861 | SME-8M-DS-24V-K-0.3-M8D     |  |
|    | Inserted in the slot lengthwise, flush with the cylinder profile | Contacting                   | Cable, 3-core         | 2.5              | 150855   | SME-8-K-LED-24              |  |
|                                                                                     |                                                                  |                              |                       | 0.3              | 150857   | SME-8-S-LED-24              |  |
| <b>N/C</b>                                                                          |                                                                  |                              |                       |                  |          |                             |  |
|    | Inserted in the slot lengthwise, flush with the cylinder profile | Contacting                   | Cable, 3-core         | 7.5              | 160251   | SME-8-O-K-LED-24            |  |
| Ordering data – Connecting cables                                                   |                                                                  |                              |                       |                  |          | Datasheets → Internet: nebu |  |
|                                                                                     | Electrical connection, left                                      | Electrical connection, right |                       | Cable length [m] | Part no. | Type                        |  |
|    | Straight socket, M8x1, 3-pin                                     | Cable, open end, 3-core      |                       | 2.5              | ★ 541333 | NEBU-M8G3-K-2.5-LE3         |  |
|                                                                                     |                                                                  |                              |                       | 5                | ★ 541334 | NEBU-M8G3-K-5-LE3           |  |
|                                                                                     | Straight socket, M12x1, 5-pin                                    | Cable, open end, 3-core      |                       | 2.5              | ★ 541363 | NEBU-M12G5-K-2.5-LE3        |  |
|                                                                                     |                                                                  |                              |                       | 5                | ★ 541364 | NEBU-M12G5-K-5-LE3          |  |
|   | Angled socket, M8x1, 3-pin                                       | Cable, open end, 3-core      |                       | 2.5              | ★ 541338 | NEBU-M8W3-K-2.5-LE3         |  |
|                                                                                     |                                                                  |                              |                       | 5                | ★ 541341 | NEBU-M8W3-K-5-LE3           |  |
|                                                                                     | Angled socket, M12x1, 5-pin                                      | Cable, open end, 3-core      |                       | 2.5              | 541367   | NEBU-M12W5-K-2.5-LE3        |  |
|                                                                                     |                                                                  |                              |                       | 5                | 541370   | NEBU-M12W5-K-5-LE3          |  |
| Ordering data – Proximity switch, cuboid shape, pneumatic                           |                                                                  |                              |                       |                  |          | Datasheets → Internet: smpo |  |
|                                                                                     | Pneumatic connection                                             |                              |                       |                  | Part no. | Type                        |  |
| <b>3/2-way valve, normally closed</b>                                               |                                                                  |                              |                       |                  |          |                             |  |
|  | Female thread M5                                                 |                              |                       |                  | 178563   | SMPO-8E                     |  |
| Ordering data – Mounting kit for proximity switch SMPO-8E                           |                                                                  |                              |                       |                  |          | Datasheets → Internet: smb  |  |
|                                                                                     | Mounting                                                         |                              |                       |                  | Part no. | Type                        |  |
|  | Clamped in T-slot                                                |                              |                       |                  | 178230   | SMB-8E                      |  |
| Ordering data – Slot cover for T-slot                                               |                                                                  |                              |                       |                  |          |                             |  |
|                                                                                     | Mounting                                                         | Length                       |                       |                  | Part no. | Type                        |  |
|  | Insertable                                                       | 2x 0.5 m                     |                       |                  | 151680   | ABP-5-S                     |  |

# Festo - Your Partner in Automation



**1 Festo Inc.**  
5300 Explorer Drive  
Mississauga, ON L4W 5G4  
Canada

**Festo Customer Interaction Center**  
Tel: 1 877 463 3786  
Fax: 1 877 393 3786  
Email: [customer.service.ca@festo.com](mailto:customer.service.ca@festo.com)

**2 Festo Pneumatic**  
Av. Ceylán 3,  
Col. Tequesquináhuac  
54020 Tlalneantla,  
Estado de México

**Multinational Contact Center**  
01 800 337 8669  
[ventas.mexico@festo.com](mailto:ventas.mexico@festo.com)

**3 Festo Corporation**  
1377 Motor Parkway  
Suite 310  
Islandia, NY 11749

**Festo Customer Interaction Center**  
1 800 993 3786  
1 800 963 3786  
[customer.service.us@festo.com](mailto:customer.service.us@festo.com)

**4 Regional Service Center**  
7777 Columbia Road  
Mason, OH 45040

Connect with us



[www.festo.com/socialmedia](http://www.festo.com/socialmedia)



[www.festo.com](http://www.festo.com)

Subject to change